LAB EXERCISE – 3

(1)//Implementation of NFA for texts i.e Example word: Theory

```
#include<stdio.h>
int current = 0;
void q0(char c)
{
       if(c=='T' || c=='t') current=1;
       else current=-1;
}
void q1(char c)
{
      if(c=='H'|| c=='h') current= 2;
      else current = -1;
}
void q2(char c)
{
      if(c=='E' || c=='e') current = 3;
      else current = -1;
}
void q3(char c)
{
      if(c=='O' | | c=='o') current = 4;
      else current = -1;
```

```
}
void q4(char c)
{
      if(c=='R' | | c=='r') current = 5;
      else current = -1;
}
void q5(char c)
{
      if(c=='Y' || c=='y') current = 6;
      else current = -1;
}
void q6(char c)
{
      current = -1;
}
int main()
{
  char str[20],c;
      int i;
      printf("Enter your word: ");
      scanf("%s",&str);
      for(i=0;str[i]!='\0';i++)
      {
```

```
c=str[i];
switch(current)
{
      case 0:
             q0(c);
             break;
      case 1:
             q1(c);
             break;
      case 2:
             q2(c);
             break;
      case 3:
             q3(c);
             break;
      case 4:
            q4(c);
             break;
      case 5:
             q5(c);
             break;
      case 6:
             q6(c);
      default:
```

```
break;
            }
      }
      if(current==6)
      {
            printf("\nYour word is accepted.");
      }
      else{
            printf("\nYour word is not accepted.");
      }
      return 0;
}
(2)//Implementing DFA of language (a+aa*b)*
#include<stdio.h>
#include<conio.h>
#include<strings.h>
#include<stdlib.h>
void main() {
 int table[2][2],i,j,l,status=0,success;
 char input[100];
 printf("Implementing DFA of language (a+aa*b)* Enter Input String:");
 table[0][0]=1;
 table[0][1]=-1;
```

```
table[1][0]=1;
 table[1][1]=0;
 scanf("%s",input);
 l=strlen(input);
 for (i=0;i<l;i++) {
   if(input[i]!='a'&&input[i]!='b') {
     printf("The entered Value is wrong");
     getch();
     exit(0);
   }
   if(input[i]=='a')
    status=table[status][0];
   else
    status=table[status][1];
   if(status==-1) {
     printf("String not Accepted");
     break;
   }
 }
 if(i==1)
   printf("String Accepted");
 getch();
}
```