RAJALAKSHMI ENGINEERING COLLEGE

SUJITH S 251801341-2025-AIDS

M2

Started on	Thursday, 6 August 2026, 10:11 AM
State	Finished
Completed on	Thursday, 6 August 2026, 10:46 AM
Time taken	34 mins 59 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Scanned with OKEN Scanner

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void function (int n)
{
    int i= 1;
```

```
    int s =1;
```

```
    while(s <= n)
    {
         i++;
         s += i;
     }
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

For example:

Input	Result
9	12

Answer: (penalty regime: 0 %)

```c
#include<stdio.h>
int count=0;
void function(int n){

    int i=1;
    count++;
    int s=1;
    count++;
    while(s<=n){
    count++;
    i++;
    count++;
    s+=i;
    count++;
    }
    count++;
}

int main(){
    int n;
    scanf("%d",&n);
    function(n);
    printf("%d",count);
}
```


Scanned with OKEN Scanner

	Input	Expected	Got	
	9	12	12	
	4	9	9	

Passed all tests!

Correct

Marks for this submission: 1.00/1.00.

Back to Course

Scanned with OKEN Scanner

RAJALAKSHMI ENGINEERING COLLEGE

SUJITH S 251801341-2025-AIDS

M2

Started on	Thursday, 6 August 2026, 10:47 AM
State	Finished
Completed on	Thursday, 6 August 2026, 11:01 AM
Time taken	14 mins 18 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Scanned with OKEN Scanner

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void func(int n)
{
    if(n==1)
    {
      printf("*");
    }
    else
    {
     for(int i=1; i<=n; i++)
     {
       for(intj=1; j<=n; j++)
       {
          printf("*");
          break;
       }
     }
   }
 }
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
int count=0;
void func(int n){
    count++;
    if(n==1){

    //    printf("*");
    }
    else{
        for(int i=1;i<=n;i++){
            count++;
            for(int j=1;j<=n;j++){
                count++;
            //    printf("*");
            count++;
            //  printf("*");
            count++;
                break;
            }
            count++;
        }
        count++;
    }
}
int main(){

    int n;
    scanf("%d",&n);
```


Scanned with OKEN Scanner

```
29      printf("%d",count);
30  }
```

	Input	Expected	Got	
				2	12	12				
	1000	5002	5002	
	143	717	717	

Passed all tests! |

Correct

Marks for this submission: 1.00/1.00.

Back to Course

Scanned with OKEN Scanner

RAJALAKSHMI ENGINEERING COLLEGE

SUJITH S 251801341-2025-AIDS

M2

Started on	Thursday, 6 August 2026, 11:02 AM
State	Finished
Completed on	Thursday, 6 August 2026, 11:08 AM
Time taken	6 mins 26 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Scanned with OKEN Scanner

Question 1 | Correct Mark 1.00 out of 1.00

Converttheffollowing algorithm into a program and find its time complexity using counter method.

```
Factor(num){
{
   for (i = 1; i <= num;++i)
   {
    if(num%i==0)
       {
         printf("%d ", i);
       }
    }
 }
```

Note: No need of counter increment for declarations and scanf() and counter variable printf() statement.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```c
#include<stdio.h>
int count=0;
void Factor(int num){
    for(int i=1;i<=num;++i){
        count++;
        count++;
        if(num%i==0){
            count++;
        //    printf("%d ",i);
        }
    }
    count++;
}
int main(){
    int num;
    scanf("%d",&num);
    Factor(num);
    printf("%d",count);
}
```

	Input	Expected	Got	
				12	31	31				
	25	54	54	
	4	12	12	

Scanned with OKEN Scanner

Passed all tests!

Correct

Marks for this submission: 1.00/1.00.

Back to Course

Scanned with OKEN Scanner

RAJALAKSHMI ENGINEERING COLLEGE

SUJITH S 251801341-2025-AIDS

M2

Started on	Thursday, 6 August 2026, 11:08 AM
State	Finished
Completed on	Thursday, 6 August 2026, 11:12 AM
Time taken	3 mins 31 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Scanned with OKEN Scanner

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time

complexity using counter method.

```
voidfunction(int n)
{
    int c= 0;
    for(int i=n/2; i<n; i++)
        for(int j=1; j<n; j = 2 * j)
            for(int k=1; k<n; k = k * 2)
                c++;
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```c
#include<stdio.h>
int count=0;
void function(int n){
    int c=0;
    count++;
    for(int i=n/2;i<n;i++){
        count++;
        for(int j=1;j<n;j=2*j){
            count++;
            for(int k=1;k<n;k=k*2){
                count++;
                c++;
                count++;
            }
            count++;
        }
        count++;
    }
    count++;
}
int main(){

    int n;
    scanf("%d",&n);
    function(n);
    printf("%d",count);
}
```

	Input	Expected	Got	
✓	4	30	30	✓
	10	212	212	

Scanned with OKEN Scanner

Passed all tests!

Correct

Marks for this submission: 1.00/1.00.

Back to Course

Scanned with OKEN Scanner

RAJALAKSHMI ENGINEERING COLLEGE

SUJITH S 251801341-2025-AIDS

M2

Started on	Thursday, 6 August 2026, 11:12 AM
State	Finished
Completed on	Thursday, 6 August 2026, 11:16 AM
Time taken	3 mins 57 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Scanned with OKEN Scanner

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using counter method.

```
void reverse(int n)
{
   int rev =0,remainder;
   while(n!=0)
    {
        remainder =n % 10;
        rev = rev * 10 + remainder;
        n/=10;

    }
print(rev);
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```c
#include<stdio.h>
int count=0;
void reverse(int n){
    int rev=0,remainder;
    count++;
    while(n!=0){
    count++;
    remainder=n%10;
    count++;
    rev = rev*10 + remainder;
    count++;
    n/=10;
    count++;
    }
    count++;
    // print(rev);
    count++;
}
int main(){

    int n;
    scanf("%d",&n);
    reverse(n);
    printf("%d",count);
}
```

	Input	Expected	Got	
✓	12	11	11	✓
	1234	19	19	

Scanned with OKEN Scanner

Passed all tests!

Correct

Marks for this submission: 1.00/1.00.

Back to Course

Scanned with OKEN Scanner