ASCENDING ORDER

EXP NO: 12

AIM:
To compute ascending order of an array using 8085 processor.

ALGORITHM:

1)   Initialize HL pair as memory pointer.

2)   Get the count at memory and load it into C register

3)   Copy it in D register (for bubble sort (N-1)) times required).

4)   Get the first value in A register.

5)   Compare it with the value at next location.

6)   If they are out of order, exchange the contents of A register

and memory.

7) Decrement D register content by 1

8) Repeat step 5 and 7 till the value in D register become zero.

9) Decrement the C register content by 1.

10) Repeat steps 3 to 9 till the value in C register becomes zero.

PROGRAM:

LOOP: LXI H,3500

MVI D,00

MVI C,05

LOOP1: MOV A,M

INX H

CMP M

JC LOOP2

MOV B,M

```
MOV M,A

DCX H

MOV M,B

INX H

MVI D,01

LOOP2: DCR C

JNZ LOOP1

MOV A,D

RRC

JC LOOP

HLT
```

INPUT:

⚙ Data	⚙ Stack	🔤 KeyPad	**Memory**	I/O Port

Start 3500   OK

Address (Hex)	Address	Data
0DAC	3500	0
0DAD	3501	1
0DAE	3502	2
0DAF	3503	3
0DB0	3504	4
0DB1	3505	6
0DB2	3506	0

OUTPUT:

RESULT: Thus
the program was executed successfully using 8085 processor simulator.