

```
R1#  
R1#  
R1#  
R1#  
R1#conf terr  
      ^  
% Invalid input detected at '^' marker.  
  
R1#conf ter  
Enter configuration commands, one per line.  End with CNTL/Z.  
R1(config)#  
*Aug 18 16:46:45.188: %LINK-3-UPDOWN: Interface Ethernet0/2, changed state to  
down  
*Aug 18 16:46:45.197: %LINK-3-UPDOWN: Interface Ethernet0/3, changed state to  
down  
*Aug 18 16:46:46.188: %LINEPROTO-5-UPDOWN: Line protocol on Interface Ethernet  
0/2, changed state to down  
*Aug 18 16:46:46.201: %LINEPROTO-5-UPDOWN: Line protocol on Interface Ethernet  
0/3, changed state to down  
R1(config)#router eigrp 10  
R1(config-router)#network 10.0.0.0  
R1(config-router)#network 20.0.0.0  
R1(config-router)#exit  
R1(config)#
```

```
R2#  
R2#  
R2#  
R2#conf ter  
Enter configuration commands, one per line.  End with CNTL/Z.  
R2(config)#router eigrp 10  
R2(config-router)#network 20.0.0.0  
R2(config-router)#networ  
*Aug 18 16:48:11.620: %DUAL-5-NBRCHANGE: EIGRP-IPv4 10: Neighbor 20.0.0.1 (Ether  
net0/0) is up: new adjacency  
R2(config-router)#network 30.0.0.0  
R2(config-router)#exit  
R2(config)#
```



```
R3#
R3#
R3#
R3#
R3#
R3#
R3#conf ter
Enter configuration commands, one per line.  End with CNTL/Z.
R3(config)#router eigrp 10
R3(config-router)#network 30.0.0.0
R3(config-router)#net
*Aug 18 16:48:54.710: %DUAL-5-NBRCHANGE: EIGRP-IPv4 10: Neighbor 30.0.0.1 (Ether
net0/1) is up: new adjacency
R3(config-router)#network 40.0.0.0
      ^
% Invalid input detected at '^' marker.

R3(config-router)#network 40.0.0.0
R3(config-router)#
```



R1



```
R1#show
*Aug 18 16:49:45.325: %SYS-5-CONFIG_I: Configured from console by console
R1#show ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
       a - application route
       + - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is not set

    10.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C       10.0.0.0/8 is directly connected, Ethernet0/0
L       10.0.0.1/32 is directly connected, Ethernet0/0
    20.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C       20.0.0.0/8 is directly connected, Ethernet0/1
L       20.0.0.1/32 is directly connected, Ethernet0/1
D       30.0.0.0/8 [90/307200] via 20.0.0.2, 00:01:33, Ethernet0/1
D       40.0.0.0/8 [90/332800] via 20.0.0.2, 00:00:40, Ethernet0/1
```



R2



```
*Aug 18 16:48:54.705: %DUAL-5-NBRCHANGE: EIGRP-IPv4 10: Neighbor 30.0.0.2 (Ethernet0/1) is up: new adjacency
```

```
R2(config)#do show ip route
```

```
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
```

```
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
```

```
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
```

```
E1 - OSPF external type 1, E2 - OSPF external type 2
```

```
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
```

```
ia - IS-IS inter area, * - candidate default, U - per-user static route
```

```
o - ODR, P - periodic downloaded static route, H - NHRP, I - LISP
```

```
a - application route
```

```
+ - replicated route, % - next hop override, p - overrides from PfR
```

```
Gateway of last resort is not set
```

```
D    10.0.0.0/8 [90/307200] via 20.0.0.1, 00:02:16, Ethernet0/0
```

```
20.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
```

```
C    20.0.0.0/8 is directly connected, Ethernet0/0
```

```
L    20.0.0.2/32 is directly connected, Ethernet0/0
```

```
30.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
```

```
C    30.0.0.0/8 is directly connected, Ethernet0/1
```

```
L    30.0.0.1/32 is directly connected, Ethernet0/1
```

```
D    40.0.0.0/8 [90/307200] via 30.0.0.2, 00:01:20, Ethernet0/1
```

```
R2(config)#
```




```
R3(config-router)#exit
R3(config)#
R3(config)#do show ip route

Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
       a - application route
       + - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is not set

D    10.0.0.0/8 [90/332800] via 30.0.0.1, 00:01:52, Ethernet0/1
D    20.0.0.0/8 [90/307200] via 30.0.0.1, 00:01:52, Ethernet0/1
    30.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C      30.0.0.0/8 is directly connected, Ethernet0/1
L      30.0.0.2/32 is directly connected, Ethernet0/1
    40.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C      40.0.0.0/8 is directly connected, Ethernet0/0
L      40.0.0.1/32 is directly connected, Ethernet0/0
```



My Documents

My Computer

My Network Places

Recycle Bin

Internet Explorer

Cisco ASDM-1...

Old Java ASDM

PuTTY

```
C:\WINDOWS\system32\cmd.exe
Destination host unreachable.
Destination host unreachable.
Destination host unreachable.
Destination host unreachable.

Ping statistics for 40.0.0.10:
    Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),

C:\Documents and Settings\user>ncpa.cpl

C:\Documents and Settings\user>ping 40.0.0.10

Pinging 40.0.0.10 with 32 bytes of data:

Reply from 40.0.0.10: bytes=32 time=2ms TTL=125
Reply from 40.0.0.10: bytes=32 time=2ms TTL=125
Reply from 40.0.0.10: bytes=32 time=2ms TTL=125
Reply from 40.0.0.10: bytes=32 time=1ms TTL=125

Ping statistics for 40.0.0.10:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 1ms, Maximum = 2ms, Average = 1ms

C:\Documents and Settings\user>
```

Start your



My Documents

My Computer

My Network
Places

Recycle Bin

Internet
ExplorerCisco
ASDM-I...

```
C:\WINDOWS\system32\cmd.exe
Microsoft Windows XP [Version 5.1.2600]
(C) Copyright 1985-2001 Microsoft Corp.

C:\Documents and Settings\user>ncpa.cpl

C:\Documents and Settings\user>ping 10.0.0.10

Pinging 10.0.0.10 with 32 bytes of data:

Reply from 10.0.0.10: bytes=32 time=3ms TTL=125
Reply from 10.0.0.10: bytes=32 time=2ms TTL=125
Reply from 10.0.0.10: bytes=32 time=2ms TTL=125
Reply from 10.0.0.10: bytes=32 time=1ms TTL=125

Ping statistics for 10.0.0.10:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 1ms, Maximum = 3ms, Average = 2ms

C:\Documents and Settings\user>_
```