



SW1



```
SW1#
SW1#
SW1#conf te
Enter configuration commands, one per line.  End with CNTL/Z.
SW1(config)#vlan 10
SW1(config-vlan)#name HR
SW1(config-vlan)#exit
SW1(config)#vlan 20
SW1(config-vlan)#name SALES
SW1(config-vlan)#exit
SW1(config)#int e0/0
SW1(config-if)#switchport access vlan 10
SW1(config-if)#int e0/1
SW1(config-if)#switchport access vlan 20
SW1(config-if)#ex
*Aug 10 12:28:59.267: %PNP-6-PNP_DISCOVERY_STOPPED: PnP Discovery stopped (Config Wizard)
SW1(config-if)#exit
SW1(config)#int e0/2
SW1(config-if)#switchport trunk encapsulation dot1q
SW1(config-if)#switchport mode trunk
SW1(config-if)#exit
SW1(config)#
```



```
g Wizard)
SW1(config-if)#exit
SW1(config)#int e0/2
SW1(config-if)#switchport trunk encapsulation dot1q
SW1(config-if)#switchport mode trunk
SW1(config-if)#exit
SW1(config)#
SW1(config)#
SW1(config)#
SW1(config)#exit
SW1#sh
*Aug 10 12:29:47.321: %SYS-5-CONFIG_I: Configured from console by console
SW1#show vlan br
```

VLAN	Name	Status	Ports
1	default	active	Et0/3
10	HR	active	Et0/0
20	SALES	active	Et0/1
1002	fddi-default	act/unsup	
1003	token-ring-default	act/unsup	
1004	fddinet-default	act/unsup	
1005	trnet-default	act/unsup	

SW1#

```
SW2(config)#vlan 10
SW2(config-vlan)#name HR
SW2(config-vlan)#EXIT
SW2(config)#VLAN 20
SW2(config-vlan)#name SALES
SW2(config-vlan)#EXIT
SW2(config)#INT E0/0
SW2(config-if)#switchport access vlan 10
^
% Invalid input detected at '^' marker.

SW2(config-if)#switchport access vlan 10
SW2(config-if)#int e0/1
SW2(config-if)#switchport access vlann 20
^
% Invalid input detected at '^' marker.

SW2(config-if)#switchport access vlan 20
SW2(config-if)#exit
SW2(config)#int e0/2
SW2(config-if)#switchport trunk encapsulation dot1q
SW2(config-if)#switchport mode trunk
SW2(config-if)#exit
SW2(config)#
```

% Invalid input detected at '^' marker.

SW2(config-if)#switchport access vlan 20

SW2(config-if)#exit

SW2(config)#int e0/2

SW2(config-if)#switchport trunk encapsulation dot1q

SW2(config-if)#switchport mode trunk

SW2(config-if)#exit

SW2(config)#

SW2(config)#exit

SW2#show

*Aug 10 12:32:01.751: %SYS-5-CONFIG_I: Configured from console by console

SW2#show vlan br

VLAN	Name	Status	Ports
1	default	active	Et0/3
10	HR	active	Et0/0
20	SALES	active	Et0/1
1002	fddi-default	act/unsup	
1003	token-ring-default	act/unsup	
1004	fddinet-default	act/unsup	
1005	trnet-default	act/unsup	

SW2#



My Documents

My Computer

My Network Places

Recycle Bin

Internet Explorer

Cisco ASDM-1...

Old Java ASDM

PuTTY

```
C:\WINDOWS\system32\CMD.exe
Windows IP Configuration

Ethernet adapter Local Area Connection:

    Connection-specific DNS Suffix  . : 
    IP Address . . . . . : 10.0.0.10
    Subnet Mask . . . . . : 255.0.0.0
    Default Gateway . . . . . : 

C:\Documents and Settings\user>ping 10.0.0.20

Pinging 10.0.0.20 with 32 bytes of data:

Reply from 10.0.0.20: bytes=32 time=2ms TTL=128
Reply from 10.0.0.20: bytes=32 time=2ms TTL=128
Reply from 10.0.0.20: bytes=32 time=2ms TTL=128
Reply from 10.0.0.20: bytes=32 time=2ms TTL=128

Ping statistics for 10.0.0.20:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 2ms, Maximum = 2ms, Average = 2ms

C:\Documents and Settings\user>
```



```
C:\WINDOWS\system32\cmd.exe
Windows IP Configuration

Ethernet adapter Local Area Connection:

    Connection-specific DNS Suffix  . : 
    IP Address. . . . . : 20.0.0.10
    Subnet Mask . . . . . : 255.0.0.0
    Default Gateway . . . . . : 

C:\Documents and Settings\user>ping 20.0.0.20

Pinging 20.0.0.20 with 32 bytes of data:

Reply from 20.0.0.20: bytes=32 time=4ms TTL=128
Reply from 20.0.0.20: bytes=32 time=3ms TTL=128
Reply from 20.0.0.20: bytes=32 time=2ms TTL=128
Reply from 20.0.0.20: bytes=32 time=3ms TTL=128

Ping statistics for 20.0.0.20:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 2ms, Maximum = 4ms, Average = 3ms

C:\Documents and Settings\user>
```

Internet
Explorer

Cisco
ASDM-I...

Old Java ASDM

PUTTY



My Documents

My Computer

My Network Places

Recycle Bin

Internet Explorer

Cisco ASDM-I...

Old Java ASDM

PuTTY

```
C:\WINDOWS\system32\cmd.exe
Windows IP Configuration

Ethernet adapter Local Area Connection:

    Connection-specific DNS Suffix  . : 
    IP Address. . . . . : 10.0.0.20
    Subnet Mask . . . . . : 255.0.0.0
    Default Gateway . . . . . : 

C:\Documents and Settings\user>ping 10.0.0.10


Pinging 10.0.0.10 with 32 bytes of data:

Reply from 10.0.0.10: bytes=32 time=2ms TTL=128
Reply from 10.0.0.10: bytes=32 time=3ms TTL=128
Reply from 10.0.0.10: bytes=32 time=2ms TTL=128
Reply from 10.0.0.10: bytes=32 time=2ms TTL=128

Ping statistics for 10.0.0.10:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 2ms, Maximum = 3ms, Average = 2ms

C:\Documents and Settings\user>
```

Start your



My Documents

My Computer

My Network Places

Recycle Bin

Internet Explorer

Cisco ASDM-I...

Old Java ASDM

PuTTY

```
C:\WINDOWS\system32\cmd.exe
Windows IP Configuration

Ethernet adapter Local Area Connection:

    Connection-specific DNS Suffix  . : 
    IP Address. . . . . : 20.0.0.20
    Subnet Mask . . . . . : 255.0.0.0
    Default Gateway . . . . . : 

C:\Documents and Settings\user>ping 20.0.0.10

Pinging 20.0.0.10 with 32 bytes of data:

Reply from 20.0.0.10: bytes=32 time=2ms TTL=128
Reply from 20.0.0.10: bytes=32 time=2ms TTL=128
Reply from 20.0.0.10: bytes=32 time=2ms TTL=128
Reply from 20.0.0.10: bytes=32 time=2ms TTL=128

Ping statistics for 20.0.0.10:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 2ms, Maximum = 2ms, Average = 2ms

C:\Documents and Settings\user>
```