

```
R1#
R1#
R1#
R1#conf ter
Enter configuration commands, one per line.  End with CNTL/Z.
R1(config)#int e0/0
R1(config-if)#ip add 10.0.0.1 255.0.0.0
R1(config-if)#no sh
R1(config-if)#int e0/1
R1(config-if)#ip add 20.0.0.1 255.0.0.0
R1(config-if)#no sh
R1(config-if)#
*Aug 17 15:56:38.639: %PNP-6-PNP_DISCOVERY_STOPPED: PnP Discovery stopped (Config Wizard)
R1(config-if)#
R1(config-if)#
R1(config-if)#
R1(config-if)#exit
R1(config)#router rip
R1(config-router)#network 10.0.0.0
R1(config-router)#network 20.0.0.0
R1(config-router)#
```

```
R1#show ip route
```

```
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP  
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area  
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2  
E1 - OSPF external type 1, E2 - OSPF external type 2  
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2  
ia - IS-IS inter area, * - candidate default, U - per-user static route  
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP  
a - application route  
+ - replicated route, % - next hop override, p - overrides from PfR
```

```
Gateway of last resort is not set
```

```
10.0.0.0/8 is variably subnetted, 2 subnets, 2 masks  
C    10.0.0.0/8 is directly connected, Ethernet0/0  
L    10.0.0.1/32 is directly connected, Ethernet0/0  
20.0.0.0/8 is variably subnetted, 2 subnets, 2 masks  
C    20.0.0.0/8 is directly connected, Ethernet0/1  
L    20.0.0.1/32 is directly connected, Ethernet0/1  
R    30.0.0.0/8 [120/1] via 20.0.0.2, 00:00:07, Ethernet0/1  
R    40.0.0.0/8 [120/2] via 20.0.0.2, 00:00:07, Ethernet0/1
```

```
R1#
```



```
R2#show ip
```

```
*Aug 17 15:59:19.640: %SYS-5-CONFIG_I: Configured from console by console
```

```
R2#show ip route
```

```
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP  
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area  
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2  
E1 - OSPF external type 1, E2 - OSPF external type 2  
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2  
ia - IS-IS inter area, * - candidate default, U - per-user static route  
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP  
a - application route  
+ - replicated route, % - next hop override, p - overrides from PfR
```

```
Gateway of last resort is not set
```

```
R    10.0.0.0/8 [120/1] via 20.0.0.1, 00:00:02, Ethernet0/0  
    20.0.0.0/8 is variably subnetted, 2 subnets, 2 masks  
C    20.0.0.0/8 is directly connected, Ethernet0/0  
L    20.0.0.2/32 is directly connected, Ethernet0/0  
    30.0.0.0/8 is variably subnetted, 2 subnets, 2 masks  
C    30.0.0.0/8 is directly connected, Ethernet0/1  
L    30.0.0.1/32 is directly connected, Ethernet0/1  
R    40.0.0.0/8 [120/1] via 30.0.0.2, 00:00:15, Ethernet0/1
```

```
R2#
```

```
R3(config-router)#
R3(config-router)#exit
R3(config)#do show ip route

Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
       a - application route
       + - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is not set

R    10.0.0.0/8 [120/2] via 30.0.0.1, 00:00:15, Ethernet0/1
R    20.0.0.0/8 [120/1] via 30.0.0.1, 00:00:15, Ethernet0/1
     30.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C        30.0.0.0/8 is directly connected, Ethernet0/1
L        30.0.0.2/32 is directly connected, Ethernet0/1
     40.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C        40.0.0.0/8 is directly connected, Ethernet0/0
L        40.0.0.1/32 is directly connected, Ethernet0/0
R3(config)#
```




My Documents



My Computer

My Network
Places

Recycle Bin

Internet
ExplorerCisco
ASDM-I...

old bus ASDM

C:\WINDOWS\system32\cmd.exe

Microsoft Windows XP [Version 5.1.2600]
<C> Copyright 1985-2001 Microsoft Corp.

C:\Documents and Settings\user>ping 40.0.0.10

Pinging 40.0.0.10 with 32 bytes of data:

Reply from 40.0.0.10: bytes=32 time=3ms TTL=125

Reply from 40.0.0.10: bytes=32 time=9ms TTL=125

Reply from 40.0.0.10: bytes=32 time=2ms TTL=125

Reply from 40.0.0.10: bytes=32 time=1ms TTL=125

Ping statistics for 40.0.0.10:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

Approximate round trip times in milli-seconds:

Minimum = 1ms, Maximum = 9ms, Average = 3ms

C:\Documents and Settings\user>_



My Documents

My Computer

My Network
Places

Recycle Bin

Internet
ExplorerCisco
ASDM-I...

Old Java ASDM

PuTTY

C:\WINDOWS\system32\cmd.exe

Microsoft Windows XP [Version 5.1.2600]
(C) Copyright 1985-2001 Microsoft Corp.

C:\Documents and Settings\user>

C:\Documents and Settings\user>

C:\Documents and Settings\user>ping 10.0.0.10

Pinging 10.0.0.10 with 32 bytes of data:

Reply from 10.0.0.10: bytes=32 time=2ms TTL=125

Reply from 10.0.0.10: bytes=32 time=1ms TTL=125

Reply from 10.0.0.10: bytes=32 time=1ms TTL=125

Reply from 10.0.0.10: bytes=32 time=1ms TTL=125

Ping statistics for 10.0.0.10:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

Approximate round trip times in milli-seconds:

Minimum = 1ms, Maximum = 2ms, Average = 1ms

C:\Documents and Settings\user>_