SCOPE

Example 1: Singleton

StudentDisplay.java | ApplicationsingletonApplication.java

```java
package com.example.Applicationsingleton;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;
import org.springframework.context.ApplicationContext;

@SpringBootApplication
public class ApplicationsingletonApplication {

    public static void main(String[] args) {

        ApplicationContext context= SpringApplication.run(ApplicationsingletonApplication.class, args);
        StudentDisplay s=context.getBean(StudentDisplay.class);
        s.display();
        s.age=24;
        StudentDisplay s1=context.getBean(StudentDisplay.class);
        s1.age=21;
        s1.display();
        System.out.println(s1.age);
        System.out.println(s.age);
    }
}
```

StudentDisplay.java | ApplicationsingletonApplication.java

```java
package com.example.Applicationsingleton;

import org.springframework.context.annotation.Scope;
import org.springframework.stereotype.Component;

@Component  4 usages
@Scope("singleton")
public class StudentDisplay {
    int age;  5 usages
    public void display()  2 usages
    {
        System.out.println("Welcome");
        System.out.println("Age: "+age);
    }
}
```

```
2026-10-15T20:14:12.235+05:30  INFO 9392 --- [Applicationsingleton] [           main] c.e.A.ApplicationsingletonAppli
2026-10-15T20:14:12.238+05:30  INFO 9392 --- [Applicationsingleton] [           main] c.e.A.ApplicationsingletonAppli
2026-10-15T20:14:12.702+05:30  INFO 9392 --- [Applicationsingleton] [           main] c.e.A.ApplicationsingletonAppli
Welcome
Age: 0
Welcome
Age: 21
21
21

Process finished with exit code 0
```

Example 2: Prototype

StudentDisplay.java | ApplicationPrototypeApplication.java

```java
package com.example.ApplicationPrototype;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;
import org.springframework.context.ApplicationContext;

@SpringBootApplication
public class ApplicationPrototypeApplication {

    public static void main(String[] args) {

        ApplicationContext context=SpringApplication.run(ApplicationPrototypeApplication.class, args);
        StudentDisplay d=context.getBean(StudentDisplay.class);
        d.name="Sujitha";
        StudentDisplay d1=context.getBean(StudentDisplay.class);
        d1.name="Ammu";
        d1.display();
        System.out.println(d.name);
    }
}
```

StudentDisplay.java | ApplicationPrototypeApplication.java

```java
package com.example.ApplicationPrototype;

import org.springframework.context.annotation.Scope;
import org.springframework.stereotype.Component;

@Component  4 usages
@Scope("prototype")
public class StudentDisplay {
    String name;  4 usages

    public void display()  1 usage
    {
        System.out.println("Welcome");
        System.out.println("Name: "+name);
    }
}
```

```
2026-10-15T20:13:13.908+05:30  INFO 5872 --- [ApplicationPrototype] [           main] c.e.A.ApplicationPrototypeAppli
2026-10-15T20:13:13.914+05:30  INFO 5872 --- [ApplicationPrototype] [           main] c.e.A.ApplicationPrototypeAppli
2026-10-15T20:13:14.439+05:30  INFO 5872 --- [ApplicationPrototype] [           main] c.e.A.ApplicationPrototypeAppli
Welcome
Name: Ammu
Sujitha

Process finished with exit code 0
```