Status	Finished
Started	Wednesday, 21 October 2026, 11:25 AM
Completed	Wednesday, 21 October 2026, 11:34 AM
Duration	9 mins 20 secs
Grade	**13.00** out of 15.00 (**86.67**%)

Question **1**

Correct

Mark 1.00 out of 1.00

What is the output of the following

```
set1 = {10, 20, 30, 40, 50}
set2 = {60, 70, 10, 30, 40, 80, 20, 50}

print(set1.issubset(set2))
print(set2.issuperset(set1))
```

a. False
True

b. False
False

c. True
False

d. True ✓
True

Question **2**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

```
my_t1 = (1, 2, 3, 4)
my_t1.append( (5, 6, 7) )
print(len(my_t1))
```

a. 2

b. 5

c. Error ✓

d. 1

Question **3**

Correct

Mark 1.00 out of 1.00

Select which is true for Python tuple?

a. None of these

b. A tuple maintains the order of items ✓

c. A tuple is unordered

d. We can change the tuple once created

Question **4**

Correct

Mark 1.00 out of 1.00

What will the below Python code do?

```
set1={2,3}

set2={3,2}

set3={2,1}

if(set1==set2):

    print("yes")

else:

    print("no")

if(set1==set3):

    print("yes")

else:

    print("no")
```

a. "==" is not supported for set in Python

b. No, No

c. Yes, No ✓

d. Yes, Yes

Question **5**

Correct

Mark 1.00 out of 1.00

A python tuple can be created without using any parentheses. (True/False)

a. False

b. True ✓

Question **6**

Correct

Mark 1.00 out of 1.00

Choose the correct option.

a. In Python, a tuple can contain only strings as its elements.

b. In Python, a tuple can contain only integers as its elements.

c. In Python, a tuple can contain either string or integer but not both at a time.

d. In Python, a tuple can contain both integers and strings as its elements. ✓

Question **7**

Correct

Mark 1.00 out of 1.00

What will be the output of below Python code?

```
tupl=("python","programming","Computer")
print(tupl[-3:0])
```

a. (Computer)

b. Computer

c. Error

d. () ✓

Question **8**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

```
t = (11, 3)
x = 3 * t
print(x)
```

a. (11,3)(11,3)(11,3)

b. [11,11,11,3,3,3]

c. (11,3,11,11,3,11,11,11,3)

d. (11, 3, 11, 3, 11, 3) ✓

Question **9**

Correct

Mark 1.00 out of 1.00

What is the output of the following set operation

```
sampleSet = {"Yellow", "Orange", "Black"}
sampleSet.update(["Blue", "Green", "Red"])
print(sampleSet)
```

a. {'Yellow', 'Orange', 'Black', ["Blue", "Green", "Red"]}

b. TypeError: update() doesn't allow list as a argument.

c. {'Yellow', 'Orange', 'Red', 'Black', 'Green', 'Blue'} ✓

d. Name Error

Question **10**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

```
>>>t = (1, 2, 4, 3, 8, 9)
>>>[t[i] for i in range(0, len(t), 2)]
```

a. [2, 3, 9]

b. (1, 4, 8)

c. [1, 2, 4, 3, 8, 9]

d. [1, 4, 8] ✓

Question **11**

Correct

Mark 1.00 out of 1.00

Select all the correct options to remove "ECE" from the set.

```
sampleSet = {"ECE", "R&A", "MCT"}
```

a. sampleSet.delete("ECE")

b. remove.sampleSet("ECE")

c. del.sampleSet("ECE")

d. sampleSet.discard("ECE") ✓

Question **12**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
list1=[1,3,4,2]

x=list1.pop(2)

print(set([x]))
```

a. {1,3,2}

b. {2}

c. {1,3,4}

d. {4} ✓

Question **13**

Correct

Mark 1.00 out of 1.00

```
What is the output of the following code?
```

```
aTuple = (10, 20, 30, 40, 50, 60, 70, 80)
print(aTuple[2:5], aTuple[:4], aTuple[3:])
```

a. (30, 40, 50) (10, 20, 30, 40) (40, 50, 60, 70, 80) ✓

b. (10, 20, 30, 40) (40, 50, 60, 70, 80)

c. (30, 40, 50) (10, 20, 30, 40)

d. (30, 40, 50)(40, 50, 60, 70, 80)

Question **14**

Incorrect

Mark 0.00 out of 1.00

What will set1|set2 do?

```
If set1={"a","b",3}
set2={3,7}
```

a. Elements of set2 will get appended to set1

b. A new set will be created with the unique elements of set1 and set2. ✗

c. A new set will be created with the elements of both set1 and set2

d. Elements of set1 will get appended to set2

Question **15**

Incorrect

Mark 0.00 out of 1.00

Which of the following options will produce the same output?

```
t = (15, 83, 21, 49, 60,45,52,85,100)
# options i, ii, iii, or iv
print(t[:-1])
print(t[0:5])
print(t[0:8])
print(t[-7:])
```

a. i,ii

b. iii,iv ✕

c. ii,iv

d. i,iii