Status	Finished
Started	Tuesday, 20 October 2026, 7:24 PM
Completed	Tuesday, 20 October 2026, 7:34 PM
Duration	9 mins 33 secs
Grade	**14.00** out of 15.00 (**93.33**%)

Question **1**

Correct

Mark 1.00 out of 1.00

Which method is used to read file line by line

a. readlines(1)
b. readline() ✓
c. read(1)
d. line()

The correct answer is: readline()

Question **2**

Correct

Mark 1.00 out of 1.00

What is the use of seek() method in files?

a. none of the mentioned
b. sets the file's current position at the offset ✓
c. sets the file's previous position at the offset
d. sets the file's current position within the file

The correct answer is:
sets the file's current position at the offset

Question **3**

Correct

Mark 1.00 out of 1.00

Which of the following is true about the readlines() method?

a. It reads the entire file and returns it as a string
b. It reads the entire file and returns it as a list of lines ✓
c. It reads the file and returns it as a dictionary
d. It reads a single line from the file

The correct answer is: It reads the entire file and returns it as a list of lines

Question **4**

Correct

Mark 1.00 out of 1.00

Which method is used to truncate a file to a specific size?

a. resize()
b. shrink()
c. truncate() ✓
d. reduce()

The correct answer is: truncate()

Question **5**

Correct

Mark 1.00 out of 1.00

What is the result of the following code?

```
with open("example.txt", "r") as f:
    data = f.read()
print(data)
```

a. Prints the first 10 characters of the file
b. Prints each line of the file
c. Prints the entire content of the file ✓
d. Prints an error message

The correct answer is: Prints the entire content of the file

Question **6**

Correct

Mark 1.00 out of 1.00

Which method is used to read a specific number of characters from a file?

- a. read(size) ✓
- b. readlines()
- c. readchar()
- d. readline()

The correct answer is: read(size)

Question **7**

Correct

Mark 1.00 out of 1.00

Which method is used to write a list of strings to a file?

- a. write()
- b. write_all()
- c. writelines() ✓
- d. write_list()

The correct answer is: writelines()

Question **8**

Correct

Mark 1.00 out of 1.00

Which of the following modes opens a file for writing in binary format?

- a. w
- b. wb ✓
- c. r+
- d. rb

The correct answer is: wb

Question **9**

Correct

Mark 1.00 out of 1.00

What does the following code do?

```
f = open("data.txt", "a")
f.write("Adding new data\n")
f.close()
```

a. Overwrites the file with "Adding new data"

b. Appends "Adding new data" to the end of the file ✓

c. Opens the file in read mode

d. Raises an error because the file is opened in append mode

The correct answer is: Appends "Adding new data" to the end of the file

Question **10**

Correct

Mark 1.00 out of 1.00

What is the output of the following code?

```
f = open("test.txt", "w")
f.write("Hello, world!")
f.close()
f = open("test.txt", "r")
print(f.read())
f.close()
```

a. world

b. An error is raised

c. Hello

d. Hello, world! ✓

The correct answer is: Hello, world!

Question **11**

Correct

Mark 1.00 out of 1.00

How do you check if a file is closed in Python?

a. file.closed ✓

b. file.is_closed()

c. file.isclosed()

d. file.closed()

The correct answer is: file.closed

Question **12**

Correct

Mark 1.00 out of 1.00

What is the purpose of the with statement in Python file handling?

a. To write data to a file
b. To automatically close the file after its suite finishes ✓
c. To delete a file
d. To read data from a file

The correct answer is: To automatically close the file after its suite finishes

Question **13**

Correct

Mark 1.00 out of 1.00

Default EOL character of text file in python is ,

a. \t
b. space
c. ,
d. \n ✓

The correct answer is:
\n

Question **14**

Correct

Mark 1.00 out of 1.00

Which function is used to open a file in Python?

a. openfile()
b. open_file()
c. open() ✓
d. file()

The correct answer is: open()

Question **15**

Incorrect

Mark 0.00 out of 1.00

Which method is used to close a file in Python?

a. finish()
b. end() ✕
c. terminate()
d. close()

The correct answer is: close()