

Advanced Short Circuit Preventive Mechanism for Electric Vehicles

1st Sheikdavood K
*Electronics and Communication
Engineering*
M.Kumarasamy College of
Engineering, Karur, India
sheikdavoodce@gmail.com

2nd Yasar S
*Electronics and Communication
Engineering*
M.Kumarasamy College of
Engineering, Karur, India
yasarsoccer@gmail.com

3rd Shanjay RK
*Electronics and Communication
Engineering*
M.Kumarasamy College of
Engineering, Karur, India
rkshanjay@gmail.com

4th Sivaramakrishnan M
*Electronics and Communication
Engineering*
M.Kumarasamy College of
Engineering, Karur, India
sivasks208@gmail.com

5th Subash P
*Electronics and Communication
Engineering*
M.Kumarasamy College of
Engineering, Karur, India
subashsivamani9595@gmail.com

Abstract— In order to improve safety, dependability, and system performance, the proposed project introduces a cutting-edge short circuit preventative mechanism made especially for electric vehicles (EVs). In EV power systems, short circuits are a serious problem since they can result in serious harm, component failures, and safety risks. Traditional protection techniques, including circuit breakers and fuses, are frequently slow, reactive, and unable to handle the complex and dynamic working circumstances of contemporary EVs to proactively prevent short circuits, this research makes use of a combination of high-speed sensing, predictive fault detection algorithms, and intelligent control tactics. The system uses machine learning techniques to predict and alleviate issues before they increase by continuously monitoring critical metrics including current, voltage, and temperature variations. To guarantee quick reaction and strong protection, sophisticated parts are integrated, such as semiconductor switches and thermal management subsystems. In order to minimize downtime and maintenance expenses, the suggested mechanism also includes self-diagnostic capabilities, which allow for continuous monitoring and automatic recovery in the event of temporary defects. The system's ability to detect and prevent short circuits is demonstrated by simulation and experimental findings, which beat conventional protection techniques in terms of speed, accuracy, and dependability. This invention contributes to safer, more effective, and sustainable EV systems by offering a comprehensive solution to one of the most important problems in electric mobility. By laying the groundwork for next-generation electrical safety solutions, the project hopes to increase EV adoption and confidence. In addition to tackling important issues in electric mobility, this innovation helps create EV systems that are safer, more effective, and more sustainable. It creates a solid basis for broad EV adoption by boosting user confidence and system resilience, hastening the shift to a cleaner and more sustainable future. Along with its technical advantages, the system's self-diagnostic features allow for automatic recovery from transient malfunctions, constant monitoring, and a reduction in maintenance needs, all of which drastically save operating expenses. Its scalable and modular architecture ensures industry-wide usability by allowing it to be integrated into a variety of EV platforms, from private automobiles to commercial fleets.

I. INTRODUCTION

The growing popularity of electric vehicles (EVs) has brought attention to how important it is to have dependable and effective electrical systems in order to guarantee both safety and peak performance. Short circuits are one of the many issues that EV power systems encounter, and they are especially dangerous since they can result in serious harm, such as system failures, thermal runaway, and even user safety risks. As a result, a top focus in automobile research and development is now creating sophisticated preventive mechanisms to identify, lessen, and control short circuits in EV power systems. Traditional short circuit protection techniques frequently involve fuses or circuit breakers, which have intrinsic drawbacks such slower response times, no real-time monitoring, and restricted reusability, despite being useful in some situations. These difficulties call for the creation of increasingly complex systems that can detect faults proactively, react quickly, and recover on their own. This study suggests a sophisticated short circuit prevention system made especially for electric cars that incorporates state-of-the-art technology including active power flow management, machine learning- based predictive diagnostics, and real-time fault detection algorithms. The risk of short circuits is further increased by the dynamic and constantly shifting working circumstances of EV power systems, which include fluctuating loads, high currents, and extremely high temperatures. Advanced preventive systems that can adjust in real-time to guarantee system stability and safety are required to meet these difficulties. In order to provide thorough and dependable protection for the entire system, effective short circuit avoidance systems must take these complexity into consideration by including features like adaptive control techniques, fault-tolerant designs, and improved thermal management.

The proposed mechanism not only enhances the safety and reliability of EV power systems but also contributes to extending the lifespan of critical components and reducing downtime. By integrating advanced analytics and control strategies, this solution aligns with the broader goal of fostering sustainable and safe transportation technologies. The effectiveness of the mechanism is validated through simulation and experimental results, demonstrating significant improvements in fault prevention and system robustness compared to traditional approaches.

BACKGROUND OF THE INVENTION

Electric vehicles (EVs) are rapidly gaining popularity due to their potential to reduce greenhouse gas emissions and dependence on fossil fuels. But there are still significant issues with EV power systems' dependability and security. Short circuits, which can have disastrous consequences like component failure, thermal runaway, fire dangers, and even the risk of human death, are a major worry in these systems. A number of things can cause short circuits, such as poor insulation, conductive objects, bad wiring, or unforeseen environmental circumstances like moisture or extremely high or low temperatures.. To address short circuits, conventional protective devices like fuses and mechanical circuit breakers are frequently employed. Although these solutions offer rudimentary security, they frequently fail to meet the particular difficulties presented by EV situations. For example, EVs are susceptible to fast cycles of charging and discharging and operate under a variety of load circumstances, which can put stress on the electrical system. Furthermore, traditional systems are reactive rather than proactive in their approach since they are unable to monitor, predict, and avoid failures in real-time [6]. The development of more effective and efficient protective methods has been made possible in recent years by developments in semiconductor technology, sensor systems, and intelligent control units. High-speed switches, advanced algorithms, and machine learning tools enable real-time monitoring and predictive fault detection, paving the way for active and preemptive short circuit prevention.




Fig. 1. Work Flow Diagram



Fig. 2. Initial Fault Detection System




Fig. 3. E V System performance

II. OBJECTIVE OF THE INVENTION

The invention's main goal is to create a cutting-edge short circuit prevention system for electric vehicles (EVs) that will increase system durability, safety, and dependability. By employing real-time monitoring, predictive diagnostics, and intelligent control strategies, the mechanism seeks to proactively identify and mitigate electrical defects, lowering risks, decreasing downtime, and enhancing the overall functionality of EV power systems. The goal of this idea is to get beyond the drawbacks of traditional protection techniques like circuit breakers and fuses, which are frequently reactive, slower, and unable to handle the dynamic operating circumstances of EVs. By utilizing cutting-edge technology including high-speed sensors, predictive defect detection algorithms, and intelligent control units, the suggested approach emphasizes proactive prevention [6]. In order to enable the system to identify, anticipate, and react to possible short circuits with remarkable speed and accuracy, it seeks to continuously monitor vital factors such as current, voltage, and thermal fluctuations. Another key objective is to integrate self-diagnostic and recovery capabilities, allowing the system to autonomously manage transient faults and minimize downtime. The invention also emphasizes scalability and cost-effectiveness, ensuring its adaptability across a wide range of EV models and operating conditions. Ultimately, this invention aspires to enhance the overall safety and reliability of EVs, fostering consumer confidence and supporting the transition to sustainable electric mobility by mitigating one of the most pressing electrical challenges in the automotive industry.

III. SUMMARY OF THE INVENTION

This invention introduces an advanced short circuit preventive mechanism specifically designed for electric vehicles (EVs) to address critical safety and reliability concerns. Unlike traditional protection methods such as fuses and circuit breakers, this system offers a proactive approach by combining real-time monitoring, predictive analytics, and intelligent control strategies. The mechanism uses high-speed sensors to continuously monitor parameters like current, voltage, and temperature, enabling rapid detection of anomalies indicative of a potential short circuit. Machine learning algorithms are employed to analyze these parameters, allowing the system to predict and mitigate faults before they occur. In addition, advanced semiconductor switches ensure rapid response and precise isolation of faulty circuits, minimizing damage and preventing cascading failures. To enhance operational reliability, the system is equipped with self-diagnostic and recovery features, allowing it to autonomously manage transient faults and resume normal operation without human intervention. This reduces downtime and maintenance costs while extending the lifespan of critical EV components. Designed for scalability, the invention can be integrated into a wide range of EV platforms and customized to suit varying operational conditions. By ensuring robust protection, improved efficiency, and reduced risks, this innovative mechanism significantly enhances the safety and dependability of EV power systems.



Fig. 4. Model of EV

IV. DETAILED DESCRIPTION OF THE INVENTION

The increasing use of electric vehicles (EVs) has made it more difficult to guarantee the dependability and safety of their electrical systems. Short circuits present serious concerns, including as system failures, thermal runaway, and fire threats, among other difficulties. Although they can be somewhat effective, traditional solutions like fuses and mechanical circuit breakers are reactive and cannot keep up with the changing needs of contemporary EV systems.

By implementing a sophisticated short circuit prevention method, our invention overcomes these constraints. It improves system longevity and safety by proactively detecting and mitigating defects through the use of intelligent control techniques, real-time monitoring, and predictive analytics.

A. System Architecture

The suggested short circuit preventative mechanism's system design consists of multiple interconnected parts that cooperate to provide electric vehicles with complete protection. High-speed sensors give the central control unit real-time data by continuously monitoring important parameters including temperature, voltage, and current. In order to anticipate and categorize such issues before they arise, the control unit uses sophisticated machine learning algorithms to process this data. Semiconductor switches minimize disturbance and avoid damage by isolating malfunctioning circuits in microseconds upon detecting anomalies.

B. Semiconductor switching system

An essential part of the suggested short circuit prevention mechanism, which is intended to offer quick and dependable fault separation in electric vehicles (EVs), is the semiconductor switching system. Semiconductor switches function electrically as opposed to mechanically, allowing for quicker reaction times and increased robustness. The system uses solid-state components that can withstand the high currents and voltages seen in EV power systems, such as Metal-Oxide-Semiconductor Field-Effect Transistors (MOSFETs) and Insulated Gate Bipolar Transistors (IGBTs). The control unit alerts the semiconductor switches to isolate the impacted area of the circuit when it detects a possible short circuit. Sensitive components are much less likely to sustain damage thanks to this isolation, which happens in microseconds. These switches' arc-free operation ensures longevity and dependability even under heavy use by removing the wear and tear that comes with mechanical systems. Additionally, the energy-efficient design of the semiconductor switches minimizes power losses when in regular use. They are perfect for integration into a variety of EV architectures, from heavy-duty electric trucks to passenger cars, due to their small size and great scalability. Furthermore, the system may operate in both directions, which makes it appropriate for EV battery systems' charging and discharging procedures. The semiconductor switches are made to identify and react to malfunctions in less than ten microseconds. This quick reaction time is essential for stopping the spread of faults and reducing damage to parts like motors, batteries, and inverters. Power flows in both directions in EV systems: when the battery is charged and when energy is being released to the motor. Bidirectional currents can be handled by semiconductor switches with ease, guaranteeing reliable functioning in a variety of scenarios. When in use, mechanical switches frequently generate arcs, which can degrade materials and pose safety hazards. Since semiconductor switches are entirely electronic, these problems are resolved, guaranteeing more robust and secure operation. Because of its low on-state resistance, the switches produce less heat and lose less energy when in use. This enhances the range of the EV and improves overall energy efficiency and efficiency of energy use.

C. System speed

Operational speed is significantly improved by implementing advanced high-speed sensors that provide real-time data on critical parameters like current, voltage, and temperature. These inputs are processed by a central control unit equipped with machine learning algorithms, ensuring rapid fault detection and

immediate response through high-precision semiconductor switches.

D. Downtime Minimization

Downtime in electric vehicle systems is greatly reduced by combining self-recovery mechanisms with real-time system diagnostics. These systems keep an eye on the functioning of important parts, like battery subsystems and power electronics, in order to spot irregularities early. With the use of sophisticated machine learning algorithms, predictive maintenance techniques examine both historical and current data to predict probable faults. This proactive approach lessens the need for physical interventions while also assisting in identifying and correcting problems before they become more serious. The overall dependability and effectiveness of the vehicle are improved by making sure that temporary issues are automatically fixed and that vital systems are quickly returned to regular functioning. By avoiding serious damage or prolonged outages, these features also increase component lifespan and save maintenance expenses. Predictive maintenance methods use both past and present data to forecast likely issues, like battery pack cell imbalances or connector deterioration. Because minor disorders are handled before they become more serious, this proactive approach lessens the need for physical treatments. For example, by identifying and isolating malfunctioning battery cells, Tesla's real-time diagnostic system can preserve overall performance and plan maintenance for off-peak hours. The vehicle's efficiency and dependability are greatly increased by making sure that transient problems are automatically fixed and vital systems are promptly restored. Additionally, these features prolong component lifespan and lower maintenance costs by preventing serious damage or prolonged downtime,

E. Managing Costs

Saving people and fleets thousands of rupees a year. By employing modular components that grow with system requirements, lowering initial investment, and permitting upgrades only when required, cost-effectiveness is guaranteed. Early defect detection via predictive diagnostics reduces maintenance costs, which are normally between ₹8,000 and ₹40,000 per component, and prevents serious failures. Energy-efficient designs, including low-resistance MOSFETs, save ₹5,000 to ₹10,000 per car yearly by reducing operating energy expenses by 10-15%. By decreasing downtime, automated self-recovery systems save ₹3,000 to ₹12,000 a year in manual intervention expenses. Together, these actions minimize costs while preserving system dependability.

F. Selection of Algorithm

To guarantee efficient defect detection and prediction, the algorithm chosen for this project places a strong emphasis on accuracy, speed, and adaptability. Gradient Boosted Trees (GBT) are used because of its excellent anomaly detection accuracy and capacity to describe intricate, non-linear relationships in sensor data. GBT is a dependable option for real-time system monitoring since it is especially well-suited to managing a variety of data inputs, including measurements of temperature, voltage, and current. In addition, temporal dependencies that are crucial for detecting and forecasting developing defects in electric car systems are captured by Recurrent Neural Networks

(RNNs), which analyze sequential data. By combining the strengths of RNN in processing temporal patterns with GBT in static data analysis, this synergy creates a strong foundation for proactive fault control. The integrated strategy reduces system downtime, guarantees quick fault isolation.

G. Prediction of short circuit

High-speed sensors are used in the suggested system to continuously monitor important parameters including temperature, voltage, and current. For instance, the central control unit (CCU) receives the data if the current increases from 50 A to 60 A in milliseconds. This is recognized as an abnormality outside of the typical operating range by the CCU, which is driven by machine learning algorithms. Then, using past patterns—like recurrent current spikes or a sharp rise in temperature from 40°C to 70°C—it forecasts a possible short circuit. Semiconductor switches are predicted to isolate the problematic circuit in less than 10 microseconds [2]. This proactive measure guarantees safe operation, safeguards components, and stops cascading failures. The occurrence is recorded by the system, which also sends out a diagnostic notice for upkeep.

H. Fault detection system

Prediction and mitigation of this kind improve enhance safety, reduce downtime, and prolong system life in electric vehicles. By merging the outputs of several decision trees to increase prediction accuracy, the suggested method improves fault identification using sophisticated techniques such as Gradient Boosted Trees for accurate anomaly detection. Recurrent neural networks (RNNs) are perfect for tracking changing EV situations and forecasting possible faults over time because they can analyze temporal patterns and sequences in sensor data. Fault profiling is further strengthened by multi-parameter analysis that makes use of temperature, voltage, and current data. Robust monitoring is ensured by hybrid sensor networks that incorporate impedance and Hall effect sensors. While redundant sensors continue to function in the event of a failure, edge computing allows real-time fault isolation within 5 microseconds. After a fault, self-healing algorithms dynamically reorganize the system to continue functioning. Proactive repairs are made possible by real-time alerts and predictive maintenance, which identify patterns. These improvements guarantee quick and accurate fault identification, increasing EV safety and reliability. Using a hybrid sensor network that consists of both voltage and current sensors, the system detects any sudden voltage drop that occurs during fast charging in an EV. While Recurrent Neural Networks (RNNs) examine the sequence of sensor data to detect any impending problems, the Gradient Boosted Trees (GBT) technique precisely forecasts the fault's nature [9]. Using self-healing algorithms built into the control unit, edge computing with FPGA-based processing units isolates the problematic component in a matter of microseconds and reconfigures the system. Through the infotainment system, the driver receives a real-time alert about a possible issue, allowing them to schedule maintenance or repairs before any serious harm is done and guaranteeing continuous operation.

I. Thermal Management System

In electric vehicles (EVs), the thermal management subsystem is essential to preserving the effectiveness, security, and durability of the short circuit prevention system. Excessive heat is produced in the system's components, especially in the power electronics and semiconductor switches, under high-load circumstances such as short circuits or abrupt power fluctuations. The thermal management subsystem maintains ideal temperature control to avoid overheating, which can result in system failure, thermal deterioration, or even fires. Active and passive cooling techniques are combined to accomplish this. High-power components, such as semiconductor switches and battery packs, are usually directly cooled by active cooling techniques like liquid cooling systems or forced air circulation [2]. Heat sinks and thermal pads are examples of passive cooling techniques that remove excess heat without the need for extra electricity or moving elements. Real-time temperature sensors are integrated into the thermal management subsystem to keep an eye on vital components. When the system detects temperatures above safe thresholds, cooling mechanisms are activated. Furthermore, sophisticated heat spreaders are used to disperse heat evenly and avoid localized hotspots that might harm delicate parts. The thermal management subsystem keeps the system's operating temperature consistently within a safe range, which helps to increase efficiency and performance while also preventing the EV from overheating in fault situations. This increases the overall safety of the vehicle's power system, decreases heat-related energy losses, and extends the life of electrical components.

V. COMPONENTS USED

A. High Speed Sensors

High-speed sensors are essential to the operation of electric vehicles' (EVs') sophisticated short circuit prevention system. Throughout the EV's power system, these sensors continuously and in real time measure vital electrical parameters like current, voltage, temperature, and impedance. Their main responsibility is to identify any departures from typical operating circumstances that can point to the beginning of a short circuit or other issues. The system can act quickly to stop harm because these sensors are made to have incredibly quick response times, usually less than one millisecond. For instance, current sensors—which are frequently based on Hall effect technology—are able to measure the system's current flow precisely and identify anomalous decreases or surges that could be signs of short circuits. These high-speed sensors continuously send data to the central control unit, which processes it to determine the short circuit risk and initiate the appropriate preventive actions. Utilizing these cutting-edge sensors improves the overall safety and dependability of the car's electrical system by enabling early fault detection and quick isolation of problematic areas [5]. The flow of current through different parts, such as the battery, inverter, and electric motor, is measured using current sensors, such as Hall effect sensors. They are able to promptly detect anomalous current decreases or surges, which frequently indicate the presence of an overcurrent or short circuit. The voltage levels across important parts of the EV's electrical system are continuously measured by these sensors. A short circuit or unstable power

supply are two examples of imminent faults that are frequently indicated by voltage variations or departures from predetermined thresholds. When voltage anomalies are detected quickly, the system can take preventative action, including rerouting power or turning off problematic areas.

B. Central Control Unit (CCU)

The central control unit (CCU), which coordinates the entire fault detection, diagnosis, and protection process, is the brains behind the electric vehicle's (EV) short circuit prevention system. By analyzing real-time data from high-speed sensors and controlling the system's reaction to possible malfunctions, it serves as the decision-making hub and guarantees the dependability and safety of the car's electrical system. A high-performance microprocessor or microcontroller, which can carry out intricate algorithms with little delay, lies at the heart of the CCU. These algorithms, which are frequently powered by artificial intelligence or machine learning, examine sensor data to find anomalous patterns that could signal the start of a short circuit or other electrical problems [8]. These patterns include current surges, voltage drops, temperature spikes, and impedance changes. By comparing real-time sensor data with predetermined safety criteria, the CCU continuously assesses the system's health and makes sure that any deviations from standard operating conditions are promptly detected and fixed. When a failure is identified, the CCU immediately initiates the required precautionary measures, such as turning on cooling systems to avoid overheating, rerouting power, or isolating the problematic circuit by turning on semiconductor switches.

C. Semiconductor Switches

Electric vehicles' (EVs') short circuit prevention system relies heavily on semiconductor switches, which isolate malfunctioning circuits quickly, effectively, and dependably. Semiconductor switches use solid-state technology, which gives them a number of important advantages over conventional mechanical circuit breakers or fuses, including quicker response times, increased longevity, and more accuracy. Advanced semiconductor materials such as Metal- Oxide-Semiconductor Field-Effect Transistors (MOSFETs) and Insulated Gate Bipolar Transistors (IGBTs), which can manage high current and voltage levels while reducing power losses, are commonly used to make these switches. Within microseconds of the system detecting a malfunction, like a short circuit, the semiconductor switches isolate the faulty circuit and stop it from spreading to other areas of the vehicle's power supply. This quick reaction greatly lowers the possibility of damaging vital parts like batteries, motors, and inverters, which can be expensive to replace or repair.

D. Power Distribution

In electric vehicles (EVs), the power distribution system is a crucial subsystem that controls the effective transfer of electrical energy from the battery to different parts including the motor, inverters, and auxiliary systems. In order to ensure smooth vehicle operation and safety, particularly in the event of a breakdown, this system is essential in making sure that power is distributed in an efficient and controlled manner. In order to direct and control electrical power throughout the vehicle's architecture, the power distribution system is made up of a

network of high-capacity connections, power distribution units (PDUs), and protective devices. Central energy storage is provided by the battery pack, and the power distribution system makes sure that energy is allocated to the engine for propulsion, the onboard chargers for recharging, and the auxiliary loads such as lights, infotainment, and climate control. The power distribution system's capacity to monitor and control voltage and current levels is a crucial component that helps avoid overvoltage or overcurrent scenarios that could cause damage or malfunctions. In order to stop additional damage, the system includes a number of safety devices, including fuses, circuit breakers, and semiconductor switches, which immediately isolate impacted sections when they detect fault conditions like overloads or short circuits. When a short circuit or other defect occurs, the central control unit (CCU) and semiconductor switches cooperate with the power distribution system to quickly cut off the problematic area, redirect power to areas that are not affected, and keep the system running continuously. Furthermore, the power distribution system is often equipped with high-speed communication lines to relay real-time information to the CCU, which processes the data and triggers corrective actions, such as activating cooling systems or adjusting power flow. The system is designed for scalability, allowing for integration with larger, more powerful systems in electric trucks, buses, or commercial vehicles.

E. Protection System

To protect the electrical architecture of electric vehicles (EVs) from defects such short circuits, overvoltage, overcurrent, and thermal overload, the protection system is an essential part that ensures the vehicle's safety as well as the integrity of its parts. This system is in charge of continuously checking the power system's condition, identifying anomalies in real time, and acting quickly to fix them in order to protect vital parts including the battery pack, motor, inverters, and wiring. Usually, the protection system consists of a mix of software and hardware elements that cooperate to identify, isolate, and lessen fault circumstances as they appear. Overcurrent protection, which makes use of fuses, circuit breakers, and solid-state semiconductors, is one of the main elements of the protective system. switches to interrupt the power flow when excessive current is detected. These gadgets are precisely adjusted to react to abrupt spikes in current, which may be a sign of short circuits or other hazardous electrical issues. Overvoltage protection, which guarantees that the voltage levels across different components stay within safe working limits, is another essential component.

To stop damage from electrical surges or spikes, the protection system will cut off or restrict power to the impacted components if it senses that the voltage has risen above the predetermined level. Since overheating can result in thermal runaway or even fires, thermal protection is also a crucial component of the protection system [4]. Temperature levels are regularly monitored by temperature sensors mounted on high-heat parts including motors, semiconductor switches, and batteries. To avoid thermal damage, the system turns on cooling mechanisms or turns off particular components if a temperature increase is detected that exceeds safe bounds.

F. Self-Diagnostic and Feedback Module

A vital component of electric vehicles' (EVs') short circuit prevention system, the Self-Diagnostic and Feedback Module improves the vehicle's overall performance, safety, and dependability. This module provides real-time examination of the vehicle's components, including the battery, power distribution system, sensors, semiconductor switches, and control units, and continuously checks the condition and functionality of the complete electrical system. The module can identify anomalies, malfunctions, or performance deterioration long before they become serious failures by utilizing sophisticated diagnostic algorithms. It continuously assesses the condition of the car's electrical subsystems using information obtained from a variety of high-speed sensors, control units, and power management systems [1]. The Self-Diagnostic and Feedback Module initiates an instantaneous reaction upon detecting a fault, be it an anomalous spike in current, an increase in temperature, a variation in voltage, or the failure of a particular component. This response may involve the activation of the protection system, the isolation of malfunctioning components, or the redirection of power to unaffected areas. The module documents the fault's kind, location, and severity in addition to taking prompt corrective action. This information can be utilized for analysis and optimization in the future. Through the use of machine learning and predictive analytics, this feedback loop is crucial for improving the system's capacity to anticipate possible errors. This helps to anticipate wear and tear or other performance problems before they result in system breakdowns. Service staff can monitor and troubleshoot remotely because to the feedback module's ability to interact with external diagnostic tools. By ensuring that problems are found and fixed before they worsen, this remote diagnostic capability minimizes downtime and lowers maintenance expenses. By offering insightful information on the vehicle's energy usage, operational effectiveness, and general health, the module also contributes significantly to system optimization [7]. This information may be utilized to improve the performance of the power system and other crucial parts. The driver can also receive warnings from the Self-Diagnostic and Feedback Module, which gives them up-to-date information on the electrical system's condition. The driver can be empowered to take preventative action by receiving notifications of possible problems, performance deterioration, or maintenance requirements. Through constant system performance evaluation, data recording, and actionable insights, the Self-Diagnostic and Feedback Module not only guarantees optimal vehicle operation but also helps to continuously enhance the vehicle's overall efficiency and safety. Real-time data sharing and cloud-based analytics for improved system insights are made possible by the Self-Diagnostic and Feedback Module's smooth integration with IoT platforms [2]. Additionally, it facilitates over-the-air upgrades, which enable ongoing enhancements to diagnostic algorithms and the addition of new defect detection features. Furthermore, by learning from past data, the module facilitates adaptive reactions, guaranteeing improved precision in identifying and addressing complicated errors. The longevity of EV components is greatly increased by this proactive approach, which also increases user confidence in the dependability of the vehicle.

G. Communication System

In order to facilitate effective operation, safety, and performance management, the communication system in electric vehicles (EVs) is a crucial piece of infrastructure that guarantees smooth data flow between several subsystems, components, and external systems. The Central Control Unit (CCU), sensors, safety features, power distribution units, and other important subsystems inside the car can all communicate in real time thanks to this technology. It is the foundation of the car's electrical and diagnostic system, making sure that every part works together and reacts fast to any changes in the system's condition. Strong and secure protocols that provide dependable, fast data transfer with low latency, such Ethernet, wireless communication, and the Controller Area Network (CAN) bus, are usually the foundation of a communication system. By transmitting essential data, including sensor readings, fault detection signals, system status updates, and diagnostic information, these protocols make sure that every subsystem is informed of the general health of the vehicle in real time. In order to identify possible problems, the CCU, for example, continuously gets input from high-speed sensors that monitor variables including current, voltage, temperature, and impedance. When a fault is detected, the communication system promptly notifies the appropriate subsystems, including the protection system, so that they can take prompt action to isolate the problematic component and stop damage [10]. Furthermore, the communication system makes sure that every part—including the self-diagnostic module, thermal management systems, and semiconductor switches—can effectively communicate with one another.

H. Fuse and Circuit Breaker

In the electrical architecture of electric vehicles (EVs), fuses and circuit breakers are vital protective elements that protect the vehicle's power supply from overcurrent situations that could cause serious harm or safety risks. These gadgets are made to identify excessive current flow, which can be brought on by overloads, short circuits, or broken parts, and cut off the faulty circuit to stop additional harm. Fuses are straightforward but efficient safety devices made especially to guard against the dangers of overcurrent situations in electrical circuits. When the current above a preset threshold, a fuse's tiny metal strip or wire melts, thus stopping the flow of electricity [11]. A fuse is a one-time-use device since it must be replaced after blowing. Fuses are commonly employed in lower-power applications that require a prompt and decisive reaction to overcurrent situations. Because they shield sensitive parts from harmful currents, they are particularly useful for safeguarding smaller electrical subsystems, sensors, and battery packs. In contrast, circuit breakers provide a more advanced, resettable solution using a thermal or magnetic mechanism that detects the increase in current and disconnects the circuit to prevent damage to the system. Circuit breakers are similar to fuses in that they are made to trip and disconnect a circuit when excessive current is detected.

but they can be reset manually or automatically after they have been tripped. This makes them more appropriate for higher-power applications where overcurrent conditions may occur more frequently but need to be addressed without replacing the component each time.

VI. Current Limiting Devices

In order to prevent excessive current flow—which can result from faults like short circuits, overloads, or malfunctioning components—from damaging the electrical architecture of electric vehicles (EVs), current limiting devices are crucial parts of their electrical systems. These gadgets are made to regulate the current that passes through a circuit so that it stays within safe operating bounds. Current limiting devices aid in preventing overheating, component deterioration, and possible system failure by actively regulating the current under fault conditions. These factors are crucial for preserving the vehicle's dependability, performance, and safety. There are several types of current limiting devices, such as resistive components, active current limiters, and passive current limiters. Because of their intrinsic resistance, passive current limiters like fuses and resistors are made to lower the current to a safe level. For instance, fuses function by adding a regulated quantity of resistance to the circuit [3]. The fuse efficiently disconnects the circuit and stops more damage when the current reaches a predetermined level. In some applications, resistors can also be employed as current limiters, acting as a buffer to absorb excess current and shield the remainder of the system from damaging power surges. All things considered, current limiting devices are essential to preserving the longevity, safety, and effectiveness of electric car electrical systems because they guarantee that they function within safe bounds and reduce the possibility of major component damage.

VII. DESIGN




Fig. 5. System Architecture

S(MVA)	U1 (kV)	U2 (kV)	$\theta(^{\circ})$	S_f (MVA)	h(%)
200	11.10	10.56	0.7438	198.1	-0.95
210	11.08	10.56	0.6927	208.0	-0.95
220	11.05	10.56	0.6476	217.9	-0.95
230	11.03	10.56	0.6076	227.8	-0.96
240	11.01	10.55	0.5719	237.7	-0.96
250	10.99	10.55	0.5399	247.6	-0.96
260	10.97	10.55	0.5111	257.5	-0.96
270	10.95	10.55	0.4849	267.4	-0.96
280	10.94	10.55	0.4611	277.3	-0.96
290	10.92	10.55	0.4395	287.2	-0.97
300	10.91	10.55	0.4196	297.1	-0.97

Fig. 6. Sample Data




Fig. 7. Transparent design view of car top

In order to guarantee the electrical safety, stability, and dependability of the vehicle, the short circuit preventative mechanism for electric vehicles (EVs) is designed as a highly sensitive and efficient system that incorporates several subsystems. The design's major goal is to preserve the vehicle's peak performance while offering smooth protection against issues like short circuits, over currents, and overvoltage situations. Advanced sensors, semiconductor switches, protection devices, communication systems, and current limiting devices are just a few of the hardware and software elements that are incorporated into the design. These elements all cooperate to identify and address issues before they have a chance to cause serious harm. The Central Control Unit (CCU), which is at the center of the design, gets data in real time from a variety of sensors that track important parameters including temperature, voltage, and current. The CCU can detect possible system hazards such an overcurrent or a short circuit using this information. The circuit breakers and semiconductor switches are triggered to isolate the problem and disconnect the impacted circuit when a fault is identified. Even in the case of a malfunction, the power system will continue to function within safe bounds thanks to the assistance of current limiting devices, which help regulate the flow of electricity.




Fig. 8. Complete design view of top of car

VIII. SYSTEM COMPARISON

A. Limitations of Existing

Traditional EV fault detection systems are slow, with response times in milliseconds, inadequate for dynamic scenarios like thermal runaway events in lithium-ion batteries. They lack predictive diagnostics and real-time monitoring, leading to costly battery replacements (~₹4,000,000) and increased downtime due to reliance on mechanical fuses. These limitations hinder effective fault isolation and fail to prevent thermal events, raising critical safety concerns. Advanced solutions with faster response times and robust diagnostics are essential to address these challenges.

B. Proposed model comparison

Important technical domains, the suggested approach shows notable improvements over conventional fault detection methods. While the suggested approach uses sophisticated semiconductor switches to provide microsecond-level responses ($<5 \mu s$), typical systems rely on mechanical components, such as fuses and circuit breakers, with reaction times in the range of 10–100 milliseconds. Another crucial area is fault detection methods, where conventional systems use threshold-based reactive detection that is devoid of predictive capabilities. On the other hand, proactive anomaly identification is made possible by the suggested model's real-time analysis of multi-parameter data using machine learning methods. The suggested method uses solid-state semiconductor switches, such as MOSFETs and IGBTs, for quick, accurate, and arc-free fault isolation, whereas conventional systems rely on mechanical components, which are slower and more prone to wear [3]. Traditional thermal management systems usually use passive techniques, like thermal pads and heat sinks, which react slowly to overheating. For efficient and dynamic thermal control, the suggested approach incorporates active techniques including liquid cooling and real-time temperature monitoring. Furthermore, traditional systems have limited scalability and adaptability, which limits their application to particular configurations. The suggested system is more flexible and effective due to its modular design.

IX. CONCLUSION

This research is innovative because it takes a proactive approach to electric car short circuit prevention by combining self-recovery capabilities, predictive fault detection, and real-time monitoring. In contrast to conventional reactive systems, this model analyses sensor data and predicts any errors before they happen by using sophisticated machine learning methods like Recurrent Neural Networks (RNNs) and Gradient Boosted Trees. High-speed semiconductor switches minimize system damage and downtime by ensuring microsecond-level fault isolation. Furthermore, the self-diagnostic module eliminates the need for user intervention by automatically restoring system functionality. A new standard for safety, dependability, and efficiency in EV power systems is set by this creative combination of automated recovery, rapid reaction mechanisms, and predictive analytics. This strategy lays the groundwork for upcoming developments in EV safety technology in addition to addressing the shortcomings of conventional fault avoidance systems. The system guarantees adaptability to a variety of operating settings by utilizing Recurrent Neural Networks for temporal pattern analysis and Gradient Boosted Trees for accurate anomaly identification. By combining these state-of-the-art methods, the system becomes more resilient and scalable, which makes it a strong answer to the changing needs of electric mobility. In the end, this research opens the door for EV systems that are more dependable, effective, and sustainable, which boosts consumer confidence and encourages a wider uptake of electric vehicles.

X. REFERENCES

- [1] D. Qiao et al., "Quantitative Diagnosis of Internal Short Circuit for Lithium-Ion Batteries Using Relaxation Voltage," in *IEEE Transactions on Industrial Electronics*, vol. 71, no. 10, pp. 13201-13210, Oct. 2024, doi: 10.1109/TIE.2023.3342289.
- [2] Z. Sun et al., "An Online Data-Driven Fault Diagnosis and Thermal Runaway Early Warning for Electric Vehicle Batteries," in *IEEE Transactions on Power Electronics*, vol. 37, no. 10, pp. 12636-12646, Oct. 2022, doi: 10.1109/TPEL.2022.3173038.
- [3] K. Miyazaki, S. Kawai, T. Ueno and H. Ishihara, "A Digital Gate Driver IC with a Digitally Adjustable DESAT and Parameter Adjustment Method for False Detection Prevention and Short-Circuit Protection of 1200V 180A SiC Module," 2024 IEEE Applied Power Electronics Conference and Exposition (APEC), Long Beach, CA, USA, 2024, pp. 1130-1134, doi: 10.1109/APEC48139.2024.10509186.
- [4] H. -C. Park, M. -J. Cha, S. -H. Jeon and R. -Y. Kim, "Design and Evaluation of High-Speed Overcurrent and Short-Circuit Detection Circuits With High Noise Margin for WBG Power Semiconductor Devices," in *IEEE Access*, vol. 12, pp. 7540-7550, 2024, doi: 10.1109/ACCESS.2024.3351744.
- [5] F. Kaya and O. Akar, "Short Circuit Effects on HV Feeders of Optimally Located Electric Vehicle Fast Charging Stations," in *IEEE Access*, vol. 12, pp. 47842-47853, 2024, doi: 10.1109/ACCESS.2024.3383433.
- [6] I. Husain et al., "Electric Drive Technology Trends, Challenges, and Opportunities for Future Electric Vehicles," in *Proceedings of the IEEE*, vol. 109, no. 6, pp. 1039-1059, June 2021, doi: 10.1109/JPROC.2020.3046112.
- [7] D. Walch, A. Geiger and C. Sultrop, "Inter-Turn Short Circuit Faults and Mitigation Measures for Dual-Three Phase Machines," 2024 International Conference on Electrical Machines (ICEM), Torino, Italy, 2024, pp. 1-7, doi: 10.1109/ICEM60801.2024.10700240.
- [8] Sheikdavood, K., A. Balachandran, and Dineshkumar Thangaraju. "Video Based 3D Convolution Network for Air Quality Assessment." In 2023 9th International Conference on Advanced Computing and Communication Systems (ICACCS), vol. 1, pp. 1129-1132. IEEE, 2023.
- [9] S. Sivaranjani, M. K. Tharnees, M. Thamilvanan and K. Vasantharaj, "Detection of Degradation in Infrastructure using IoT," 2023 International Conference on Sustainable Computing and Data Communication Systems (ICSCDS), Erode, India, 2023, pp. 1107-1112, doi: 10.1109/ICSCDS56580.2023.10104719.
- [10] Sheikdavood, K., K. Soundar, M. G. Yaswanth, and P. TarunKumar. "Smart Health Monitoring System for Coma Patients using IoT." In 2023 7th International Conference on Computing Methodologies and Communication (ICCMC), pp. 1342-1347. IEEE, 2023.