

| <i>Equipment</i>          | <i>Daily</i>                                                                     | <i>Weekly/ Monthly</i>                                                                      | <i>Critical watch points</i>                                                                      |
|---------------------------|----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------|
| Baling machine            | Check hydraulic fluid level; clear wire jams; inspect bale tie mechanism         | Monthly: lubricate machinery; check bale wire tension; inspect safety guards                | Blade wear, hydraulic leaks, electrical panel moisture - cause of most baler fires                |
| Conveyor belt             | Check belt tension and alignment; clear material jams; inspect motor temperature | Monthly: clean rollers; check belt splice; grease bearings; inspect emergency stop function | Misaligned belt wears out in 2–3 months; single most common conveyor failure                      |
| Forklift / pallet mover   | Check tyre pressure; test horn and lights; check hydraulic hose condition        | Monthly: battery water level (for electric); chain lubrication; brake test                  | Overloading beyond rated capacity causes tipping - common with heavy bale stacking                |
| Weighbridge / floor scale | Zero calibration before first load; clean platform of debris                     | Monthly: full calibration against reference weight; inspect load cell connections           | Uncalibrated scales = systematic billing errors with buyers - hard to catch and costly to resolve |
| Generator (if applicable) | Check fuel and oil levels; test start and transfer switch                        | Monthly: coolant level, belt condition, air filter cleaning                                 | Diesel quality in rural areas causes injector fouling - use filtered diesel                       |