

PETRONAS COOLANT

High Performance Summer Coolant

PETRONAS COOLANT is a high performance summer coolant based on ethylene glycol containing a balance mixture of corrosion inhibitors. It provides good corrosion protection whether the cooling system be of predominantly aluminum or ferrous metal construction.

PETRONAS COOLANT is designed for use with cooling system of cars, trucks, buses and motorcycles

Applications

PETRONAS COOLANT is designed for use with radiator of cars, trucks, buses and motorcycles which is made from aluminum, copper or ferrous metal construction.

Customer Benefits

- Excellent corrosion protection for metallic parts of the cooling system
- Resists oxidation and corrosion from the high temperatures
- Compatibility with rubber components of cooling system
- Excellent heat transfer

Product Typicals

Characteristics	Typical
Clearness	Clear
Miscibility with water	Infinite
Freezing point, 50 v% distilled water, °C	-37
Pour Point, Undiluted °C	< 17.8
PH, 50 v% in water	8.05
Density	1.130

Instruction

1. Arrange the pure water in the clean vessel and then pour the Petronas coolant to the water.
2. Mix a Petronas coolant with water in a 30:70 ratio or maximum 50:50 (Do not put Petronas coolant more than 50% as the radiator will be over heat)
3. Stir to dissolve well proper mixture before pour to the clean radiator and need to change the coolant mixture every 1-2 years for the good efficiency of radiator.