

PETRONAS Urania 3000 NGV

10W-40

Designed with StrongTech™, engineered with core strength to stay stronger for longer in Mobile Gas Engine (CNG, LNG, LPG) for Commercial Vehicles

It's tough out there and getting tougher for your commercial transport business. The world is changing at breakneck speed, throwing an ever-growing, intense set of external challenges and pressures your way. Yet, in the face of all this, you are relied upon to get the job done. The same is true of your truck.

Description and Applications

PETRONAS Urania 3000 NGV 10W-40 is a semi synthetic engine oil formulated with StrongTech™ technology, engineered to stay stronger for longer, forming a uniquely strong fluid film to extend drain intervals and engine life, maximize performance and keep your business and your trucks moving. This helps in extending engine life and reduces the total cost of ownership. Demonstrated by field trials and engine test performed on Mobile Gas Applications. This helps in extending engine life and reduces the total cost of ownership.

PETRONAS Urania 3000 NGV 10W-40 ensures excellent oxidation & nitration control in addition to outstanding wear and deposit benefits and is suitable for most types of four stroke gas-fueled (CNG, LNG or LPG) engines, as well as two stroke diesel engines. It is ideal for buses and trucks that seek cost competitive supply of engine oils suitable for use in heavy duty gas-fueled engines.

Benefits

PETRONAS Urania 3000 NGV 10W-40 enhances your Business Profits and your vehicle availability while significantly reducing your operating costs through:

- **Long Drain Interval and Engine Life** driven by:
 - o Improved thermal stability, preventing oil ageing
 - o Reduced harmful deposit formation for improved engine cleanliness
 - o Reduces acidic levels that lead to corrosion, making your fleet engines more durable and longer life.
 - o Long oil drain capability up to 40.000 km (30.000 km for Bus application)

Provides outstanding Driving Experience through:

- **Excellent low temperature viscosity for improved lubrication during start-up**

Approvals, Specifications and Recommendations

Performance

- Cummins CES 20085
- Detroit Diesel DDC 93K216
- Volvo CNG
- MB 226.9
- Renault RGD

Note: Always consult your owner's manual to check recommended viscosity grade and specifications for your specific vehicle

Typical Physical Data

Parameters	Method	Unit	Typical Value
Appearance	-	-	Bright & Clear
Density @15°C	ASTM D 4052	g/cm ³	0.864
Kinematic Viscosity @100°C	ASTM D 445	mm ² /s (cSt)	14.8
Viscosity Index	ASTM D 2270	-	152
Flash Point COC	ASTM D 92	°C	230
Sulphated Ash	ASTM D 874	%	0.84
TBN	ASTM D 2896	mgKOH/g	6.5
Pour Point	ASTM D 97	°C	-30

All technical data is provided for reference only. These characteristics are typical of current production. Whilst future production will conform to PLI's specification, variations in these characteristics may occur.

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refer to product SDS or contact us at: www.pli-petronas.com

Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contained herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortious action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.

Code: 71819