



PETRONAS MACH 5 SL 10W-30

Extra High Performance, Extra Heavy-Duty Engine Oil

PETRONAS Mach 5 10W-30 is an extra high performance multigrade engine oil specially designed and formulated to provide very high level of engine protection and superior performance in engines running under the severest driving conditions. It is exclusively formulated with premium quality unconventional base oils and advanced additives technology to provide the outstanding thermal and oxidation stability that ensure minimum oil thickening at very high operating temperature, excellent deposits control and minimized engine wear and tear.

Engineered based on extensive field, racetrack, rally and testing experiences over many years, PETRONAS Mach 5 10W-30 provides the outstanding performance lubricant that ensure complete engine protections especially for engines operating under the severest operating conditions throughout today's long drain interval.

Applications

Recommended for use in all types of passenger cars especially the latest model high performance cars fitted with fuel injections, multi-valves, turbochargers or superchargers operating under the most extreme conditions. Also suitable for engines requiring API SJ, SH, SG or lower performance levels.

Features and Benefits

- Outstanding engine protection at all driving conditions
- Prolongs engine life
- Outstanding engine cleanliness – protects against engine sludge and varnish deposits
- Resists viscosity and thermal breakdown even in severe service
- Very high shear stability – stay in grade
- Easier cold engine starting – minimize friction and wear at start-up

Specifications, Approvals and Recommendation

- API SL/CF

PETRONAS MACH 5 SL 10W-30

Extra High Performance, Extra Heavy-Duty Engine Oil

Typical Properties

Characteristics	Typical Value
Density @ 15 °C, kg/l	0.8768
Pour Point, °C	-33
Flash Point, °C	228
Kinematic Viscosity, cSt	
@ 40 °C	72.9
@ 100 °C	10.2
Viscosity Index	132
Cold Cranking Visc, cP	
@ -25 °C	4130
Sulphated Ash, %wt	0.81
TBN, mg KOH/g	7.6
ASTM Colour	L1.5 to L3.5

* All technical data is provided for reference only.

Health, Safety and Environment

For further assistance on product MSDS, recommendation or technical queries, please liaise with the regional technical services engineer or contact HQ technical engineers.