

PRODUCT INFORMATION



VALVOLINE™ SYNTHETIC BRAKE FLUID DOT 3

Valvoline™ Synthetic Brake Fluid DOT 3 is a high quality fully synthetic brake fluid suitable for brake and clutch system that requires brake fluid with minimum DOT 3 Standard for all passenger car, pick up and bus & truck.

SYNTHETIC BRAKE FLUID DOT 3 ADVANTAGES

- Protect metal parts ie Brake Pump from wear
- High boiling point, High resistant to heat from brake
- Do not damage seal or rubber in the system

PERFORMANCE LEVEL

FMVSS 116 DOT 3

SAE J-1703

ISO 4925 Class 3

Typical properties:

Typical Properties characteristics are based on current production. Whilst future will confirm to Valvoline specification, variations in these characteristics may occur.

Typical Characteristics	
Test	Typical Properties
Equilibrium Reflux Boiling Point, °C	273
Wet Equilibrium Reflux Boiling Point, °C	149
Kinematic Viscosity, cSt @ -40°C	1225
Kinematic Viscosity, cSt @ 100°C	2.4
pH Value	10.2

This product is not likely to present any significant health or safety hazards when properly used in recommended application and good standards of personal hygiene are maintained. Reference is made to Safety Data Sheet (SDS) which is available on request via your local technical or sales representative.

This information only applies to products manufactured in the following location(s): Thailand

Effective Date

Oct 2020

Author

AUS