



Certificate of Analysis

Product name: HP GEAR OIL 80W-90 LSD
Batch No.: B251226042
Received Date: 26-12-25
Tested Date: 26-12-25

Document No.: 225121056
Issue Date: 26-12-25
Reference: FG2528521
Blending Date: 26-12-25

CONTROL TEST	Unit	Method	Control Limit	Test result
APPEARANCE	-	VISUAL	BRIGHT & CLEAR	BRIGHT & CLEAR
COLOR	-	ASTM D1500	3.0 MAX	2.5
DENSITY @30 °C	g/mL	ASTM D4052	REPORT	0.8888
VISCOSITY @40°C	mm ² /s	ASTM D445	REPORT	141.5
VISCOSITY @100°C	mm ² /s	ASTM D445	15.00 - 17.00	15.74
VISCOSITY INDEX	-	ASTM D2270	REPORT	116
FLASH POINT (COC)	°C	ASTM D92	230 MIN	238
POUR POINT	°C	ASTM D6749	-27 MAX	-33
FOAMING TEST (SEQUENCE I)	ml/ml	ASTM D892	20/0 MAX	NIL/0
FOAMING TEST (SEQUENCE II)	ml/ml	ASTM D892	50/0 MAX	10/0
FOAMING TEST (SEQUENCE III)	ml/ml	ASTM D892	20/0 MAX	NIL/0
BROOKFIELD VISCOSITY @-26°C	mPa.s	ASTM D 2983	150,000 MAX	147600
COLOR (Compare with Standard)	-	VISUAL	SAME AS STANDARD	SAME AS STANDARD

Approved by : Titipaporn Buakhaw
(Supply Chain Manager, Thailand)
Valvoline (Thailand) Ltd.,

Scope of report Valvoline has stringent and standard quality assurance procedures to ensure the product specifications and performances .| The test results presented within this report pertain exclusively to the sample submitted for analysis.| The sampling procedures are controlled and detailed in the related operational procedures.| This test report is the property of Valvoline (Thailand) Ltd. and may not be reproduced , in part or in whole, without explicit written consent.