



Certificate of Analysis

Product name: HP GEAR OIL GL-5 SAE 80W90
Batch No.: B251007041
Received Date: 07-10-25
Tested Date: 07-10-25

Document No.: 225100260
Issue Date: 07-10-25
Reference: FG2521960
Blending Date: 07-10-25

CONTROL TEST	Unit	Method	Control Limit	Test result
APPEARANCE	-	VISUAL	B&C	B&C
COLOR	-	ASTM D1500	REPORT	1.0
DENSITY@30 °C	g/mL	ASTM D4052	REPORT	0.8743
VISCOSITY @40°C	mm ² /s	ASTM D445	REPORT	139.0
VISCOSITY @100°C	mm ² /s	ASTM D445	14.50-18.00	15.56
VISCOSITY INDEX	-	ASTM D2270	95 MIN	116
FLASH POINT (COC)	°C	ASTM D92	REPORT	246
POUR POINT	°C	ASTM D6749	REPORT	-33
FOAMING TEST (SEQUENCE II)	ml/ml	ASTM D892	50/0 MAX.	10/0
BROOKFIELD VISCOSITY @-26°C	mPa.s	ASTM D 2983	150,000 MAX.	119000

Approved by : Titipaporn Buakhow
(Supply Chain Manager, Thailand)
Valvoline (Thailand) Ltd.,

Scope of report | Valvoline has stringent and standard quality assurance procedures to ensure the product specifications and performances .| The test results presented within this report pertain exclusively to the sample submitted for analysis.| The sampling procedures are controlled and detailed in the related operational procedures.| This test report is the property of Valvoline (Thailand) Ltd. and may not be reproduced , in part or in whole, without explicit written consent.