



Certificate of Analysis

Product name: VALVOLINE HLP 46 (HYDRAULIC)
Batch No.: B251009093
Received Date: 09-10-25
Tested Date: 09-10-25

Document No.: 225100390
Issue Date: 09-10-25
Reference: FG2522250
Blending Date: 09-10-25

CONTROL TEST	Unit	Method	Control Limit	Test result
APPEARANCE	-	VISUAL	BRIGHT & CLEAR	BRIGHT & CLEAR
COLOR	-	ASTM D1500	1.5 MAX	L0.5
DENSITY @30 °C	g/mL	ASTM D4052	REPORT	0.8583
VISCOSITY @40°C	mm ² /s	ASTM D445	41.5 - 50.5	49.40
VISCOSITY @100°C	mm ² /s	ASTM D445	REPORT	7.251
VISCOSITY INDEX	-	ASTM D2270	95 MIN	106
FLASH POINT (COC)	°C	ASTM D92	210 MIN	242
FOAMING TEST (SEQUENCE II)	ml/ml	ASTM D892	50/0 MAX	10/0
WATER CONTENT	%	ASTM D6304	REPORT	0.0075

Approved by : Titipaporn Buakhow
(Supply Chain Manager, Thailand)
Valvoline (Thailand) Ltd.,

Scope of report | Valvoline has stringent and standard quality assurance procedures to ensure the product specifications and performances .| The test results presented within this report pertain exclusively to the sample submitted for analysis.| The sampling procedures are controlled and detailed in the related operational procedures.| This test report is the property of Valvoline (Thailand) Ltd. and may not be reproduced , in part or in whole, without explicit written consent.