



Certificate of Analysis

Product name: VALVOLINE ULTAMAX HLP 46 (HYDRAULIC)
Batch No.: B260310152
Received Date: 10-03-26
Tested Date: 10-03-26

Document No.: 226030313
Issue Date: 10-03-26
Reference: FG2605729
Blending Date: 10-03-26

CONTROL TEST	Unit	Method	Control Limit	Test result
APPEARANCE	-	VISUAL	BRIGHT & CLEAR	BRIGHT & CLEAR
COLOR	-	ASTM D1500	1.5 MAX	L0.5
DENSITY @30 °C	g/mL	ASTM D4052	REPORT	0.8585
VISCOSITY @40°C	mm ² /s	ASTM D445	41.5 - 50.5	48.40
VISCOSITY @100°C	mm ² /s	ASTM D445	REPORT	7.178
VISCOSITY INDEX	-	ASTM D2270	95 MIN	107
FLASH POINT (COC)	°C	ASTM D92	210 MIN	240
FOAMING TEST (SEQUENCE II)	ml/ml	ASTM D892	50/0 MAX	10/0
WATER CONTENT	%wt	ASTM D6304	REPORT	0.0053

Approved by : Titipaporn Buakhow
(Supply Chain Manager, Thailand)
Valvoline (Thailand) Ltd.,

Scope of report | Valvoline has stringent and standard quality assurance procedures to ensure the product specifications and performances .| The test results presented within this report pertain exclusively to the sample submitted for analysis.| The sampling procedures are controlled and detailed in the related operational procedures.| This test report is the property of Valvoline (Thailand) Ltd. and may not be reproduced , in part or in whole, without explicit written consent.