

PRODUCT INFORMATION



All Fleet HD SAE 15W-40

Valvoline All Fleet HD SAE 15W-40 is a heavy-duty diesel engine oil designed for use in a wide range of mixed fleet applications.

Valvoline All Fleet HD SAE 15W-40 is engineered for long-term lubrication and optimal engine performance. All Fleet HD SAE 15W-40 have been formulated to meet the API CI-4/SL performance level and are recommended for use in various models of buses, trucks, generator sets, heavy-duty equipment, etc.

ALL FLEET HD ADVANTAGES

- Ensures optimal engine performance with advanced additive technology.
- Protects the engine against wear and corrosion with the strong oil film.
- Provides long-term lubrication and keeps the engine clean over an extended drain period.
- Break down resistance with the thermal and oxidation stable oil film.

PERFORMANCE LEVEL

API CI-4/SL

Typical properties:

Typical Properties characteristics are based on current production. Whilst future will confirm to Valvoline specification, variations in these characteristics may occur.

Typical Characteristics	15W-40
Kinematic Viscosity, cSt @ 100 °C	14.61
Viscosity Index	133
TBN, mg KOH/g	10.2
Flash Point, COC, °C	232
Pour Point, °C, Max.	-33
CCS @ -20 °C, cP, Max.	6220

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local technical or sales representative.

This information only applies to products manufactured in the following location(s): Thailand

Product Code:

150184

Effective Date

Sep 2024

Author

NW