

PRODUCT INFORMATION



VALVOLINE™ ALL-FLEET™ E900 PLUS SAE 15W-40

Valvoline All-Fleet E900 Plus Engine Oil is formulated to provide enhanced oxidation control and shear stability demanded in modern diesel engines operating under a wide variety of service conditions, including engines with diesel particulate filters (DPF) and cooled exhaust gas recirculation (EGR). All-Fleet E900 Plus is blended with premium basestocks and high-quality additive chemistry to achieve the following benefits: high temperature piston deposit control, foam protection, soot dispersancy and oil-thickening control, oxidation inhibition, low temperature sludge protection, corrosion and rust inhibition, valve train wear protection and TBN retention. All-Fleet E900 Plus provides excellent performance in local stop and go routes, on-and off-highway, farm, construction, and mining applications.

All-Fleet E900 Plus is licensed for API service CK-4, CJ-4, CI-4 PLUS, CI-4, CH-4, SN and all prior gasoline categories.

All-Fleet E900 Plus is recommended for applications where Cummins CES 20086, Detroit Diesel DFS 93K222, Mack EOS-4.5, Volvo VDS-4.5, Caterpillar ECF-3 or Ford WSS-M2C171-F1 type performance levels are specified.

Typical Properties:	SAE 15W-40
KV100 (cSt)	14.9
KV40 (cSt)	113
Viscosity Index	137
Density (g/cm ³)	0.880
CCS @ -20°C, cP	<6600
HTHS @ 150°C, cP	4.2
Pour Point (°C)	-30
Sulfated Ash, mass %	<1.0
TBN (D-2896), meq KOH/g	10
Noack, % loss	11
Zinc, ppm	1100
Phosphorous, ppm	1010

Refer to Valvoline's Material Safety Data Sheet for health and safety information. This information only applies to products manufactured in Singapore

Effective Date:
Aug 21

Author:
AS