

PRODUCT INFORMATION



VALVOLINE™ MAXLIFE SAE 10W-40

Valvoline™ MaxLife SAE 10W-40 is the first motor oil specially formulated to address the unique needs of higher mileage engines. MaxLife is a blend of synthetic and premium conventional base stocks with seal conditioning agents, extra cleaning agents, additional anti-wear additives and novel friction modifiers for added protection. MaxLife provides performance benefits for high mileage, new and re-built engines.

Valvoline™ MaxLife SAE 10W-40 is approved and licensed for the newly adopted API SP classification, protecting GDI (Gasoline Direct Injection) engines from low-speed pre-ignition (LSPI).

MAXLIFE ADVANTAGES

- Conditions seals
- Formulated to reduce oil consumption
- Maximizes power output
- Helps reduce friction
- Resists thermal breakdown
- Reduces deposit formation

PERFORMANCE LEVEL

API SP

Typical properties:

Typical Properties characteristics are based on current production. Whilst future will confirm to Valvoline specification, variations in these characteristics may occur.

Typical Characteristics	
SAE Viscosity Grade	10W-40
Kinematic Viscosity, cSt @ 100°C	15.70
Viscosity Index	154
TBN, mg KOH/g	8.80
Pour Point, °C	-42
Flash Point, COC, °C	220
CCS@ -25 °C, cP	6200

This product is not likely to present any significant health or safety hazards when properly used in recommended application and good standards of personal hygiene are maintained. Reference is made to Safety Data Sheet (SDS) which is available on request via your local technical or sales representative.

This information only applies to products manufactured in the following location(s): Thailand

Product Code: 100043

Effective Date

Feb 2022

Author

AUS