

PRODUCT INFORMATION



VALVOLINE DURABLEND MOTOR OIL

DURABLEND SAE 5W-30 and 10W-40 are multi-grade motor oils formulated with the latest advanced additive technology and high-quality synthetic and highly refined base oils that protect modern engines against undesirable deposits, contamination, and thermal breakdown under severe service conditions.

DURABLEND SAE 5W-30 and 10W-40 are designed to meet the latest performance requirements of virtually all naturally aspirated, turbocharged, and supercharged passenger cars. Suitable for use with the flexible fuel like gasohol - gasoline-ethanol blends.

Advantages:

- Delivers daily-use protection for turbocharged gasoline Direct Injection engines from Low-Speed Pre-Ignition (LSPI) and timing chain wear
- Provides very good engine cleanliness through superior sludge and varnish protection
- Protect engine components against wear even in tough driving conditions
- Enhanced fuel efficiency (SAE 5W-30)

PERFORMANCE LEVEL

API SQ

ILSAC GF-7A (SAE 5W-30)

Typical properties:

Typical Properties characteristics are based on current production. Whilst future will confirm to Valvoline specifications, variations in these characteristics may occur.

Typical Characteristics

SAE Viscosity Grade	5W-30	10W-40
Kinematic Viscosity, cSt @ 100°C	10.55	15.02
Viscosity Index	156	154
TBN, mg KOH/g	7.2	7.2
Pour Point, °C	-36	-36
Flash Point, COC, °C	230	236
CCS, cP @ -30 °C	6446	-
CCS, cP @ -25 °C	-	6145

This product is not likely to present any significant health or safety hazards when properly used in recommended application and good standards of personal hygiene are maintained. Reference is made to Safety Data Sheet (SDS) which is available on request via your local sales representative or through our website <https://sds.valvoline.com>.

This information only applies to products manufactured in the following location(s): Thailand

Product Code:

5W-30 : 100096
10W-40 : 100097 100098

Effective Date

Nov 25

Author

CR