

PRODUCT INFORMATION



GEO MA SAE 40

Valvoline GEO MA is a conventional engine oil with advanced lubricating performance in gas stationary that is specially formulated with selected high-quality base stocks and high-performance additive components to provide outstanding lubrication of engines running on gases such as biogas, landfills, Sewer gas, etc.

Valvoline GEO MA also ensures excellent control of engine wear and engine cleanliness, while protecting against corrosion of all engine parts. The lubricant has the ability to neutralize acids and resist oxidation which helps prevent oil thickening.

Valvoline GEO MA is recommended for Power generation applications running on gases that may contain corrosive components i.e. Biogas, Landfill Gas or Sewer Gas.

GEO MA ADVANTAGES

- Medium ash
- Excellent oxidation /nitration control.
- Superior performance in resistance to acids
- Enhanced engine protection against wear and corrosion
- Capability of extended oil drains.

PERFORMANCE LEVEL

Caterpillar 33000, 34000, 35000, 36000 Series

Waukesha VHP, Co-Gen

Jenbacher Type 2, 3, 4 &6

Typical properties:

Typical Properties characteristics are based on current production. Whilst future will confirm to Valvoline specification, variations in these characteristics may occur.

Typical Characteristics	SAE 40
Density @ 30°C, g/cm ³	0.8708
Kinematic Viscosity, cSt @ 40 °C	133.0
Kinematic Viscosity, cSt @ 100 °C	14.95
Viscosity Index	114
TBN, mg KOH/g	6.0
Flash Point, COC, °C	>210
Pour Point, °C	-21
Sulfated Ash, %wt	0.7

This product is not likely to present any significant health or safety hazards when properly used in recommended application and good standards of personal hygiene are maintained. Reference is made to Safety Data Sheet (SDS) which is available on request via your local technical or sales representative.

This information only applies to products manufactured in the following location(s): Thailand

Product Code:

200001

Effective Date

Sep 2024

Author

NW