

PRODUCT INFORMATION



VALVOLINE GEAR GARD SAE 80W-90

Valvoline GEAR GARD 80W-90 is multipurpose Sulphur-phosphorus based extreme pressure superior quality heavy-duty gear oils. The products have been specially formulated to meet severe duty operation in heavily loaded gear systems, such as hypoid, spiral, bevel, worm gears, where an active GL-4 performance oils are required. The products offer excellent performance under severe stress, heavy loads and low temperatures.

Valvoline Gear Gard EP 80W-90 have been fully inhibited with advanced additive chemistry to combat extreme pressure, wear, corrosion, oxidation and foaming. Valvoline Gear Gard SAE 80W-90 is recommended for hypoid, spiral, bevel or worm gear transmission system of cars, buses, trucks and tractors requiring EP type lubricants.

GEAR GARD ADVANTAGES

- Enhanced performance in both low and high temperature operating conditions
- Excellent wear protection under high loads and extreme pressure
- Protects parts from rust and corrosion
- Fully compatible with yellow metals including copper, bronze, brass
- Outstanding performance of synchronizers

PERFORMANCE LEVEL

API GL-4

Typical properties:

Typical Properties characteristics are based on current production. Whilst future will confirm to Valvoline specification, variations in these characteristics may occur.

Typical Characteristics	
SAE Grade	80W-90
Kinematic Viscosity, cSt @ 100 C	16.35
Viscosity Index	121
Pour Point, C, Max.	-33
Flash Point, COC, C	240

This product is not likely to present any significant health or safety hazards when properly used in recommended application and good standards of personal hygiene are maintained. Reference is made to Safety Data Sheet (SDS) which is available on request via your local technical or sales representative.

This information only applies to products manufactured in the following location(s): Thailand

Effective Date

Oct 2020

Author

NW