

PRODUCT INFORMATION



VALVOLINE INDUSTRIAL GEAR OIL 220 / 320

Valvoline Industrial Gear Oils are premium extreme pressure gear compounds designed to meet the heavy-duty demands of a variety of industrial gear applications including those operating under such severe conditions as critical sliding velocities and shock loading that may occur under certain loading situations. They are formulated from high quality selected base oils with an appropriate additive package to provide the best combination of performance properties, such as extreme pressure and oxidation resistance, required in several industrial applications.

Valvoline Industrial Gear Oils may be used for lubricating industrial enclosed bearings both in industrial and mining applications with helical, herringbone, bevel and spur gears. These oils exhibit high Timken OK loads and excellent results on the FZG and Four Ball Wear Test.

PERFORMANCE LEVEL

AISE 224 (US Steel 224)

AGMA 9005-F16

David Brown S1.53.101(E)

DIN 51517 Part III,

Typical properties:

Typical Properties characteristics are based on current production. Whilst future will confirm to Valvoline specification, variations in these characteristics may occur.

Typical Characteristics

ISO VG	220	320
Kinematic Viscosity, cSt @ 40 °C	240.8	332.3
Viscosity Index	97	97
Pour Point, °C, Max.	-9	-6
Flash Point, COC, °C	250	254
FZG Scuffing Test, load stage	12	12
Foaming Sequence I, ml/ml	0/0	0/0
Foaming Sequence II, ml/ml	0/0	0/0
Foaming Sequence III, ml/ml	0/0	0/0

This product is not likely to present any significant health or safety hazards when properly used in recommended application and good standards of personal hygiene are maintained. Reference is made to Safety Data Sheet (SDS) which is available on request via your local technical or sales representative.

This information only applies to products manufactured in the following location(s): Thailand

Effective Date

Apr 2024

Author

NW