

PRODUCT INFORMATION



VALVOLINE™ Amber EP 3 Grease

Valvoline Amber EP 3 Grease are extreme pressure greases formulated with premium quality mineral base oil and special additive chemistry. They possess excellent load carrying and anti-wear properties. Valvoline Amber EP 3 greases provide outstanding mechanical and roll stability, excellent wear protection, good resistance to water washout and effective protection from corrosion under severe operating conditions. They provide continuous lubrication as grease stays between lubricated surfaces.

Valvoline Amber EP 3 Grease are recommended for lubrication of both plain & anti-friction bearings in a wide variety of applications such as automotive, earthmoving equipment, gear coupling, mining equipment & other industrial applications.

AMBER EP 3 GREASE ADVANTAGES

- Excellent extreme pressure properties for efficient lubrication
- Good water resistance properties
- Excellent protection against rust & corrosion
- Low oil separation coupled with excellent mechanical and roll stability

PERFORMANCE LEVEL

IS 7623 : 2019 Specification

IPSS : 1-09-005-20 3rd Rev specification

Typical properties:

Typical Properties characteristics are based on current production. Whilst future will confirm to Valvoline specification, variations in these characteristics may occur.

Typical Characteristics	
Product	Amber EP3
NLGI Grade	3
Type of Soap	Lithium and Proprietary
Worked Penetration (60 Strokes) @ 25°C	220-250
Dropping Point, °C, min	180
4 Ball Weld Load, Kg	250
4 Ball Wear Scar Dia. mm, max	0.6
Timken Ok Load, Kg, min	22
Corrosion preventive, Rating, Max	1

This product is not likely to present any significant health or safety hazards when properly used in recommended application and good standards of personal hygiene are maintained. Reference is made to Safety Data Sheet (SDS) which is available on request via your local technical or sales representative.

This information only applies to products sold in the following location(s): Thailand

Product Code: 350016 = 0.5 kg
350018 = 2 kg

Effective Date

Author

Oct 2023

NW