

Certificate of Analysis

Product: HYDRAULIC 68 A
Batch Number : 2604090508

Properties	Test Method	Unit	Specification	Result
Appearance	Visual	-	Bright & Clear	Bright & Clear
ASTM Color	ASTM D 1500	-	Report	L1.0
Density @15 degree C	ASTM D 4052	g/cm3	Report	0.8842
Density @ 30 degree C	ASTM D 4052	g/cm3	Report	0.8748
Kinematic Viscosity @ 40 degree C	ASTM D 445	cSt.	64 -72	68.02
Kinematic Viscosity @ 100 degree C	ASTM D 445	cSt.	Report	8.680
Viscosity Index	ASTM D 2270	-	95 min.	99
Foaming Characteristic (Sequence I)	ASTM D 892	mL/mL	150/0 max.	Nil/0
Foaming Characteristic (Sequence II)	ASTM D 892	mL/mL	75/0 max.	10/0
Foaming Characteristic (Sequence III)	ASTM D 892	mL/mL	150/0 max.	Nil/0
Zinc Content	ASTM D 4951	%wt.	0.027 - 0.041	0.0335
Phosphorus Content	ASTM D 4951	%wt.	0.023 - 0.035	0.0314
Flash Point (COC)	ASTM D 92	degree C	215 min.	244
Pour Point	ASTM D 5950	degree C	Report	-6
Total Acid Number	ASTM D 664	mg KOH/g	1.5 max.	0.62
Water Content	ASTM D 95	%vol.	Nil	Nil

The product passes the specification requirements.