

PRODUCT INFORMATION



Valvoline HLP (Hydraulic)

Valvoline HLP is a conventional hydraulic oil, formulated with high quality mineral base oils and anti-wear additives to offer the solid hydraulic performance in a wide range of applications.

Valvoline HLP hydraulic oils meeting DIN 51524 part 2 (HLP) standard, are available in three ISO viscosity grades (ISO 32, 46, 68).

PERFORMANCE LEVEL

DIN 51524 Part II (HLP)
ISO 11158 HM

Typical properties:

Typical Properties characteristics are based on current production. Whilst future will confirm to Valvoline specification, variations in these characteristics may occur.

Typical Characteristics

ISO	VG 32	VG 46	VG 68
Kinematic Viscosity, cSt @ 40 °C	34.33	48.56	69.28
Kinematic Viscosity, cSt @ 100 °C	5.68	7.11	9.08
Viscosity Index	103	103	105
Pour Point, °C, Max.	-9	-9	-9
Flash Point, COC, °C	228	232	250
Rust Test D665, A&B, 24 hrs.	Pass	Pass	Pass
Copper Strip Corrosion	1a	1a	1a
Foaming Test Sequence I	10/0	10/0	10/0
Foaming Test Sequence II	10/0	10/0	10/0
Foaming Test Sequence III	10/0	10/0	10/0

This product is not likely to present any significant health or safety hazards when properly used in recommended application and good standards of personal hygiene are maintained. Reference is made to Safety Data Sheet (SDS) which is available on request via your local technical or sales representative.

This information only applies to products manufactured in the following location(s): Thailand

Product Code:

Valvoline HLP 32 - 18L	400025
Valvoline HLP 32 - 200L	400003
Valvoline HLP 46 - 18L	400011
Valvoline HLP 46 - 200L	400001
Valvoline HLP 68 - 18L	400002
Valvoline HLP 68 - 200L	400004
Valvoline HLP 68 - 1000L	400012

Effective Date: Jul 2024

Author: NW