

PRODUCT INFORMATION



Valvoline Ultramax HLP (Hydraulic)

Valvoline Ultramax HLP hydraulic oils are purposefully to be suitable for a variety of applications. Their ability to withstand a wide temperature range and heavy loads makes them ideal types of hydraulic oils to be used in harsh working conditions where superior protection and performance are required. They are recommended for both mobile and static hydraulic systems, as well as industrial, off-road, earthmoving, road building, and mining applications.

Valvoline Ultramax HLP are formulated with high-quality premium base oils and anti-wear additives to deliver the excellent oxidation stability and superior anti-wear, anti-corrosion, anti-foaming characteristics. They provide high-load capacity, and the ability to withstand high pressure.

PERFORMANCE LEVEL

ASTM D6158 HM
Bosch Rexroth RDE-90235
DIN 51524 Part II (HLP)
Eaton Vickers I-286S, M2950-S
Five Cincinnati P-68, P-69, P-70
GB 11118.1L-HM
GM LS-2

ISO 11158 HM
JCMAS HK P041
Parker Denison HF-0, HF-1, HF-2
US Steel 126
ZF TE-ML 07H, 21M

Typical properties:

Typical Properties characteristics are based on current production. Whilst future will confirm to Valvoline specification, variations in these characteristics may occur.

Typical Characteristics

ISO	VG 32	VG 46	VG 68	VG 100
Kinematic Viscosity, cSt @ 40 °C	34.50	48.56	68.72	99.76
Kinematic Viscosity, cSt @ 100 °C	5.78	7.30	9.20	11.70
Viscosity Index	107	110	109	105
Pour Point, °C, Max.	-12	-12	-12	-9
Flash Point, COC, °C	224	242	238	268
Rust Test D665, A&B, 24 hrs.	Pass	Pass	Pass	Pass
Copper Strip Corrosion	1a	1a	1a	1a
Foaming Test Sequence I	0/0	0/0	0/0	0/0
Foaming Test Sequence II	10/0	0/0	0/0	0/0
Foaming Test Sequence III	0/0	0/0	0/0	0/0

This product is not likely to present any significant health or safety hazards when properly used in recommended application and good standards of personal hygiene are maintained. Reference is made to Safety Data Sheet (SDS) which is available on request via your local technical or sales representative.

This information only applies to products manufactured in the following location(s): Thailand

Product Code:

Valvoline Ultramax HLP 32 - 18L	400014
Valvoline Ultramax HLP 32 - 200L	400005
Valvoline Ultramax HLP 46 - 18L	400018
Valvoline Ultramax HLP 46 - 200L	400006
Valvoline Ultramax HLP 68 - 18L	400007
Valvoline Ultramax HLP 68 - 200L	400008
Valvoline Ultramax HLP 68 - 1000L	400013
Valvoline Ultramax HLP 100 - 200L	400024

Effective Date: Jul 2024

Author: NW