

Github(동빈나) ---

C:\Users\석유진>git

usage: git [--version] [--help] [-C <path>] [-c <name>=<value>]
 [--exec-path[=<path>]] [--html-path] [--man-path] [--info-path]
 [-p | --paginate | -P | --no-pager] [--no-replace-objects] [--bare]
 [--git-dir=<path>] [--work-tree=<path>] [--namespace=<name>]
 <command> [<args>]

These are common Git commands used in various situations:

start a working area (see also: git help tutorial)

- clone Clone a repository into a new directory
- init Create an empty Git repository or reinitialize an existing one

work on the current change (see also: git help everyday)

- add Add file contents to the index
- mv Move or rename a file, a directory, or a symlink
- reset Reset current HEAD to the specified state
- rm Remove files from the working tree and from the index

examine the history and state (see also: git help revisions)

- bisect Use binary search to find the commit that introduced a bug
- grep Print lines matching a pattern
- log Show commit logs
- show Show various types of objects
- status Show the working tree status

grow, mark and tweak your common history

- branch List, create, or delete branches
- checkout Switch branches or restore working tree files
- commit Record changes to the repository
- diff Show changes between commits, commit and working tree, etc
- merge Join two or more development histories together
- rebase Reapply commits on top of another base tip
- tag Create, list, delete or verify a tag object signed with GPG

collaborate (see also: git help workflows)

- fetch Download objects and refs from another repository
- pull Fetch from and integrate with another repository or a local branch
- push Update remote refs along with associated objects

'git help -a' and 'git help -g' list available subcommands and some concept guides. See 'git help <command>' or 'git help <concept>' to read about a specific subcommand or concept.

C:\Users\석유진>git --version
git version 2.22.0.windows.1

C:\Users\석유진>git config --global user.name sukyoujin

C:\Users\석유진>git config --global user.email gemmy_@naver.com

C:\Users\석유진>cd C:\Education

C:\Education>git clone https://github.com/sukyoujin/Git-Tutorial.git
Cloning into 'Git-Tutorial'...
warning: You appear to have cloned an empty repository.

C:\Education>cd C:\Education\Git-Tutorial

C:\Education\Git-Tutorial>git add document.txt

C:\Education\Git-Tutorial>git commit -m "Add Text File [document.txt]
[master (root-commit) eff749b] Add Text File [document.txt]
1 file changed, 1 insertion(+)
create mode 100644 document.txt

C:\Education\Git-Tutorial>git push
Enumerating objects: 3, done.
Counting objects: 100% (3/3), done.
Writing objects: 100% (3/3), 233 bytes | 33.00 KiB/s, done.
Total 3 (delta 0), reused 0 (delta 0)
To https://github.com/sukyoujin/Git-Tutorial.git
* [new branch] master -> master

파일 생성 및 수정 후 add, commit, push 하기-----
C:\>cd C:\Tutorials

C:\Tutorials>git clone https://github.com/sukyoujin/Git-Tutorial.git
Cloning into 'Git-Tutorial'...
remote: Enumerating objects: 3, done.
remote: Counting objects: 100% (3/3), done.
remote: Total 3 (delta 0), reused 3 (delta 0), pack-reused 0
Unpacking objects: 100% (3/3), done.

```
C:\₩Tutorials>dir
C 드라이브의 볼륨에는 이름이 없습니다.
볼륨 일련 번호: 6EB0-7DBA
C:\₩Tutorials 디렉터리
2019-07-21 오전 10:05 <DIR> .
2019-07-21 오전 10:05 <DIR> ..
2019-07-21 오전 10:05 <DIR> Git-Tutorial
0개 파일 0 바이트
3개 디렉터리 8,544,256,000 바이트 남음
```

```
C:\₩Tutorials>cd Git-Tutorial
```

```
C:\₩Tutorials\₩Git-Tutorial>dir
C 드라이브의 볼륨에는 이름이 없습니다.
볼륨 일련 번호: 6EB0-7DBA
C:\₩Tutorials\₩Git-Tutorial 디렉터리
2019-07-21 오전 10:05 <DIR> .
2019-07-21 오전 10:05 <DIR> ..
2019-07-21 오전 10:05 2 document.txt
1개 파일 2 바이트
2개 디렉터리 8,544,391,168 바이트 남음
```

```
C:\₩Tutorials\₩Git-Tutorial>git status
On branch master
Your branch is up to date with 'origin/master'.
Untracked files:
  (use "git add <file>..." to include in what will be committed)
    my_module.java.txt
nothing added to commit but untracked files present (use "git add" to track)
```

```
C:\₩Tutorials\₩Git-Tutorial>git add my_module.java.txt //git add +파일명
```

```
C:\₩Tutorials\₩Git-Tutorial>git status
On branch master
Your branch is up to date with 'origin/master'.
Changes to be committed:
  (use "git reset HEAD <file>..." to unstage)
    new file:   my_module.java.txt
```

```
C:\₩Tutorials\₩Git-Tutorial>git reset my_module.java.txt //수정 내역 삭제 명령
```

```
C:\₩Tutorials\₩Git-Tutorial>git status
On branch master
Your branch is up to date with 'origin/master'.
Untracked files:
  (use "git add <file>..." to include in what will be committed)
    my_module.java.txt
nothing added to commit but untracked files present (use "git add" to track)
```

```
C:\₩Tutorials\₩Git-Tutorial>git add . //git add . (모든 파일)
```

```
C:\₩Tutorials\₩Git-Tutorial>git status
On branch master
Your branch is up to date with 'origin/master'.
Changes to be committed:
  (use "git reset HEAD <file>..." to unstage)
    new file:   my_module.java.txt
//git commit -m "Add +파일명 +메모"
C:\₩Tutorials\₩Git-Tutorial>git commit -m "Add my_module.java.txt [Add]"
[master cf3aba7] Add my_module.java.txt [Add]
1 file changed, 1 insertion(+)
create mode 100644 my_module.java.txt
```

```
C:\₩Tutorials\₩Git-Tutorial>git push //git push
Enumerating objects: 4, done.
Counting objects: 100% (4/4), done.
Delta compression using up to 4 threads
Compressing objects: 100% (2/2), done.
Writing objects: 100% (3/3), 325 bytes | 65.00 KiB/s, done.
Total 3 (delta 0), reused 0 (delta 0)
To https://github.com/sukyoujin/Git-Tutorial.git
    eff749b..cf3aba7 master -> master
```

```
C:\₩Tutorials\₩Git-Tutorial>git status
On branch master
Your branch is up to date with 'origin/master'.
nothing to commit, working tree clean
```

```
C:\₩Tutorials\₩Git-Tutorial>git status //(수정 후 확인함)
On branch master
Your branch is up to date with 'origin/master'.
Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
```

```
(use "git checkout -- <file>..." to discard changes in working directory)
        modified:   my_module.java.txt
no changes added to commit (use "git add" and/or "git commit -a")
        //git checkout -- 파일명 (수정한 사항 무시 명령)
C:\₩Tutorials₩Git-Tutorial>git checkout -- my_module.java.txt

C:\₩Tutorials₩Git-Tutorial>git add .                //(다시 수정 후 add함)
```

```
C:\₩Tutorials₩Git-Tutorial>git commit -m "Add my_module.java.txt [Add]"
On branch master
Your branch is ahead of 'origin/master' by 1 commit.
    (use "git push" to publish your local commits)
nothing to commit, working tree clean
```

```
C:\₩Tutorials₩Git-Tutorial>git status
On branch master
Your branch is ahead of 'origin/master' by 1 commit.
    (use "git push" to publish your local commits)
nothing to commit, working tree clean
```

```
C:\₩Tutorials₩Git-Tutorial>git push
Enumerating objects: 5, done.
Counting objects: 100% (5/5), done.
Delta compression using up to 4 threads
Compressing objects: 100% (2/2), done.
Writing objects: 100% (3/3), 330 bytes | 82.00 KiB/s, done.
Total 3 (delta 0), reused 0 (delta 0)
To https://github.com/sukyoujin/Git-Tutorial.git
    cf3aba7..f07874d  master -> master
```

```
github commit 내역 수정하기 (특정 지점으로 회귀) -----
C:\₩Tutorials₩Git-Tutorial>git pull
Already up to date.
```

```
C:\₩Tutorials₩Git-Tutorial>git add .                //새 파일 생성, add, commit, push 함
```

```
C:\₩Tutorials₩Git-Tutorial>git commit -m "Add my_module.java.txt"
[master 17d8a3c] Add my_module.java.txt
    1 file changed, 3 insertions(+), 1 deletion(-)
```

```
C:\₩Tutorials₩Git-Tutorial>git push
Enumerating objects: 5, done.
```

```
Counting objects: 100% (5/5), done.
Delta compression using up to 4 threads
Compressing objects: 100% (2/2), done.
Writing objects: 100% (3/3), 329 bytes | 82.00 KiB/s, done.
Total 3 (delta 0), reused 0 (delta 0)
To https://github.com/sukyoujin/Git-Tutorial.git
    f07874d..17d8a3c  master -> master
```

```
C:\₩Tutorials₩Git-Tutorial>git log                //로그 기록 보기
commit 17d8a3c474dd407c24fb4ea1bc44a673a9d9f607 (HEAD -> master, origin/maste
r, origin/HEAD)
Author: sukyoujin <gemmy_@naver.com>
Date:   Sun Jul 21 10:29:50 2019 +0900
    Add my_module.java.txt
commit f07874dc3f244c2deda816547e5baea6b92d55df
Author: sukyoujin <gemmy_@naver.com>
Date:   Sun Jul 21 10:13:11 2019 +0900
    Add my_module.java.txt [Add]:
commit cf3aba7f8d04c1e2ccaf1c30d2a4e6a26e2c6e40
Author: sukyoujin <gemmy_@naver.com>
Date:   Sun Jul 21 10:09:14 2019 +0900
    Add my_module.java.txt [Add]
commit eff749bf9280354873baf2e613f60485720dba2c
Author: sukyoujin <gemmy_@naver.com>
Date:   Thu Jul 18 06:17:02 2019 +0900
    Add Text File [document.txt]
```

```
C:\₩Tutorials₩Git-Tutorial>git reset --hard eff749bf9280354873baf2e613f6048572
0dba2c
HEAD is now at eff749b Add Text File [document.txt]    //특정 지점으로 원상복귀함
                                                    // git reset -hard +특정지점값
```

```
C:\₩Tutorials₩Git-Tutorial>git log
commit eff749bf9280354873baf2e613f60485720dba2c (HEAD -> master)
Author: sukyoujin <gemmy_@naver.com>
Date:   Thu Jul 18 06:17:02 2019 +0900
    Add Text File [document.txt]
```

```
C:\₩Tutorials₩Git-Tutorial>git push                //이전 상태와 다르니 예러가 남
To https://github.com/sukyoujin/Git-Tutorial.git
    ! [rejected]        master -> master (non-fast-forward)
error: failed to push some refs to 'https://github.com/sukyoujin/Git-Tutorial
.git'
```

hint: Updates were rejected because the tip of your current branch is behind
hint: its remote counterpart. Integrate the remote changes (e.g.
hint: 'git pull ...') before pushing again.
hint: See the 'Note about fast-forwards' in 'git push --help' for details.

```
C:\W\Tutorials\WGit-Tutorial>git push -f //강제로 push 해줌
Total 0 (delta 0), reused 0 (delta 0)
To https://github.com/sukyoujin/Git-Tutorial.git
+ 17d8a3c...eff749b master -> master (forced update)

C:\W\Tutorials\WGit-Tutorial>git add . //다시 생성,add, commit, push

C:\W\Tutorials\WGit-Tutorial>git commit -m "Add my_model.java sss"
[master db443e7] Add my_model.java sss
1 file changed, 1 insertion(+)
create mode 100644 git.txt.txt

C:\W\Tutorials\WGit-Tutorial>git push
Enumerating objects: 4, done.
Counting objects: 100% (4/4), done.
Delta compression using up to 4 threads
Compressing objects: 100% (2/2), done.
Writing objects: 100% (3/3), 284 bytes | 71.00 KiB/s, done.
Total 3 (delta 0), reused 0 (delta 0)
To https://github.com/sukyoujin/Git-Tutorial.git
eff749b..db443e7 master -> master

C:\W\Tutorials\WGit-Tutorial>git commit -amend //push 이후의 내용 수정으로, push내용을 바꿈
[a master fd78644] Add my_model.java sss&ddq
Date: Sun Jul 21 10:38:47 2019 +0900
1 file changed, 1 insertion(+)
create mode 100644 git.txt.txt
```

github Branch 사용 -----

```
C:\W\Education\WGit-Tutorials>git add a.txt //a.txt 라는 파일 생성 후 올리기

C:\W\Education\WGit-Tutorials>git commit -m "Add a.txt [a.txt]"
[master (root-commit) 3f380a4] Add a.txt [a.txt]
1 file changed, 1 insertion(+)
create mode 100644 a.txt

C:\W\Education\WGit-Tutorials>git push
```

```
Enumerating objects: 3, done.
Counting objects: 100% (3/3), done.
Writing objects: 100% (3/3), 214 bytes | 71.00 KiB/s, done.
Total 3 (delta 0), reused 0 (delta 0)
To https://github.com/sukyoujin/Git-Tutorials.git
* [new branch] master -> master

C:\W\Tutorials\WGit-Tutorial>git branch //branch 내역 확인 (master만 존재)
* master

C:\W\Tutorials\WGit-Tutorial>git branch develop //develop branch 생성

C:\W\Tutorials\WGit-Tutorial>git branch
develop
* master

C:\W\Tutorials\WGit-Tutorial>git checkout develop //switch branch to develop
Switched to branch 'develop'

C:\W\Tutorials\WGit-Tutorial>git branch
* develop
Master

C:\W\Education\WGit-Tutorials>git add . //develop서 수정, add, commit

C:\W\Education\WGit-Tutorials>git commit -m "Add a.txt [Add b]"
[develop 4a22d88] Add a.txt [Add b]
1 file changed, 2 insertions(+), 1 deletion(-)

C:\W\Education\WGit-Tutorials>git checkout master //다시 master로 바꿔서
Switched to branch 'master'
Your branch is up to date with 'origin/master'.

C:\W\Education\WGit-Tutorials>git merge develop //develop 작업내용과 merge
Updating 3f380a4..4a22d88
Fast-forward
a.txt | 3 ++-
1 file changed, 2 insertions(+), 1 deletion(-)

C:\W\Education\WGit-Tutorials>git push //github에 git push해주고
Enumerating objects: 5, done.
Counting objects: 100% (5/5), done.
```

Writing objects: 100% (3/3), 246 bytes | 82.00 KiB/s, done.
Total 3 (delta 0), reused 0 (delta 0)
To https://github.com/sukyoujin/Git-Tutorials.git
3f380a4..4a22d88 master -> master

C:\W\Education\W\Git-Tutorials>git branch -d develop //develop branch 삭제
Deleted branch develop (was 4a22d88).

C:\W\Education\W\Git-Tutorials>git branch
* master

Branch 간 충돌 해결 -----

C:\W\Education\W\Git-Tutorials>git branch develop

C:\W\Education\W\Git-Tutorials>git checkout develop //develop 내 수정1
Switched to branch 'develop'

C:\W\Education\W\Git-Tutorials>git add .

C:\W\Education\W\Git-Tutorials>git commit -m "Add a.txt [Add c]"
[develop d7dbfc9] Add a.txt [Add c]
1 file changed, 2 insertions(+), 1 deletion(-)

C:\W\Education\W\Git-Tutorials>git checkout master // master 내 수정2
Switched to branch 'master'
Your branch is up to date with 'origin/master'.

C:\W\Education\W\Git-Tutorials>git add .

C:\W\Education\W\Git-Tutorials>git commit -m "Add a.txt [Add c + //주석]"
[master ebff67c] Add a.txt [Add c + //주석]
1 file changed, 2 insertions(+), 1 deletion(-)

C:\W\Education\W\Git-Tutorials>git checkout develop
Switched to branch 'develop'

C:\W\Education\W\Git-Tutorials>git log //develop의 로그
commit d7dbfc97ce92c94f47b96efe3898a933a57fd2b3 (HEAD -> develop)
Author: sukyoujin <gemmy_@naver.com>
Date: Sun Jul 21 11:50:19 2019 +0900
Add a.txt [Add c]
commit 4a22d88acd566ad781dcc2a6521d0f2ed1c6e5a7 (origin/master)

Author: sukyoujin <gemmy_@naver.com>
Date: Sun Jul 21 11:38:19 2019 +0900
Add a.txt [Add b]
commit 3f380a4347140d360a4f7506fe955541b2c71540
Author: sukyoujin <gemmy_@naver.com>
Date: Sun Jul 21 11:34:58 2019 +0900
Add a.txt [a.txt]

C:\W\Education\W\Git-Tutorials>git checkout master //master의 로그
Switched to branch 'master'
Your branch is ahead of 'origin/master' by 1 commit.
(use "git push" to publish your local commits)
C:\W\Education\W\Git-Tutorials>git log
commit ebff67cefc7b8f302136f7279f32dc56ec199d80 (HEAD -> master)
Author: sukyoujin <gemmy_@naver.com>
Date: Sun Jul 21 11:53:50 2019 +0900
Add a.txt [Add c + //<EC><A3><BC><EC><84><9D>]
commit 4a22d88acd566ad781dcc2a6521d0f2ed1c6e5a7 (origin/master)
Author: sukyoujin <gemmy_@naver.com>
Date: Sun Jul 21 11:38:19 2019 +0900
Add a.txt [Add b]
commit 3f380a4347140d360a4f7506fe955541b2c71540
Author: sukyoujin <gemmy_@naver.com>
Date: Sun Jul 21 11:34:58 2019 +0900
Add a.txt [a.txt]

C:\W\Education\W\Git-Tutorials>git merge develop //merge 요청 시 오류 -수정 1과2 충돌
Auto-merging a.txt
CONFLICT (content): Merge conflict in a.txt
Automatic merge failed; fix conflicts and then commit the result.
문서 확인하면 자동으로 이렇게 저장돼 있고 :
수작업으로 지워 둘 중 하나 선택할 수 있음
a
b
<<<<<<< HEAD
c //충돌
=====
c
>>>>>>> develop
C:\W\Education\W\Git-Tutorials>git add . //수정 후 add, commit 해주고

C:\W\Education\W\Git-Tutorials>git commit -m "Add a.txt [Add c + //주석]"
[master 6ce1f31] Add a.txt [Add c + //주석]

```
C:\WEducation\WGit-Tutorials>git merge develop //다시 merge 하면
Already up to date.
```

```
C:\WEducation\WGit-Tutorials>git log //merged log printed
commit 6ce1f31ac1d200855009da8a1f982ab49ab2bf45 (HEAD -> master)
Merge: ebff67c d7dbfc9
Author: sukyoujin <gemmy_@naver.com>
Date: Sun Jul 21 12:00:50 2019 +0900
    Add a.txt [Add c + //<EC><A3><BC><EC><84><9D>}
commit ebff67cefc7b8f302136f7279f32dc56ec199d80
Author: sukyoujin <gemmy_@naver.com>
Date: Sun Jul 21 11:53:50 2019 +0900
    Add a.txt [Add c + //<EC><A3><BC><EC><84><9D>}
commit d7dbfc97ce92c94f47b96efe3898a933a57fd2b3 (develop)
Author: sukyoujin <gemmy_@naver.com>
Date: Sun Jul 21 11:50:19 2019 +0900
    Add a.txt [Add c]
commit 4a22d88acd566ad781dcc2a6521d0f2ed1c6e5a7 (origin/master)
Author: sukyoujin <gemmy_@naver.com>
Date: Sun Jul 21 11:38:19 2019 +0900
    Add a.txt [Add b]
commit 3f380a4347140d360a4f7506fe955541b2c71540
Author: sukyoujin <gemmy_@naver.com>
Date: Sun Jul 21 11:34:58 2019 +0900
commit 6ce1f31ac1d200855009da8a1f982ab49ab2bf45 (HEAD -> master)
Merge: ebff67c d7dbfc9
Author: sukyoujin <gemmy_@naver.com>
Date: Sun Jul 21 12:00:50 2019 +0900
    Add a.txt [Add c + //<EC><A3><BC><EC><84><9D>}
commit ebff67cefc7b8f302136f7279f32dc56ec199d80
Author: sukyoujin <gemmy_@naver.com>
Date: Sun Jul 21 11:53:50 2019 +0900
    Add a.txt [Add c + //<EC><A3><BC><EC><84><9D>}
commit d7dbfc97ce92c94f47b96efe3898a933a57fd2b3 (develop)
Author: sukyoujin <gemmy_@naver.com>
Date: Sun Jul 21 11:50:19 2019 +0900
    Add a.txt [Add c]
commit 4a22d88acd566ad781dcc2a6521d0f2ed1c6e5a7 (origin/master)
Author: sukyoujin <gemmy_@naver.com>
Date: Sun Jul 21 11:38:19 2019 +0900
    Add a.txt [Add b]
commit 3f380a4347140d360a4f7506fe955541b2c71540
```

```
Author: sukyoujin <gemmy_@naver.com>
Date: Sun Jul 21 11:34:58 2019 +0900
```

```
C:\WEducation\WGit-Tutorials>git branch -d develop //develop branch 다 썼으니 삭제
Deleted branch develop (was d7dbfc9).
```

```
C:\WEducation\WGit-Tutorials>git push //github에 git push done
Enumerating objects: 9, done.
Counting objects: 100% (9/9), done.
Delta compression using up to 4 threads
Compressing objects: 100% (3/3), done.
Writing objects: 100% (7/7), 590 bytes | 84.00 KiB/s, done.
Total 7 (delta 1), reused 0 (delta 0)
remote: Resolving deltas: 100% (1/1), done.
To https://github.com/sukyoujin/Git-Tutorials.git
    4a22d88..6ce1f31 master -> master
```

git에서 원격저장소 관리하기 -----

```
C:\WEducation\WGit-Tutorials>git remote //원격저장소에 뭐 있나 검색
origin
```

```
C:\WEducation\WGit-Tutorials>git remote show origin //origin 자세히 보기
* remote origin
Fetch URL: https://github.com/sukyoujin/Git-Tutorials.git
Push URL: https://github.com/sukyoujin/Git-Tutorials.git
HEAD branch: master
Remote branch:
    master tracked
Local branch configured for 'git pull':
    master merges with remote master
Local ref configured for 'git push':
    master pushes to master (up to date)
```

```
C:\WEducation\WGit-Tutorials>git remote add test https://github.com/sukyoujin/190719.git
```

```
C:\WEducation\WGit-Tutorials>git remote -v //github 내 특정 저장소 추가 후 모두 보기 함
origin https://github.com/sukyoujin/Git-Tutorials.git (fetch)
origin https://github.com/sukyoujin/Git-Tutorials.git (push)
test https://github.com/sukyoujin/190719.git (fetch)
test https://github.com/sukyoujin/190719.git (push)
```

```
C:\WEducation\WGit-Tutorials>git remote rename test temp //이름 바꾸기
```

```
C:\Education\Git-Tutorials>git remote -v
origin  https://github.com/sukyoujin/Git-Tutorials.git (fetch)
origin  https://github.com/sukyoujin/Git-Tutorials.git (push)
temp    https://github.com/sukyoujin/190719.git (fetch)
temp    https://github.com/sukyoujin/190719.git (push)
```

```
C:\Education\Git-Tutorials>git log origin/master //log도 볼 수 있고
commit 6ce1f31ac1d200855009da8a1f982ab49ab2bf45 (HEAD -> master, origin/master)
Merge: ebff67c d7dbfc9
Author: sukyoujin <gemmy_@naver.com>
Date:   Sun Jul 21 12:00:50 2019 +0900
    Add a.txt [Add c + //<EC><A3><BC><EC><84><9D>}
commit ebff67cefc7b8f302136f7279f32dc56ec199d80
Author: sukyoujin <gemmy_@naver.com>
Date:   Sun Jul 21 11:53:50 2019 +0900
    Add a.txt [Add c + //<EC><A3><BC><EC><84><9D>}
commit d7dbfc97ce92c94f47b96efe3898a933a57fd2b3
Author: sukyoujin <gemmy_@naver.com>
Date:   Sun Jul 21 11:50:19 2019 +0900
    Add a.txt [Add c]
commit 4a22d88acd566ad781dcc2a6521d0f2ed1c6e5a7
Author: sukyoujin <gemmy_@naver.com>
Date:   Sun Jul 21 11:38:19 2019 +0900
    Add a.txt [Add b]
commit 3f380a4347140d360a4f750fe955541b2c71540
Author: sukyoujin <gemmy_@naver.com>
Date:   Sun Jul 21 11:34:58 2019 +0900
    Add a.txt [a.txt]
```

```
C:\Education\Git-Tutorials>git merge origin/master //merge도 가능하고
Already up to date.
```

```
C:\Education\Git-Tutorials>git remote rm temp //이름도 바꿀 수 있음
```

```
C:\Education\Git-Tutorials>git remote -v
origin  https://github.com/sukyoujin/Git-Tutorials.git (fetch)
origin  https://github.com/sukyoujin/Git-Tutorials.git (push)
```

```
git에서 log 보기 (다양한 commit 내역 확인)-----
C:\Education\Git-Tutorials>git log -p -3 //p 옵션 : 어떤 방식으로 commit 됐나 3개 확인
commit 6ce1f31ac1d200855009da8a1f982ab49ab2bf45 (HEAD -> master, origin/master)
```

```
Merge: ebff67c d7dbfc9
Author: sukyoujin <gemmy_@naver.com>
Date:   Sun Jul 21 12:00:50 2019 +0900
    Add a.txt [Add c + //<EC><A3><BC><EC><84><9D>}
commit ebff67cefc7b8f302136f7279f32dc56ec199d80
Author: sukyoujin <gemmy_@naver.com>
Date:   Sun Jul 21 11:53:50 2019 +0900
    Add a.txt [Add c + //<EC><A3><BC><EC><84><9D>}
diff --git a/a.txt b/a.txt
index 0a207c0..ce6714f 100644
--- a/a.txt
+++ b/a.txt
@@ -1,2 +1,3 @@
    a
-b
\ No newline at end of file
+b
+c    //<C3><E6><B5><B9>
\ No newline at end of file
```

```
commit d7dbfc97ce92c94f47b96efe3898a933a57fd2b3
Author: sukyoujin <gemmy_@naver.com>
Date:   Sun Jul 21 11:50:19 2019 +0900
    Add a.txt [Add c]
diff --git a/a.txt b/a.txt
index 0a207c0..1c943a9 100644
--- a/a.txt
+++ b/a.txt
@@ -1,2 +1,3 @@
    a
-b
```

```
C:\Education\Git-Tutorials>git log --pretty=oneline // 한 줄로 각각의 commit 내용 확인
6ce1f31ac1d200855009da8a1f982ab49ab2bf45 (HEAD -> master, origin/master) Add a.txt
[Add c + //<EC><A3><BC><EC><84><9D>}
ebff67cefc7b8f302136f7279f32dc56ec199d80 Add a.txt [Add c + //<EC><A3><BC>
<EC><84><9D>}
d7dbfc97ce92c94f47b96efe3898a933a57fd2b3 Add a.txt [Add c]
4a22d88acd566ad781dcc2a6521d0f2ed1c6e5a7 Add a.txt [Add b]
3f380a4347140d360a4f750fe955541b2c71540 Add a.txt [a.txt]

//포맷도 정해서 볼 수 있다
C:\Education\Git-Tutorials>git log --pretty=format:"%h -> %an, %ar : %s" --graph
```

```
* 6ce1f31 -> sukyoujin, 20 minutes ago : Add a.txt [Add c + //<EC><A3><BC>
<EC><84><9D>}]
|₩
| * d7dbfc9 -> sukyoujin, 31 minutes ago : Add a.txt [Add c]
* | ebff67c -> sukyoujin, 27 minutes ago : Add a.txt [Add c + //<EC><A3><BC>
<EC><84><9D>}]
|/
* 4a22d88 -> sukyoujin, 43 minutes ago : Add a.txt [Add b]
* 3f380a4 -> sukyoujin, 46 minutes ago : Add a.txt [a.txt]
```

Git Rebase 명령으로 특정 commit 수정/삭제-----

```
C:₩Git-Tutorials>cd C:₩Git-Tutorials₩Git Sample

C:₩Git-Tutorials₩Git Sample>git init
Initialized empty Git repository in C:/Git-Tutorials/Git Sample/.git/
```

```
C:₩Git-Tutorials₩Git Sample>git add .
```

```
C:₩Git-Tutorials₩Git Sample>git commit -m "Add 1.txt 2.txt"
[master (root-commit) 3c8ec52] Add 1.txt 2.txt
 2 files changed, 2 insertions(+)
 create mode 100644 1.txt
 create mode 100644 2.txt
```

```
C:₩Git-Tutorials₩Git Sample>git add .
```

```
C:₩Git-Tutorials₩Git Sample>git commit -m "Delete 2.txt"
[master ea667db] Delete 2.txt
 1 file changed, 1 deletion(-)
 delete mode 100644 2.txt
```

```
C:₩Git-Tutorials₩Git Sample>git add .
```

```
C:₩Git-Tutorials₩Git Sample>git commit -m "Add 3.txt"
[master 327b636] Add 3.txt
 1 file changed, 1 insertion(+)
 create mode 100644 3.txt
```

```
C:₩Git-Tutorials₩Git Sample>git log
commit 327b63610cea45ec2a61b9a270b8840c08e94afb (HEAD -> master)
Author: sukyoujin <gemmy_@naver.com>
Date: Sun Jul 21 16:20:09 2019 +0900
```

```
Add 3.txt
commit ea667db176f1326b2926d983c86e11a7107d7b4d
Author: sukyoujin <gemmy_@naver.com>
Date: Sun Jul 21 16:19:30 2019 +0900

Delete 2.txt
commit 3c8ec5278f3605c16815aff9c28ff14713bc2eba
Author: sukyoujin <gemmy_@naver.com>
Date: Sun Jul 21 16:18:39 2019 +0900

Add 1.txt 2.txt
```

```
C:₩Git-Tutorials₩Git Sample>git rebase -i HEAD~2 //하단에 명령어 관련 안내가 나옴
[detached HEAD 05dde0d] Drop 2.txt //reword 입력 -> 내용 변경 -> :wq
Date: Sun Jul 21 16:19:30 2019 +0900
 1 file changed, 1 deletion(-)
 delete mode 100644 2.txt
Successfully rebased and updated refs/heads/master.
```

```
C:₩Git-Tutorials₩Git Sample>git log
commit f9eccc4a255956068e9db01383af4794b6de7129 (HEAD -> master)
Author: sukyoujin <gemmy_@naver.com>
Date: Sun Jul 21 16:20:09 2019 +0900

Add 3.txt
commit 05dde0ddbfc1a61110500b314afc13a56d6ad621
Author: sukyoujin <gemmy_@naver.com>
Date: Sun Jul 21 16:19:30 2019 +0900

Drop 2.txt //delete->drop 수정 완료
commit 3c8ec5278f3605c16815aff9c28ff14713bc2eba
Author: sukyoujin <gemmy_@naver.com>
Date: Sun Jul 21 16:18:39 2019 +0900

Add 1.txt 2.txt
```

```
C:₩Git-Tutorials₩Git Sample>git rebase -i 3c8ec5278f3605c16815aff9c28ff14713bc2e
ba //특정 commit을 지정할 수도
Successfully rebased and updated refs/heads/master.
```

프로젝트 소개글 작성하기(README.md)-----

```
C:₩Education₩Git-Tutorials>git pull 할 수도 있지만, github repository 내 ReadMe 파일 작성하
라는 곳에서 작성 후 수정이 편함
# 제목 /## smaller font size
** 강조는 굵은 글씨 별 2개 **
~~ 취소선 앞뒤로 물결 2개 ~~ ...
```