

VAPT Internship — Nepal | Week 4

docs.google.com/forms/d/e/1FAIpQLSfWplrZdIM_ykY_dGvks4ZGk6T2aKY7zM2RXN6F_mWKbghtg/formResponse?pli=1

sulavadh124@gmail.com [Switch accounts](#)

Not shared

Draft saved

* Indicates required question

Section A

1. Which Nmap flag is used for SYN scan? *

☐ A. -sT

☐ B. -sU

☒ C. -sS

☐ D. -sV

2. What does the -sn flag do in Nmap? *

☐ A. Scan ports

☐ B. Detect OS

☒ C. Host discovery only

☐ D. Run scripts

VAPT Internship — Nepal | Week 1

docs.google.com/forms/d/e/1FAIpQLSiFWplrZdIM_ykY_dGvks4ZGk6T2aKY7zM2RXN6F_mWKbghtg/formResponse?pli=1

☐ D. Run scripts

3. Which scan type completes the full TCP handshake? *

☐ A. SYN scan

☐ B. UDP scan

☒ C. TCP Connect scan

☐ D. Xmas scan

4. Which port is commonly used by SMB? *

☐ A. 21

☐ B. 22

☐ C. 80

☒ D. 445

5. What does -p- mean in Nmap? *

☐ A. Scan top 1000 ports

☐ B. Scan specific port

☒ C. Scan all ports

☐ D. Skip ports

VAPT Internship — Nepal | Week 1

docs.google.com/forms/d/e/1FAIpQLSfWplrZdIM_ykY_dGvks4ZGk6T2aKY7zM2RXN6F_mWKbghtg/formResponse?pli=1

☐ D. Skip ports

6. Which tool is used for SMB enumeration? *

☐ A. Nikto

☐ B. Gobuster

☒ C. enum4linux

☐ D. Wireshark

7. What is the purpose of Gobuster? *

☐ A. Scan vulnerabilities

☒ B. Brute-force directories

☐ C. Capture packets

☐ D. Encrypt data

8. Which command checks FTP anonymous login? *

☐ A. nmap -sV

☒ B. nmap --script=ftp-anon

☐ C. ftp connect

☐ D. gobuster ftp

VAPT Internship — Nepal | Week 1

docs.google.com/forms/d/e/1FAIpQLSfWplrZdIM_ykY_dGvks4ZGk6T2aKY7zM2RXN6F_mWKbghtg/formResponse?pli=1

☒ B. nmap -script=ftp-anon

☐ C. ftp connect

☐ D. gobuster ftp

9. What does "filtered" port state mean? *

☐ A. Port is open

☐ B. Port is closed

☒ C. Firewall blocking response

☐ D. Service crashed

10. Which command is used for banner grabbing? *

☐ A. ssh

☐ B. ftp

☒ C. nc

☐ D. ping

Back Next Clear form

Never submit passwords through Google Forms.

This content is neither created nor endorsed by Google. - [Contact form owner](#) - [Terms of Service](#) - [Privacy Policy](#)

Does this form look suspicious? [Report](#)

Google Forms

VAPT Internship — Nepal | Weel

docs.google.com/forms/d/e/1FAIpQLSiFWplrZdIM_ykY_dGvks4ZGk6T2aKY7zM2RXN6F_mWKbghtg/formResponse?pli=1

sulavadh124@gmail.com [Switch accounts](#)

Not shared

Draft saved

* Indicates required question

Section B

1. Explain different types of Nmap scans with examples. (5 marks) *

Nmap is a network scanning tool used to discover hosts, open ports, services, and operating systems.

Types of Nmap scans:

a) SYN Scan (-sS)
It is called a half-open scan because it does not complete the full TCP handshake. It is fast and stealthy.
Example: `nmap -sS 192.168.1.1`

b) TCP Connect Scan (-sT)
It completes the full TCP handshake. It is used when SYN scan is not allowed.
Example: `nmap -sT 192.168.1.1`

c) UDP Scan (-sU)
Used to scan UDP ports like DNS and SNMP.
Example: `nmap -sU 192.168.1.1`

d) Version Detection (-sV)
Detects service versions running on open ports.
Example: `nmap -sV 192.168.1.1`

e) OS Detection (-O)
Identifies the target operating system.
Example: `nmap -O 192.168.1.1`

VAPT Internship — Nepal | Week 1

docs.google.com/forms/d/e/1FAIpQLSiFWplrZdIM_ykY_dGvks4ZGk6T2aKY7zM2RXN6F_mWKbghtg/formResponse?pli=1

2. What is SMB enumeration? Explain tools and commands used. (5 marks) *

SMB (Server Message Block) is a protocol used for file sharing, printer sharing, and network communication in Windows systems. It commonly runs on port 445.

SMB enumeration means collecting information such as shared folders, users, groups, and system details from a target machine.

Tools used:

a) enum4linux
Used to enumerate SMB shares, users, groups, and policies.
Example: enum4linux 192.168.1.10

b) smbclient
Used to connect and list shared folders.
Example: smbclient -L //192.168.1.10 -N

c) Nmap SMB scripts
Example: nmap -script smb-os-discovery 192.168.1.10

3. Explain Web Enumeration using Nikto and Gobuster. (5 marks) *

Web enumeration is the process of gathering information about websites, directories, files, and vulnerabilities.

a) Nikto
Nikto is a web vulnerability scanner used to detect outdated software, dangerous files, and security issues.
Example: nikto -h http://192.168.1.20
It checks for:
- Server misconfigurations
- Default files
- Vulnerable versions
- Security headers

b) Gobuster

VAPT Internship — Nepal | Week 1

docs.google.com/forms/d/e/1FAIpQLSiFWplrZdIM_ykY_dGvks4ZGk6T2aKY7zM2RXN6F_mWKbghtg/formResponse?pli=1

b) Gobuster

Gobuster is used for brute-forcing hidden directories and files on web servers.

Example:

```
gobuster dir -u http://192.168.1.20 -w wordlist.txt
```

It helps find:

- Hidden admin panels
- Backup files
- Login pages
- Secret directories

Both tools are important for web application testing.

4. What is Banner Grabbing? Explain with examples. (5 marks) *

Banner grabbing is the process of collecting service information from open ports, such as software name, version, and server details.

It helps attackers and security testers identify services running on the target.

Tools used:

a) Netcat (nc)

Example: nc 192.168.1.10 80

Then type:

```
HEAD / HTTP/1.0
```

This may show server details like Apache or Nginx version.

b) Telnet

Example: telnet 192.168.1.10 21

It may display FTP server banner like: 220 FTP Server Ready

c) Nmap Version Detection

Example: nmap -sV 192.168.1.10

Banner grabbing helps in identifying outdated or vulnerable services.

Back

Submit

Clear form

Never submit passwords through Google Forms.