

# Лабораторная работа №9

Управление SELinux

---

Сулейм Гамбердов

16 октября 2025

Российский университет дружбы народов, Москва, Россия

## Цель работы

---

Получить навыки работы с контекстом безопасности и политиками **SELinux**, научиться изменять режимы работы, восстанавливать контексты и применять политики к нестандартным каталогам.

## Ход выполнения работы

---

# Проверка состояния SELinux

```
-----
root@sigamberdov:/home/sigamberdov# sestatus -v
SELinux status:                enabled
SELinuxfs mount:               /sys/fs/selinux
SELinux root directory:        /etc/selinux
Loaded policy name:             targeted
Current mode:                   enforcing
Mode from config file:         enforcing
Policy MLS status:             enabled
Policy deny_unknown status:    allowed
Memory protection checking:    actual (secure)
Max kernel policy version:     33

Process contexts:
Current context:                unconfined_u:unconfined_r:unconfined_t:s0-s0:c0.c1023
Init context:                   system_u:system_r:init_t:s0
/usr/sbin/sshd                  system_u:system_r:sshd_t:s0-s0:c0.c1023

File contexts:
Controlling terminal:          unconfined_u:object_r:user_devpts_t:s0
/etc/passwd                    system_u:object_r:passwd_file_t:s0
/etc/shadow                    system_u:object_r:shadow_t:s0
/bin/bash                      system_u:object_r:shell_exec_t:s0
/bin/login                     system_u:object_r:login_exec_t:s0
/bin/sh                        system_u:object_r:bin_t:s0 -> system_u:object_r:shell_exec_t:s0
/sbin/agetty                   system_u:object_r:getty_exec_t:s0
/sbin/init                     system_u:object_r:bin_t:s0 -> system_u:object_r:init_exec_t:s0
/usr/sbin/sshd                 system_u:object_r:sshd_exec_t:s0
root@sigamberdov:/home/sigamberdov# getenforce
Enforcing
root@sigamberdov:/home/sigamberdov# setenforce 0
root@sigamberdov:/home/sigamberdov# getenforce
Permissive
root@sigamberdov:/home/sigamberdov#
```

# Изменение режима работы SELinux

```
GNU nano 8.1 /etc/sysconfig/selinux Modified

# This file controls the state of SELinux on the system.
# SELINUX= can take one of these three values:
#   enforcing - SELinux security policy is enforced.
#   permissive - SELinux prints warnings instead of enforcing.
#   disabled - No SELinux policy is loaded.
# See also:
# https://docs.fedoraproject.org/en-US/quick-docs/getting-started-with-selinux/#getting-started-with-selinux
#
# NOTE: In earlier Fedora kernel builds, SELINUX=disabled would also
# fully disable SELinux during boot. If you need a system with SELinux
# fully disabled instead of SELinux running with no policy loaded, you
# need to pass selinux=0 to the kernel command line. You can use grubby
# to persistently set the bootloader to boot with selinux=0:
#
#   grubby --update-kernel ALL --args selinux=0
#
# To revert back to SELinux enabled:
#
#   grubby --update-kernel ALL --remove-args selinux
#
SELINUX=disabled
# SELINUXTYPE= can take one of these three values:
#   targeted - Targeted processes are protected,
#   minimum - Modification of targeted policy. Only selected processes are protected.
#   mls - Multi Level Security protection.
SELINUXTYPE=targeted
```

```
sigamberdov@sigamberdov:~$ su
Password:
root@sigamberdov:/home/sigamberdov# getenforce
Disabled
root@sigamberdov:/home/sigamberdov# setenforce 1
setenforce: SELinux is disabled
root@sigamberdov:/home/sigamberdov# █
```

Рис. 3: Отключение SELinux в конфигурационном файле

## Отключение и повторное включение SELinux

```
sigamberdov@sigamberdov:/home/sigamberdov – nano /etc/sysconfig/selinux
GNU nano 8.1 /etc/sysconfig/selinux Mod

# This file controls the state of SELinux on the system.
# SELINUX= can take one of these three values:
#   enforcing - SELinux security policy is enforced.
#   permissive - SELinux prints warnings instead of enforcing.
#   disabled - No SELinux policy is loaded.
# See also:
# https://docs.fedoraproject.org/en-US/quick-docs/getting-started-with-selinux/#getting-started-with-
#
# NOTE: In earlier Fedora kernel builds, SELINUX=disabled would also
# fully disable SELinux during boot. If you need a system with SELinux
# fully disabled instead of SELinux running with no policy loaded, you
# need to pass selinux=0 to the kernel command line. You can use grubby
# to persistently set the bootloader to boot with selinux=0:
#
#   grubby --update-kernel ALL --args selinux=0
#
# To revert back to SELinux enabled:
#
#   grubby --update-kernel ALL --remove-args selinux
#
SELINUX=enforcing
# SELINUXTYPE= can take one of these three values:
#   targeted - Targeted processes are protected,
#   minimum - Modification of targeted policy. Only selected processes are protected.
#   mls - Multi Level Security protection.
SELINUXTYPE=targeted
```



## Отключение и повторное включение SELinux

```
sigamberdov@sigamberdov:~$ su
Password:
root@sigamberdov:/home/sigamberdov# sestatus -v
SELinux status:                enabled
SELinuxfs mount:               /sys/fs/selinux
SELinux root directory:        /etc/selinux
Loaded policy name:             targeted
Current mode:                   enforcing
Mode from config file:         enforcing
Policy MLS status:             enabled
Policy deny_unknown status:     allowed
Memory protection checking:     actual (secure)
Max kernel policy version:     33

Process contexts:
Current context:                unconfined_u:unconfined_r:unconfined_t:s0-s0:c0.c1023
Init context:                   system_u:system_r:init_t:s0
/usr/sbin/sshd                  system_u:system_r:sshd_t:s0-s0:c0.c1023

File contexts:
Controlling terminal:           unconfined_u:object_r:user_devpts_t:s0
/etc/passwd                     system_u:object_r:passwd_file_t:s0
/etc/shadow                    system_u:object_r:shadow_t:s0
/bin/bash                      system_u:object_r:shell_exec_t:s0
/bin/login                    system_u:object_r:login_exec_t:s0
/bin/sh                        system_u:object_r:bin_t:s0 -> system_u:object_r:shell_exec_t:s0
/sbin/agetty                   system_u:object_r:getty_exec_t:s0
/sbin/init                     system_u:object_r:bin_t:s0 -> system_u:object_r:init_exec_t:s0
/usr/sbin/sshd                 system_u:object_r:sshd_exec_t:s0
root@sigamberdov:/home/sigamberdov#
```

```
[ 1.333674] vmwgfx 0000:00:02.0: [drm] *ERROR* vmwgfx seems to be running on
an unsupported hypervisor.
[ 1.333676] vmwgfx 0000:00:02.0: [drm] *ERROR* This configuration is likely b
roken.
[ 1.333677] vmwgfx 0000:00:02.0: [drm] *ERROR* Please switch to a supported g
raphics device to avoid problems.
[ 7.510340] selinux-autorelabel[828]: *** Warning -- SELinux targeted policy relabel is required.
[ 7.510394] selinux-autorelabel[828]: *** Relabeling could take a very long time, depending on file
[ 7.510414] selinux-autorelabel[828]: *** system size and speed of hard drives.
[ 7.512731] selinux-autorelabel[828]: Running: /sbin/fixfiles -T 0 restore
```

Рис. 6: Использование restorecon и autorelabel для восстановления контекста

```
Transaction test succeeded.  
Running transaction  
  Preparing      :  
  Installing     : lynx-2.9.0-6.el10.x86_64  
  Running scriptlet: lynx-2.9.0-6.el10.x86_64  
  
Installed:  
  lynx-2.9.0-6.el10.x86_64  
  
Complete!  
root@sigamberdov:/home/sigamberdov# mkdir /web  
root@sigamberdov:/home/sigamberdov# cd /web  
root@sigamberdov:/web# touch index.html  
root@sigamberdov:/web# echo "Welcome to my web server" > index.html  
root@sigamberdov:/web#
```

Рис. 7: Установка lynx и подготовка каталога /web

## Настройка контекста для каталога веб-сервера

```
GNU nano 8.1 /etc/httpd/conf/httpd.conf
# particular features to be enabled - so if something's not working as
# you might expect, make sure that you have specifically enabled it
# below.
#
#
# DocumentRoot: The directory out of which you will serve your
# documents. By default, all requests are taken from this directory, but
# symbolic links and aliases may be used to point to other locations.
#
#DocumentRoot "/var/www/html"

DocumentRoot "/web"

<Directory "/web">
    AllowOverride None
    Require all granted
</Directory>

#
```


Рис. 8: Изменение конфигурации DocumentRoot

## Настройка контекста для каталога веб-сервера

```
root@sigamberdov:/web#  
root@sigamberdov:/web# semanage fcontext -a -t httpd_sys_content_t "/web(/.*)?"  
root@sigamberdov:/web# restorecon -R -v /web  
Relabeled /web from unconfined_u:object_r:default_t:s0 to unconfined_u:object_r:httpd_sys_content_t:s0  
Relabeled /web/index.html from unconfined_u:object_r:default_t:s0 to unconfined_u:object_r:httpd_sys_content_t:s0  
root@sigamberdov:/web#
```

Рис. 9: Назначение контекста безопасности для каталога /web

## Настройка контекста для каталога веб-сервера



## Настройка параметров SELinux для FTP

```
-----sigam-----/home/sigam-----
root@sigamverdov:/home/sigamverdov# getsebool -a | grep ftp
ftpd_anon_write --> off
ftpd_connect_all_unreserved --> off
ftpd_connect_db --> off
ftpd_full_access --> off
ftpd_use_cifs --> off
ftpd_use_fusefs --> off
ftpd_use_nfs --> off
ftpd_use_passive_mode --> off
httpd_can_connect_ftp --> off
httpd_enable_ftp_server --> off
tftp_anon_write --> off
tftp_home_dir --> off
root@sigamverdov:/home/sigamverdov# semanage boolean -l | grep ftpd_anon
ftpd_anon_write (off , off) Allow ftpd to anon write
root@sigamverdov:/home/sigamverdov# setsebool ftpd_anon_write on
root@sigamverdov:/home/sigamverdov# getsebool ftpd_anon_write
ftpd_anon_write --> on
root@sigamverdov:/home/sigamverdov# semanage boolean -l | grep ftpd_anon
ftpd_anon_write (on , off) Allow ftpd to anon write
root@sigamverdov:/home/sigamverdov# setsebool -P ftpd_anon_write on
root@sigamverdov:/home/sigamverdov# semanage boolean -l | grep ftpd_anon
ftpd_anon_write (on , on) Allow ftpd to anon write
root@sigamverdov:/home/sigamverdov# █
```

## Итоги работы

---



В ходе лабораторной работы были освоены приёмы администрирования SELinux:

- изменение режимов работы системы безопасности;
- назначение и восстановление контекстов безопасности;
- настройка SELinux для нестандартных каталогов веб-сервера и FTP-сервиса.

Работа позволила понять принципы функционирования механизма SELinux и его роль в обеспечении безопасности Linux-систем.