

Cryptography and Network Security

Dr. Rafiqul Islam

Classical Encryption Techniques

- Symmetric Cipher Techniques
- Asymmetric Cipher Techniques

Symmetric Cipher

- **Plaintext:** Input Text
- **Encryption algorithm:** The encryption algorithm performs various substitutions and transformations on the plaintext.
- **Secret key:** The secret key is also input to the encryption algorithm. The key is a value independent of the plaintext and of the algorithm.
- **Cipher text:** This is the scrambled message produced as output. It depends on the plaintext and the secret key. The ciphertext is an apparently random stream of data and, as it stands, is unintelligible.
- **Decryption algorithm:** This is essentially the encryption algorithm run in reverse. It takes the ciphertext and the secret key and produces the original plaintext.

Symmetric Cipher




Figure 2.1 Simplified Model of Symmetric Encryption

Different Types of Ciphers

- Traditional Ciphers
- Modern Ciphers
- Asymmetric-Key Ciphers


Traditional ciphers

- Traditional ciphers are called symmetric-key ciphers (or secret-key ciphers)
- because the same key is used for encryption and decryption and
- the key can be used for bidirectional communication.

Topics Discussed in the Section

- ✓ Key
- ✓ Substitution Ciphers
- ✓ Transposition Ciphers
- ✓ Stream and Block Ciphers

General idea of traditional cipher



substitution cipher

- A substitution cipher replaces one symbol with another

Representation of characters in modulo 26

Plaintext →	a	b	c	d	e	f	g	h	i	j	k	l	m	n	o	p	q	r	s	t	u	v	w	x	y	z
Ciphertext →	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z
Value →	00	01	02	03	04	05	06	07	08	09	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25

plain: a b c d e f g h i j k l m n o p q r s t u v w x y z
 cipher: D E F G H I J K L M N O P Q R S T U V W X Y Z A B C

Let us assign a numerical equivalent to each letter:

a	b	c	d	e	f	g	h	i	j	k	l	m
0	1	2	3	4	5	6	7	8	9	10	11	12

n	o	p	q	r	s	t	u	v	w	x	y	z
13	14	15	16	17	18	19	20	21	22	23	24	25

Contd.

- In additive cipher, the plaintext, ciphertext, and key are integers in modulo 26.
- $C = (P+K) \bmod 26$
- $P = (C-K) \bmod 26$

Example 01

Use the additive cipher with key = 15 to encrypt the message “hello”.

Solution

We apply the encryption algorithm to the plaintext, character by character. The result is “WTAAD”. Note that the cipher is mono alphabetic because two instances of the same plaintext character (ls) are encrypted as the same character (A).

Plaintext: h \rightarrow 07	Encryption: $(07 + 15) \bmod 26$	Ciphertext: 22 \rightarrow W
Plaintext: e \rightarrow 04	Encryption: $(04 + 15) \bmod 26$	Ciphertext: 19 \rightarrow T
Plaintext: l \rightarrow 11	Encryption: $(11 + 15) \bmod 26$	Ciphertext: 00 \rightarrow A
Plaintext: l \rightarrow 11	Encryption: $(11 + 15) \bmod 26$	Ciphertext: 00 \rightarrow A
Plaintext: o \rightarrow 14	Encryption: $(14 + 15) \bmod 26$	Ciphertext: 03 \rightarrow D

Example 01

Use the additive cipher with key = 15 to decrypt the message “WTAAD”.

Solution

We apply the decryption algorithm to the plaintext character by character. The result is “hello”. Note that the operation is in modulo 26, which means that we need to add 26 to a negative result (for example -15 becomes 11).

Ciphertext: W \rightarrow 22	Decryption: $(22 - 15) \bmod 26$	Plaintext: 07 \rightarrow h
Ciphertext: T \rightarrow 19	Decryption: $(19 - 15) \bmod 26$	Plaintext: 04 \rightarrow e
Ciphertext: A \rightarrow 00	Decryption: $(00 - 15) \bmod 26$	Plaintext: 11 \rightarrow l
Ciphertext: A \rightarrow 00	Decryption: $(00 - 15) \bmod 26$	Plaintext: 11 \rightarrow l
Ciphertext: D \rightarrow 03	Decryption: $(03 - 15) \bmod 26$	Plaintext: 14 \rightarrow o

An example key for mono-alphabetic substitution cipher

Plaintext	→	a	b	c	d	e	f	g	h	i	j	k	l	m	n	o	p	q	r	s	t	u	v	w	x	y	z
Ciphertext	→	N	O	A	T	R	B	E	C	F	U	X	D	Q	G	Y	L	K	H	V	I	J	M	P	Z	S	W

Example

- We can use the key to encrypt the message

this message is easy to encrypt but hard to find the key

The ciphertext is

ICFVQRVVNEFVRNVSIYRGAHSLIOJICNHTIYBFGTICRXRS


Transposition Cipher

- A transposition cipher reorders symbols


Transposition cipher




Alice



Bob



Transmission




Modern ciphers

- The traditional symmetric-key ciphers that we have studied so far are character-oriented ciphers.
- With the advent of the computer, we need bit-oriented ciphers.
- This is because the information to be encrypted is not just text; it can also consist of numbers, graphics, audio, and video data.
- It is convenient to convert these types of data into a stream of bits, to encrypt the stream, and then to send the encrypted stream.
- A modern block cipher can be either a block cipher or a stream cipher.


Topics Discussed in the Section

- Modern Block Ciphers
- Data Encryption Standard (DES)
- Modern Stream Ciphers


A modern block cipher




Components of a modern block cipher




Transposition




Substitution




Exclusive-Or




Shift



Swap




Split




Combine


General structure of DES



DES function



Key generation



Example 04

- We choose a random plaintext block, a random key, and a computer program to determine what the cipher text block would be (all in hexadecimal):

Plaintext:

123456ABCD132536

Key:

AABB09182736CCDD

CipherText:

C0B7A8D05F3A829C

Example 05

- To check the effectiveness of DES, when a single bit is changed in the input, let us use two different plaintexts with only one single bit difference.
- The two cipher texts are completely different without even changing the key:

Plaintext:	Key:	Ciphertext:
0000000000000000	22234512987ABB23	4789FD476E82A5F1
Plaintext:	Key:	Ciphertext:
0000000000000001	22234512987ABB23	0A4ED5C15A63FEA3

Although the two plaintext blocks differ only in the rightmost bit, the ciphertext blocks differ in 29 bits.

End Chapter 2

- Questions?