

sheet4_zli

November 14, 2017

1 Exercise H4.2: Comparison of gradient descent methods

```
In [1]: import numpy as np
import matplotlib
import matplotlib.pyplot as plt
%matplotlib inline

data = np.array([[ -1, -0.1], [0.3, 0.5], [2, 0.5]])
X = np.array(zip(np.ones(data.shape[0]), data[:, 0])).T
Y = data[:, 1].reshape(1, 3)
W1 = np.array([-0.45, 0.2]).reshape(2,1)



def func_g(w, x, y):
    # x: D*N
    # y: 1*N
    # w: D*1
    H = X.dot(X.T)
    b = -X.dot(Y.T)
    return H.dot(w) + b
```

1.1 (a) Gradient Descent

```
In [2]: learning_rate = 0.1
w_gradient_descent_array = []
# w_gradient_descent_array.append(W1)
w_tmp = W1
for i in range(0, 100):
    w_gradient_descent_array.append(w_tmp)
    w_tmp = w_tmp - learning_rate * func_g(w_tmp, X, Y)
W = np.array(w_gradient_descent_array).reshape(100, 2)

plt.plot(W[:, 0], W[:, 1])
plt.xlabel('w0')
plt.ylabel("w1")
plt.show()
```

```
plt.plot(range(0, W.shape[0]), W[:, 0], color='r', label='w0')
plt.plot(range(0, W.shape[0]), W[:, 1], color='g', label='w1')
plt.legend()
plt.show()
```



1.2 (b) Line Search

```
In [3]: H = X.dot(X.T)
```



```
def calc_optimal_step_size(w, gt, dt):
    return dt.T.dot(gt)/(dt.T.dot(H)).dot(dt)

w_gradient_descent_array = []
w_tmp = W1
g1 = func_g(W1, X, Y)
step_size = calc_optimal_step_size(w_tmp, g1, g1)
for i in range(0, 100):
    w_gradient_descent_array.append(w_tmp)
    gt = func_g(w_tmp, X, Y)
    step_size = calc_optimal_step_size(w_tmp, gt, gt)
    w_tmp = w_tmp - step_size * gt
W = np.array(w_gradient_descent_array).reshape(100, 2)

plt.plot(W[:, 0], W[:, 1])
plt.xlabel('w0')
plt.ylabel("w1")
plt.show()

plt.plot(range(0, W.shape[0]), W[:, 0], color='r', label='w0')
plt.plot(range(0, W.shape[0]), W[:, 1], color='g', label='w1')
plt.legend()
plt.show()
```

```
/usr/local/lib/python2.7/site-packages/ipykernel_launcher.py:4: RuntimeWarning: invalid value en
after removing the cwd from sys.path.
```





1.3 (c) Conjugate Gradient

```
In [14]: def calc_beta(g_new, g_old):
    return g_new.T.dot(g_new)/g_old.T.dot(g_old)
    w_gradient_descent_array = []
    w_tmp = W1
    g1 = func_g(W1, X, Y)
    d1 = -g1
    gt_new = g1
    dt = d1
    step_size = calc_optimal_step_size(w_tmp, g1, d1)
    for i in range(0, 100):
        w_gradient_descent_array.append(w_tmp)
        step_size = calc_optimal_step_size(w_tmp, gt_new, dt)
        w_tmp = w_tmp - step_size * dt
        gt_old = gt_new
        gt_new = func_g(w_tmp, X, Y)
        beta = calc_beta(gt_new, gt_old)
        dt = gt_new - beta * dt
    W = np.array(w_gradient_descent_array).reshape(100, 2)

    plt.plot(W[:, 0], W[:, 1])
    plt.xlabel('w0')
    plt.ylabel("w1")
    plt.show()

    plt.plot(range(0, W.shape[0]), W[:, 0], color='r', label='w0')
    plt.plot(range(0, W.shape[0]), W[:, 1], color='g', label='w1')
    plt.legend()
    plt.show()
```

/usr/local/lib/python2.7/site-packages/ipykernel_launcher.py:4: RuntimeWarning: invalid value encountered in divide
after removing the cwd from sys.path.



In []: