Programming Fundamentals Using C++

Huma Israr

Department Of Information Engineering Technology

National Skills University, Islamabad.

huma.israr@nsu.edu.pk

Fall 2024, BS-CS

Week 07

Lecture – 02

Escape Sequence

Semester Calendar

Class Schedule

Lab Hours (Practice)

Tuesday (09:00 to 10:30)
Wednesday (09:30 to 12:30)
Wednesday (03:00 to 04:30)

Escape Sequences.

- Character combinations consisting of a backslash (\) followed by a letter or by a combination of digits are called "escape sequences."
- Escape sequences are the special characters used in control string to modify the format of the output.
- These characters are not displayed in output.
- These characters are used with combination of backslash \.
- This backslash \ is called escape character.
- The escape sequence can be inserted in any position of the string such as At the beginning of the string, In the middle of the string , At the end of the string

Escape Sequence:

- For example, the escape sequence '\n' is used to insert a new line. The cursor moves from the current position on the output device to the beginning of the next line. If escape sequence '\n' is inserted at the beginning of the string then the string will be printed after printing a blank line e.g.

```
cout<<"\nWelcome";
cout<<"Programming\nFundamentals";
```

List Of Escape sequence

Escape Sequences	Purpose
1. \a	Alarm (Beep, bell)
2. \t	tab
3. \n	new line
4. \f	Form Feed
5. \r	Carriage Return
6. \’	Single quote mark
7. \”	Double quote mark
8. \?	Question mark
9. \b	Backspace

Switch Statement without Break

Escape sequence	Description	
\’	single quote	cout<<” \’ COMPUTER SCIENCE \’ ”;
\”	double quote	cout<<” \” COMPUTER SCIENCE \” ”;
\n	line feed - new line	cout<<” COMPUTER\nSCIENCE ”;
\t	horizontal tab	cout<<” COMPUTER\tSCIENCE ”;
\v	vertical tab	cout<<” COMPUTER\vSCIENCE ”;
\b	backspace	cout<<” COMPUTER\bSCIENCE ”;
\a	audible bell	cout<<” COMPUTER\aSCIENCE ”;
\r	carriage return	cout<<” COMPUTER\rSCIENCE ”;
\\	backslash	cout<<” \\\ COMPUTER SCIENCE \\\ ”;
\?	question mark	cout<<” COMPUTER SCIENCE \? ”;

Reserved keywords in C++.

- A reserved word is a word that cannot be used as an identifier, such as the name of a variable, function, or label – it is "reserved from use".
- reserved words in C++ library are used to perform an internal operation.
- They are used by the language, these keywords are not available for re-definition .
- There are a total of 95 reserved words in C++

Exclusive reserved Words.

- Following is the list of reserved word which cannot be used as identifiers (even though they follow naming rules in C++).

double float int short unsigned break continue
else for long signed switch case default goto
sizeof char do if return while namespace bool
false using true not cin endl main std cout
include iostream string cout

Escape Sequences.

- int a; // valid
- int for ; // wrong
- float num ; // valid
- float cout; //wrong
- double number; //valid
- double main; //wrong

Any Question