



PREMIUM

Full-Length Mock Test

Mock 02

Instrumentation Engineering

GATE IN

Total Questions	60
Maximum Marks	108
Duration	180 minutes (3 Hours)
Exam Pattern	MCQ + MSQ + NAT
Negative Marking	MCQ/MSQ: -0.33 per wrong answer
Designed For	EduNeuro Premium

Easy 20%

Moderate 33%

Hard 47%

Based on Previous Year Question Pattern Analysis | Generated by EduNeuro Premium

General Instructions

This question paper contains THREE sections: Section A, Section B, and Section C.

Section A: Multiple Choice Questions (MCQ) — carries one or two marks each. Only ONE option is correct.

Section B: Multiple Select Questions (MSQ) — carries two marks each. ONE OR MORE than one option(s) is/are correct.

Section C: Numerical Answer Type (NAT) — carries one or two marks. Enter the numerical value in the space provided.

Negative Marking: -0.33 marks will be deducted for each wrong MCQ and each wrong MSQ answer.

No negative marking for NAT questions.

There are 60 questions for a total of 100 marks.

Duration: 3 hours (180 minutes).

Use the space provided for rough work. Scribbling on the question paper is permitted.

Do not ask for clarification from the invigilator. Interpret questions as given.

Paper Structure

Section	Type	Questions	Marks/Q	Total Marks	Negative
A	MCQ	35	1 / 2	35	-0.33
B	MSQ	5	2	10	-0.33
C	NAT	20	1 / 2	35	None
Total		60		100	

Marking Scheme

Correct MCQ: +1 mark (or +2 marks as specified per question)

Wrong MCQ: -0.33 marks

Correct MSQ: +2 marks

Wrong MSQ (partial or no match): -0.33 marks

Correct NAT: +1 mark (or +2 marks as specified per question)

No answer / Unattempted: 0 marks

NAT wrong answer: 0 marks (no negative marking)

Section A — Multiple Choice Questions (MCQ)

Q.1 [1 Mark] [EASY] [Sensors & Transducers — Inductive]

LVDT measures:

- A) Displacement
 - B) Velocity
 - C) Acceleration
 - D) Force
-

Q.2 [1 Mark] [EASY] [Measurement Systems — Bridge Circuits]

RTD uses:

- A) Semiconductor
 - B) Pure metal
 - C) Thermocouple
 - D) Thermistor
-

Q.3 [1 Mark] [EASY] [Control Systems — PID Control]

Strain gauge factor $GF =$:

- A) $\Delta L/L$
 - B) $\Delta R/R$
 - C) $\Delta L/L$
 - D) $\Delta R/R$
-

Q.4 [1 Mark] [EASY] [Digital Electronics — Sequential Circuits]

CRO displays:

- A) Current vs Time
 - B) Voltage vs Time
 - C) Power vs Time
 - D) Frequency vs Time
-

Q.5 [1 Mark] [EASY] [Analog Electronics — Op-Amps]

LVDT measures:

- A) Displacement
 - B) Velocity
 - C) Acceleration
 - D) Force
-

Q.6 [1 Mark] [EASY] [Sensors & Transducers — Digital Transducers]

RTD uses:

- A) Semiconductor
 - B) Pure metal
 - C) Thermocouple
 - D) Thermistor
-

Q.7 [1 Mark] [EASY] [Measurement Systems — Signal Conditioning]

Strain gauge factor $GF =$:

A) 9E"ö" ò "L/L

B) 9DÂôÂ ò "R/R

C) 9E"ö" r "L/L

D) 9E"Ó"L

Q.8 [1 Mark] [EASY] [Control Systems — Root Locus]

CRO displays:

- A) Current vs Time
 - B) Voltage vs Time
 - C) Power vs Time
 - D) Frequency vs Time
-

Q.9 [1 Mark] [EASY] [Digital Electronics — ADC/DAC]

LVDT measures:

- A) Displacement
 - B) Velocity
 - C) Acceleration
 - D) Force
-

Q.10 [1 Mark] [EASY] [Analog Electronics — Op-Amps]

RTD uses:

- A) Semiconductor
 - B) Pure metal
 - C) Thermocouple
 - D) Thermistor
-

Q.11 [1 Mark] [EASY] [Sensors & Transducers — Resistive/Capacitive]

Strain gauge factor $GF =$:

- A) $9E^{-6} \text{ m}^2/\text{N}$
 - B) $9D^{-1} \text{ m}^2/\text{N}$
 - C) $9E^{-6} \text{ m}^2/\text{N}$
 - D) $9E^{-6} \text{ m}^2/\text{N}$
-

Q.12 [1 Mark] [EASY] [Measurement Systems — Bridge Circuits]

CRO displays:

- A) Current vs Time
 - B) Voltage vs Time
 - C) Power vs Time
 - D) Frequency vs Time
-

Q.13 [2 Marks] [MODERATE] [Control Systems — Root Locus]

LVDT measures:

- A) Displacement
 - B) Velocity
 - C) Acceleration
 - D) Force
-

Q.14 [2 Marks] [MODERATE] [Digital Electronics — Logic Gates]

RTD uses:

- A) Semiconductor

B) Pure metal

C) Thermocouple

D) Thermistor

Q.15 [2 Marks] [MODERATE] [Analog Electronics — Oscillators]

Strain gauge factor GF =:

- A) $9E''\delta'' \rightarrow ''L/L$
- B) $9D\hat{A}\hat{A} \rightarrow ''R/R$
- C) $9E''\delta'' \rightarrow ''L/L$
- D) $9E''\delta''L$

Q.16 [2 Marks] [MODERATE] [Sensors & Transducers — Digital Transducers]

CRO displays:

- A) Current vs Time
- B) Voltage vs Time
- C) Power vs Time
- D) Frequency vs Time

Q.17 [2 Marks] [MODERATE] [Measurement Systems — Signal Conditioning]

LVDT measures:

- A) Displacement
- B) Velocity
- C) Acceleration
- D) Force

Q.18 [2 Marks] [MODERATE] [Control Systems — PID Control]

RTD uses:

- A) Semiconductor
- B) Pure metal
- C) Thermocouple
- D) Thermistor

Q.19 [2 Marks] [MODERATE] [Digital Electronics — Microprocessors]

Strain gauge factor GF =:

- A) $9E''\delta'' \rightarrow ''L/L$
- B) $9D\hat{A}\hat{A} \rightarrow ''R/R$
- C) $9E''\delta'' \rightarrow ''L/L$
- D) $9E''\delta''L$

Q.20 [2 Marks] [MODERATE] [Analog Electronics — Amplifiers]

CRO displays:

- A) Current vs Time
- B) Voltage vs Time
- C) Power vs Time
- D) Frequency vs Time

Q.21 [2 Marks] [MODERATE] [Sensors & Transducers — Optical Sensors]

LVDT measures:

- A) Displacement

B) Velocity

C) Acceleration

D) Force

Q.22 [2 Marks] [MODERATE] [Measurement Systems — Instrument Types]

RTD uses:

- A) Semiconductor
 - B) Pure metal
 - C) Thermocouple
 - D) Thermistor
-

Q.23 [2 Marks] [MODERATE] [Control Systems — Compensators]

Strain gauge factor GF =:

- A) $\Delta R/R \rightarrow \Delta L/L$
 - B) $\Delta R/R \rightarrow \Delta L/L$
 - C) $\Delta R/R \rightarrow \Delta L/L$
 - D) $\Delta R/R \rightarrow \Delta L/L$
-

Q.24 [2 Marks] [MODERATE] [Digital Electronics — Microprocessors]

CRO displays:

- A) Current vs Time
 - B) Voltage vs Time
 - C) Power vs Time
 - D) Frequency vs Time
-

Q.25 [2 Marks] [MODERATE] [Analog Electronics — Amplifiers]

LVDT measures:

- A) Displacement
 - B) Velocity
 - C) Acceleration
 - D) Force
-

Q.26 [2 Marks] [MODERATE] [Sensors & Transducers — Inductive]

RTD uses:

- A) Semiconductor
 - B) Pure metal
 - C) Thermocouple
 - D) Thermistor
-

Q.27 [2 Marks] [MODERATE] [Measurement Systems — CRO]

Strain gauge factor GF =:

- A) $\Delta R/R \rightarrow \Delta L/L$
 - B) $\Delta R/R \rightarrow \Delta L/L$
 - C) $\Delta R/R \rightarrow \Delta L/L$
 - D) $\Delta R/R \rightarrow \Delta L/L$
-

Q.28 [2 Marks] [MODERATE] [Control Systems — Block Diagrams]

CRO displays:

- A) Current vs Time

B) Voltage vs Time

C) Power vs Time

D) Frequency vs Time

Q.29 [2 Marks] [MODERATE] [Digital Electronics — Logic Gates]

LVDT measures:

- A) Displacement
- B) Velocity
- C) Acceleration
- D) Force

Q.30 [2 Marks] [MODERATE] [Analog Electronics — Op-Amps]

RTD uses:

- A) Semiconductor
- B) Pure metal
- C) Thermocouple
- D) Thermistor

Q.31 [2 Marks] [MODERATE] [Sensors & Transducers — Optical Sensors]

Strain gauge factor GF =:

- A) $9E''\delta'' \rightarrow ''L/L$
- B) $9D\hat{A}\hat{A} \rightarrow ''R/R$
- C) $9E''\delta'' r ''L/L$
- D) $9E''\delta''L$

Q.32 [2 Marks] [MODERATE] [Measurement Systems — CRO]

CRO displays:

- A) Current vs Time
- B) Voltage vs Time
- C) Power vs Time
- D) Frequency vs Time

Q.33 [2 Marks] [HARD] [Control Systems — Compensators]

LVDT measures:

- A) Displacement
- B) Velocity
- C) Acceleration
- D) Force

Q.34 [2 Marks] [HARD] [Digital Electronics — Microprocessors]

RTD uses:

- A) Semiconductor
- B) Pure metal
- C) Thermocouple
- D) Thermistor

Q.35 [2 Marks] [HARD] [Analog Electronics — Amplifiers]

Strain gauge factor GF =:

- A) $9E''\delta'' \rightarrow ''L/L$

B) 9DÂôÂ ò "R/R

C) 9E"ö" r "L/L

D) 9E"Ó"L

EduNeuro

Section B — Multiple Select Questions (MSQ)

Q.36 [2 Marks] [HARD] [Sensors & Transducers — Thermoelectric]

Which statements are correct?

- A) Statement A
 - B) Statement B
 - C) Statement C
 - D) Statement D
 - E) Statement E
-

Q.37 [2 Marks] [HARD] [Measurement Systems — CRO]

Which statements are correct?

- A) Statement A
 - B) Statement B
 - C) Statement C
 - D) Statement D
 - E) Statement E
-

Q.38 [2 Marks] [HARD] [Control Systems — PID Control]

Which statements are correct?

- A) Statement A
 - B) Statement B
 - C) Statement C
 - D) Statement D
 - E) Statement E
-

Q.39 [2 Marks] [HARD] [Digital Electronics — ADC/DAC]

Which statements are correct?

- A) Statement A
 - B) Statement B
 - C) Statement C
 - D) Statement D
 - E) Statement E
-

Q.40 [2 Marks] [HARD] [Analog Electronics — Amplifiers]

Which statements are correct?

- A) Statement A
 - B) Statement B
 - C) Statement C
 - D) Statement D
 - E) Statement E
-

Section C — Numerical Answer Type (NAT)**Q.51 [2 Marks] [HARD] [Sensors & Transducers — Inductive]**

Wheatstone bridge: $R_1=R_2=R_3=R_4=100\Omega$ à Output voltage (V)?

Answer: _____

Q.52 [2 Marks] [HARD] [Measurement Systems — Signal Conditioning]

RTD: Pt100 at 0°C has resistance = ?

Answer: _____

Q.53 [2 Marks] [HARD] [Control Systems — PID Control]

Wheatstone bridge: $R_1=R_2=R_3=R_4=100\Omega$ à Output voltage (V)?

Answer: _____

Q.54 [2 Marks] [HARD] [Digital Electronics — Combinational Circuits]

RTD: Pt100 at 0°C has resistance = ?

Answer: _____

Q.55 [2 Marks] [HARD] [Analog Electronics — Oscillators]

Wheatstone bridge: $R_1=R_2=R_3=R_4=100\Omega$ à Output voltage (V)?

Answer: _____

Q.56 [2 Marks] [HARD] [Sensors & Transducers — Optical Sensors]

RTD: Pt100 at 0°C has resistance = ?

Answer: _____

Q.57 [2 Marks] [HARD] [Measurement Systems — CRO]

Wheatstone bridge: $R_1=R_2=R_3=R_4=100\Omega$ à Output voltage (V)?

Answer: _____

Q.58 [2 Marks] [HARD] [Control Systems — Compensators]

RTD: Pt100 at 0°C has resistance = ?

Answer: _____

Q.59 [2 Marks] [HARD] [Digital Electronics — ADC/DAC]

Wheatstone bridge: $R_1=R_2=R_3=R_4=100\Omega$ Output voltage (V)?

Answer: _____

Q.60 [2 Marks] [HARD] [Analog Electronics — Oscillators]

RTD: Pt100 at 0°C has resistance = ?

Answer: _____

EduNeuro

Answer Key

Verify your answers after completing the full paper.

Q.1:	A	Q.2:	B	Q.3:	A
Q.4:	B	Q.5:	A	Q.6:	B
Q.7:	A	Q.8:	B	Q.9:	A
Q.10:	B	Q.11:	A	Q.12:	B
Q.13:	A	Q.14:	B	Q.15:	A
Q.16:	B	Q.17:	A	Q.18:	B
Q.19:	A	Q.20:	B	Q.21:	A
Q.22:	B	Q.23:	A	Q.24:	B
Q.25:	A	Q.26:	B	Q.27:	A
Q.28:	B	Q.29:	A	Q.30:	B
Q.31:	A	Q.32:	B	Q.33:	A
Q.34:	B	Q.35:	A	Q.36:	AC
Q.37:	AC	Q.38:	AC	Q.39:	AC
Q.40:	AC	Q.41:	AC	Q.42:	AC
Q.43:	AC	Q.44:	AC	Q.45:	AC
Q.46:	AC	Q.47:	AC	Q.48:	AC
Q.49:	AC	Q.50:	AC	Q.51:	0
Q.52:	100	Q.53:	0	Q.54:	100
Q.55:	0	Q.56:	100	Q.57:	0
Q.58:	100	Q.59:	0	Q.60:	100

Detailed Solutions

Question 1*[Sensors & Transducers — Inductive]*

LVDT measures:

Answer: (A)

LVDT = Linear Variable Differential Transformer. Measures linear displacement.

Question 2*[Measurement Systems — Bridge Circuits]*

RTD uses:

Answer: (B)

RTD uses pure metal (Pt, Ni) with positive temperature coefficient.

Question 3*[Control Systems — PID Control]*Strain gauge factor $GF =$:**Answer:** (A) $GF = (9E''\delta''' \div f''L/L)$. Gauges strain in conductors.**Question 4***[Digital Electronics — Sequential Circuits]*

CRO displays:

Answer: (B)

Cathode Ray Oscilloscope displays voltage vs time.

Question 5*[Analog Electronics — Op-Amps]*

LVDT measures:

Answer: (A)

LVDT = Linear Variable Differential Transformer. Measures linear displacement.

Question 6*[Sensors & Transducers — Digital Transducers]*

RTD uses:

Answer: (B)

RTD uses pure metal (Pt, Ni) with positive temperature coefficient.

Question 7*[Measurement Systems — Signal Conditioning]*Strain gauge factor $GF =$:**Answer:** (A) $GF = (9E''\delta''' \div f''L/L)$. Gauges strain in conductors.**Question 8***[Control Systems — Root Locus]*

CRO displays:

Answer: (B)

Cathode Ray Oscilloscope displays voltage vs time.

Question 9*[Digital Electronics — ADC/DAC]*

LVDT measures:

Answer:

LVDT = Linear Variable Differential Transformer. Measures linear displacement.

Question 10 [Analog Electronics — Op-Amps]

RTD uses:

Answer: (B)

RTD uses pure metal (Pt, Ni) with positive temperature coefficient.

Question 11 [Sensors & Transducers — Resistive/Capacitive]

Strain gauge factor $GF =$:

Answer: (A)

$GF = (9E''\delta''' \div f''L/L)$. Gauges strain in conductors.

Question 12 [Measurement Systems — Bridge Circuits]

CRO displays:

Answer: (B)

Cathode Ray Oscilloscope displays voltage vs time.

Question 13 [Control Systems — Root Locus]

LVDT measures:

Answer: (A)

LVDT = Linear Variable Differential Transformer. Measures linear displacement.

Question 14 [Digital Electronics — Logic Gates]

RTD uses:

Answer: (B)

RTD uses pure metal (Pt, Ni) with positive temperature coefficient.

Question 15 [Analog Electronics — Oscillators]

Strain gauge factor $GF =$:

Answer: (A)

$GF = (9E''\delta''' \div f''L/L)$. Gauges strain in conductors.

Question 16 [Sensors & Transducers — Digital Transducers]

CRO displays:

Answer: (B)

Cathode Ray Oscilloscope displays voltage vs time.

Question 17 [Measurement Systems — Signal Conditioning]

LVDT measures:

Answer: (A)

LVDT = Linear Variable Differential Transformer. Measures linear displacement.

Question 18 [Control Systems — PID Control]

RTD uses:

Answer:

(B)

RTD uses pure metal (Pt, Ni) with positive temperature coefficient.

Question 19 [Digital Electronics — Microprocessors]

Strain gauge factor $GF =$:

Answer: (A)

$GF = (9E^{-6} \text{ } \Omega / L) / f \text{ } L/L$. Gauges strain in conductors.

Question 20 [Analog Electronics — Amplifiers]

CRO displays:

Answer: (B)

Cathode Ray Oscilloscope displays voltage vs time.

Question 21 [Sensors & Transducers — Optical Sensors]

LVDT measures:

Answer: (A)

LVDT = Linear Variable Differential Transformer. Measures linear displacement.

Question 22 [Measurement Systems — Instrument Types]

RTD uses:

Answer: (B)

RTD uses pure metal (Pt, Ni) with positive temperature coefficient.

Question 23 [Control Systems — Compensators]

Strain gauge factor $GF =$:

Answer: (A)

$GF = (9E^{-6} \text{ } \Omega / L) / f \text{ } L/L$. Gauges strain in conductors.

Question 24 [Digital Electronics — Microprocessors]

CRO displays:

Answer: (B)

Cathode Ray Oscilloscope displays voltage vs time.

Question 25 [Analog Electronics — Amplifiers]

LVDT measures:

Answer: (A)

LVDT = Linear Variable Differential Transformer. Measures linear displacement.

Question 26 [Sensors & Transducers — Inductive]

RTD uses:

Answer: (B)

RTD uses pure metal (Pt, Ni) with positive temperature coefficient.

Question 27 [Measurement Systems — CRO]

Strain gauge factor $GF =$:

Answer:

$GF = (9E''\delta''' \div f''L/L)$. Gauges strain in conductors.

Question 28 [Control Systems — Block Diagrams]

CRO displays:

Answer: (B)

Cathode Ray Oscilloscope displays voltage vs time.

Question 29 [Digital Electronics — Logic Gates]

LVDT measures:

Answer: (A)

LVDT = Linear Variable Differential Transformer. Measures linear displacement.

Question 30 [Analog Electronics — Op-Amps]

RTD uses:

Answer: (B)

RTD uses pure metal (Pt, Ni) with positive temperature coefficient.

Question 31 [Sensors & Transducers — Optical Sensors]

Strain gauge factor $GF =$:

Answer: (A)

$GF = (9E''\delta''' \div f''L/L)$. Gauges strain in conductors.

Question 32 [Measurement Systems — CRO]

CRO displays:

Answer: (B)

Cathode Ray Oscilloscope displays voltage vs time.

Question 33 [Control Systems — Compensators]

LVDT measures:

Answer: (A)

LVDT = Linear Variable Differential Transformer. Measures linear displacement.

Question 34 [Digital Electronics — Microprocessors]

RTD uses:

Answer: (B)

RTD uses pure metal (Pt, Ni) with positive temperature coefficient.

Question 35 [Analog Electronics — Amplifiers]

Strain gauge factor $GF =$:

Answer: (A)

$GF = (9E''\delta''' \div f''L/L)$. Gauges strain in conductors.

Question 36 [Sensors & Transducers — Thermoelectric]

Which statements are correct?

Answer:

Based on theoretical analysis of the topic.

Question 37 [Measurement Systems — CRO]

Which statements are correct?

Answer: (A, C)

Based on theoretical analysis of the topic.

Question 38 [Control Systems — PID Control]

Which statements are correct?

Answer: (A, C)

Based on theoretical analysis of the topic.

Question 39 [Digital Electronics — ADC/DAC]

Which statements are correct?

Answer: (A, C)

Based on theoretical analysis of the topic.

Question 40 [Analog Electronics — Amplifiers]

Which statements are correct?

Answer: (A, C)

Based on theoretical analysis of the topic.

Question 41 [Sensors & Transducers — Optical Sensors]

Which statements are correct?

Answer: (A, C)

Based on theoretical analysis of the topic.

Question 42 [Measurement Systems — Instrument Types]

Which statements are correct?

Answer: (A, C)

Based on theoretical analysis of the topic.

Question 43 [Control Systems — Routh-Hurwitz]

Which statements are correct?

Answer: (A, C)

Based on theoretical analysis of the topic.

Question 44 [Digital Electronics — Microprocessors]

Which statements are correct?

Answer: (A, C)

Based on theoretical analysis of the topic.

Question 45 [Analog Electronics — Diodes]

Which statements are correct?

Answer:

Based on theoretical analysis of the topic.

Question 46 [Sensors & Transducers — Thermoelectric]

Which statements are correct?

Answer: (A, C)

Based on theoretical analysis of the topic.

Question 47 [Measurement Systems — Bridge Circuits]

Which statements are correct?

Answer: (A, C)

Based on theoretical analysis of the topic.

Question 48 [Control Systems — PID Control]

Which statements are correct?

Answer: (A, C)

Based on theoretical analysis of the topic.

Question 49 [Digital Electronics — Combinational Circuits]

Which statements are correct?

Answer: (A, C)

Based on theoretical analysis of the topic.

Question 50 [Analog Electronics — Filters]

Which statements are correct?

Answer: (A, C)

Based on theoretical analysis of the topic.

Question 51 [Sensors & Transducers — Inductive]

Wheatstone bridge: $R_1=R_2=R_3=R_4=100\Omega$ → Output voltage (V)?

Answer: (0)

Balanced bridge: $R_1/R_2 = R_4/R_3 = 1$. Output = 0.

Question 52 [Measurement Systems — Signal Conditioning]

RTD: Pt100 at 0°C has resistance = ?

Answer: (100)

Pt100 = 100 Ω B 0. Coefficient α_H 0.385 $\pm$ 0.001.

Question 53 [Control Systems — PID Control]

Wheatstone bridge: $R_1=R_2=R_3=R_4=100\Omega$ → Output voltage (V)?

Answer: (0)

Balanced bridge: $R_1/R_2 = R_4/R_3 = 1$. Output = 0.

Question 54 [Digital Electronics — Combinational Circuits]

RTD: Pt100 at 0°C has resistance = ?

Answer:

Pt100 = 100:° B 0. Coefficient "H 0.385 :°û 0.

Question 55 [Analog Electronics — Oscillators]

Wheatstone bridge: $R_1=R_2=R_3=R_4=100\text{:}^\circ$ à Output voltage (V)?

Answer: (0)

Balanced bridge: $R_1/R_2 = R_4/R_3 = 1$. Output = 0.

Question 56 [Sensors & Transducers — Optical Sensors]

RTD: Pt100 at 0°C has resistance = ?

Answer: (100)

Pt100 = 100:° B 0. Coefficient "H 0.385 :°û 0.

Question 57 [Measurement Systems — CRO]

Wheatstone bridge: $R_1=R_2=R_3=R_4=100\text{:}^\circ$ à Output voltage (V)?

Answer: (0)

Balanced bridge: $R_1/R_2 = R_4/R_3 = 1$. Output = 0.

Question 58 [Control Systems — Compensators]

RTD: Pt100 at 0°C has resistance = ?

Answer: (100)

Pt100 = 100:° B 0. Coefficient "H 0.385 :°û 0.

Question 59 [Digital Electronics — ADC/DAC]

Wheatstone bridge: $R_1=R_2=R_3=R_4=100\text{:}^\circ$ à Output voltage (V)?

Answer: (0)

Balanced bridge: $R_1/R_2 = R_4/R_3 = 1$. Output = 0.

Question 60 [Analog Electronics — Oscillators]

RTD: Pt100 at 0°C has resistance = ?

Answer: (100)

Pt100 = 100:° B 0. Coefficient "H 0.385 :°û 0.
