



Connectors > Lighting Connectors > Poke-In Connectors



Connector System: **Wire-to-Board**
Number of Positions: **1**
Connector & Contact Terminates To: **Wire & Cable**
Connector Height: **3.9 mm [.154 in]**
Termination Method to PCB: **Surface Mount**

Features

Electrical Characteristics

Operating Voltage	250 VDC
-------------------	---------

Industry Standards

Compatible With Agency/Standards Products	UL, CSA
UL Flammability Rating	UL 94V-0
Compatible With Approved Standards Products	UL E28476, UL 1977, CSA/C22.2 No. 182.3-M1987

Body Features

Primary Product Color	White
Header Mating Direction	Horizontal

Mechanical Attachment

Connector Mounting Type	Board Mount
PCB Mount Retention	With

Packaging Features

Packaging Method	SMT Pocket Tape
------------------	-----------------



Contact Features

PCB Contact Termination Area Plating Material Thickness	3 µm[118.11 µin]
Contact Layout	Inline
Contact Underplating Material	Nickel
Contact Mating Area Plating Material	Tin
PCB Contact Termination Area Plating Material	Tin
PCB Contact Termination Area Plating Material Finish	Matte
Contact Fabrication	Stamped & Formed
Contact Mating Area Plating Material Finish	Matte
Contact Mating Area Plating Material Thickness	3 µm[118 µin]
Contact Current Rating (Max)	4 A

Dimensions

Compatible Insulation Diameter Range	2.1 mm[.083 in]
Connector Height	3.9 mm[.154 in]
Wire Size	18 – 22 AWG

Product Type Features

Product Line	Poke-In
Connector System	Wire-to-Board
Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Positions	1
---------------------	---

Termination Features

Termination Method to PCB	Surface Mount
---------------------------	---------------

Usage Conditions

Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
-----------------------------	----------------------------

Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

Other

EU RoHS Compliance	Compliant
EU ELV Compliance	Compliant

Product Compliance



For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Reflow solder capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



Customers Also Bought



TE Part #1-1879011-3
SMF2 680R 5%

TE Part #1879666-6
H8 150K 0.1% 15PPM

TE Part #1623932-6
CFR50 5% 100R

TE Part #8-1879208-0
CPF 0402 20K 0.1% 25PPM 1K RL

TE Part #3-1623931-7
CFR25 5% 47R

TE Part #4-1419128-6
OJE-SS-112LM,000

TE Part #5-2176397-6
3502 200R 1%

TE Part #1-1623788-7
SQM5 68R 5% (WIRE)

TE Part #7-1623931-7
CFR25 5% 820R

TE Part #7-1625892-7
3W SM M/OX 5% 18K

Documents

Product Drawings

Connector,1 Pos SMT Poke-In

English

CAD Files

Customer View Model

ENG_CVM_CVM_2008563-1_A.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2008563-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2008563-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages



SMT_AND_THRU-HOLE_POKE-IN_WIRE_LIGHTING_CONNECTORS

English

Product Specifications

Application Specification

English

Agency Approvals

UL Report

English