

Low Voltage Multiple Spots

3 Light Trim Lamp Included

| _ | • |
|-------------|-------------------|
| Model | Finish |
| MT-316LED | WT White |
| MT-316LEDTL | WT/WT White/White |
| | |

Fixture Type:

Catalog Number:

Project:

Location:

Example: MT-316LED-WT/WT

DESCRIPTION

Low Voltage Multiple Spots are ideal for perimeter lighting applications in smaller scale retail, commercial and hospitality environments. Square single light gimbal ring style adjustable recessed fixture, available with flanged trim or Invisible Trim™, designed to sit flush with the ceiling for a clean architectural look. Housing, trim, and lamp are sold separately.

FEATURES

- Trim version has a 1/4" low profile, Invisible Trim™ sits flush to ceiling
- The supplied clear glass lens can be replaced by a variety of lenses or accessories
- 5 year warranty

SPECIFICATIONS

Construction Stamped metal trim

Power: 21W

Light Source: LED MR16 (Included)

Cut Out: Trim: 5 3/16" x 13 1/4", Trimless: 5 5/8" x 13 3/4"

Finish: Electrostatically Powder Coated: White/White, White


Standards: UL, cUL, Damp Location Listed



FINISHES:



LINE DRAWING:



WAC LIGHTING

Low Voltage Multiple Spots

3 Light Housing

Model & Product

MT-316HS Low Voltage Multiple Three Light Non-IC Housing

Example: MT-316HS

DESCRIPTION

Low Voltage Multiple Spots are ideal for perimeter lighting applications in smaller scale retail, commercial and hospitality environments. Square single light gimbal ring style adjustable recessed fixture, available with flanged trim or Invisible Trim™, designed to sit flush with the ceiling for a clean architectural look. Housing, trim, and lamp are sold separately.

FEATURES

- Electronic short circuit and overload protection with automatic reset
- Soft start to prolong lamp life
- Transformer concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Construction Aluminum hardware with mouth blown etched glass diffuser

Input: 120 VAC,50/60Hz **Dimming:** ELV: 100-10%


Light Source: Halogen or LED MR16

Mounting: Supplied with hanger bars, adjustable from 15"-24 1/2" to

accommodate various joist construction and grid sizes


Ceiling Thickness: 1/2" - 1"

Standards: UL, cUL, Damp Location Listed, Non IC





LINE DRAWING:





Low Voltage Multiple Spots

3 Light Housing

| Fixture Type: | | |
|-----------------|--|--|
| Catalog Number: | | |
| Project: | | |
| Location: | | |

ACCESSORIES

| Model | Description | Finish |
|----------------------------------------------------------|--------------------------------------------------------------|-------------------------------|
| LENS-16-RED LENS-16-GRN LENS-16-BLU LENS-16-AMB | Colored Lens Colored Lens Colored Lens Colored Lens | Red Green Blue Amber |
| LENS-16-FR | Clear/Frosted Lens | Frosted |
| LENS-16-SPR | Spread Lens | Spread Lens |
| LENS-16-UVF | UV Filter lens | Clear |
| LENS-16-BEL | Beam Elongating Lens | Beam Elongating |
| LENS-16-HCL | Honeycomb Louver | Black |