



Connectors > Lighting Connectors > Street Lighting Controls > Street Lighting Power Management



Compatible With Agency/Standards Products: **UL**

Number of Positions: **3**

Sealable: **No**

Contact Current Rating (Max): **15 A**

Operating Temperature Range: **-40 – 105 °C [-40 – 221 °F]**

Features

Housing Features

Centerline (Pitch)	15.3 mm[.606 in]
--------------------	------------------

Industry Standards

Compatible With Agency/Standards Products	UL
---	----

Product Type Features

Sealable	No
----------	----

Configuration Features

Number of Positions	3
---------------------	---

Contact Features

Contact Current Rating (Max)	15 A
------------------------------	------

Usage Conditions

Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
-----------------------------	----------------------------

Other

EU RoHS Compliance	Compliant
EU ELV Compliance	Compliant



Product Compliance

For compliance documentation, visit the product page on [TE.com](#)>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2024 (241) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 2343403-1
RECEPTACLE, LUMAWISE
ENDURANCE S, KEYED

TE Part # 2363638-2
Recept, LUMAWISE Endurance S2 Kit,
KeyA

TE Part # 2341474-2
SEALING CAP, RCPT, LUMAWISE
ENDURANCE S

TE Part # 2341474-1
SEALING CAP, RCPT, LUMAWISE
ENDURANCE S



TE Part # 2376865-6
Rcpt Assy, w/ intg gasket; PC; 3P

TE Part # 1-2363638-2
Rcpt, LUMAWISE Endurance S2 Kit, KeyA, Dots

TE Part # CAT-Z23-DRE
LUMAWISE Endurance N Poke-In: Streetlight Dimming Receptacles

Also in the Series

Custom Terminal Block

PCB Terminal Blocks(7)

Street Lighting Power Management(1)

Customers Also Bought

TE Part #2176090-2
RP 1J 0.166W 133K 0.1% 25PPM 1K RL

TE Part #5-103635-4
05 MTE HDR SRRA LTCH.100CL LF

TE Part #61968-1
110 FASTON TAB TPBR

TE Part #1-322249-0
PG SPD FLG 22-16COMM22-18MIL 8

TE Part #FC2231-0000-0010-L
MID RANGE COMPRESSION SENSOR

TE Part #1-1879502-4
CRGH2512 5% 47K 2W

TE Part #2213254-1
LUMAWISE LED HOLDER Z50 LOW PROFILE 1919

TE Part #321235
RECEPT, FASTON SPLICE 22-10

TE Part #2834171-3
ULTRAMINIATURE SLIM CONTACT

TE Part #350789-1
03P UMNL PIN HDR ASSY 94VO



Documents

Product Drawings

LUMAWISE POWER INPUT TERMINAL BLOCK (TB)

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2382635-1_1.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2382635-1_1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2382635-1_1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

LUMAWISE Power Input Terminal Block

English

Product Specifications

Application Specification

English

Agency Approvals

UL

English