

Lotos 4" & 6" Round

Adjustable Downlight 5CCT

| Adjustable Downlight SCC1 | | | | | | | |
|---------------------------|--------------|---------------------------|--------|------|----------|--|--|
| Model | Beam | Color Temp & CRI | Lumens | CBCP | Finish | | |
| R4ERAR | W 45° | 9CS | 1290 | 1920 | BK Black | | |
| R6ERAR | | 2700K/3000K/3500K/4000K/5 | 1340 | 1896 | WT White | | |
| | | 000K - 90 | 690 | 925 | | | |
| | | | 800 | 1020 | | | |

Example: R4ERAR-W9CS-BK

FEATURES

- 5-CCT Switchable between 2700K and 5000K
- Multiple LED array for uniform illumination
- · Rotatable multi-axis gimbal ring
- · Driver included
- 5 year warranty

SPECIFICATIONS

Construction Steel with frosted TIR lens

Power: 9W, 15W

Input: 120 -277 VAC,50/60Hz
Dimming: ELV: 100-5%, TRIAC: 100-5%

Light Source: Integrated LED

Rated Life: 50,000 Hours

Mounting: Heavy gauge retention clips secures fixture to ceiling

Cut Out: 4 1/4", 5"

Finish: Electrostatically powder coated Black, Electrostatically powder

coated White

Ceiling Thickness: 1/2" - 1"

Operating Temp: -4°F to 104°F (-20°C to 40°C)

Standards: ETL, cETL, Wet Location Listed, Energy Star 2.0, Airtight, IC



FINISHES:

Fixture Type:


Project:

Location:

Catalog Number:



LINE DRAWING:





Lotos 4" & 6" Round

Adjustable Downlight 5CCT

| Fixture Type: | |
|-----------------|--|
| Catalog Number: | |
| Project: | |
| Location: | |

| ACCESSORIES | | | | |
|-------------|-----------|-------------|--------|--|
| | Model | Description | Finish | |
| | RER-FRAME | Lotos | | |
| | | | | |
| | | | | |