

Ocularc 3.0

0° - 35° Adjustable Square

F	ixture Type:
C	Catalog Number:
P	Project:
L	ocation:

Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish
R3BSA	F 50°	927 2700K - 90	900	1196	BK Black
		930 3000K - 90	970	1285	BN Brushed Nickel
	N 25°	927 2700K - 90	915	2513	WT White
		930 3000K - 90	985	2701	
	S 15°	927 2700K - 90	900	4384	
		930 3000K - 90	970	4712	

Example: R3BSA-F927-BK

DESCRIPTION

Engineered with state of the art LED and driver technology, Ocularc 3.0, 2.0, 1.0 family of recessed lighting offers various styles, IC and Airtight Rated New Construction and Remodel, and low glare optical distributions to beautifully illuminate a diverse range of applications.

FEATURES

- Shallow housing under 4in depth
- Single spot light source
- 5 year warranty

SPECIFICATIONS

Construction Die-cast aluminum trim and heat sink

Power: 11W

Light Source: Integrated LED, 3 Step Mac Adam Ellipse

Rated Life: 50,000 Hours

Mounting: Heavy gauge retention clips support trim firmly

Finish: Electrostatically Powder Coated: White, Electroplated Brushed

Nickel, Black

Operating Temp: -4°F to 104°F (-20°C to 40°C)

Standards: ETL, cETL, Damp Location Listed, Energy Star 2.0, Airtight



FINISHES:








Brushed White

LINE DRAWING:



WAC LIGHTING

Ocularc 3.0

Remodel Housing

Model & Product

R3BBRT-10 Ocularc 3.0 LED Remodel IC-Rated Housing

Example: R3BBRT-10

DESCRIPTION

Engineered with state of the art LED and driver technology, Ocularc 3.0, 2.0, 1.0 family of recessed lighting offers various styles, IC and Airtight Rated New Construction and Remodel, and low glare optical distributions to beautifully illuminate a diverse range of applications.

FEATURES

- Shallow housing under 4in depth
- Driver concealed within the fixture
- 5 year warranty



Construction 20 gauge cold rolled steel wiring box

Power: 11W

Input: 120 VAC,50/60Hz

Dimming: YES


Rated Life: 50,000 Hours

Mounting: Heavy gauge retention clips secures housing firmly to ceiling

Cut Out: 4 1/4"
Ceiling Thickness: 1/2" - 1"


Operating Temp: -4°F to 104°F (-20°C to 40°C)

Standards: ETL, cETL, IC





LINE DRAWING:



WAC LIGHTING

Ocularc 3.0

New Construction Housing

Model

R3BNICA-10 Ocularc 3.0 LED New Construction IC-Rated Airtight Housing (120V)

R3BNICA-10U Ocularc 3.0 LED New Construction IC-Rated Airtight Housing

R3BNICA-10U-EM Ocularc 3.0 LED New Construction IC-Rated Airtight Housing (120-277V)

Example: R3BNICA-10

DESCRIPTION

Engineered with state of the art LED and driver technology, Ocularc 3.0, 2.0, 1.0 family of recessed lighting offers various styles, IC and Airtight Rated New Construction and Remodel, and low glare optical distributions to beautifully illuminate a diverse range of applications.

FEATURES

- Shallow housing under 4in depth
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Construction 20 gauge cold rolled steel wiring box

Power: 11W

Input: 120 VAC,120-277 VAC,50/60Hz

Dimming: YES

Rated Life: 50,000 Hours

Mounting: Heavy gauge retention clips secures housing firmly to ceiling

Cut Out: 4 1/4"
Ceiling Thickness: 1/2" - 1"

Operating Temp: -4°F to 104°F (-20°C to 40°C)

Standards: ETL, cETL, Airtight, IC



LINE DRAWING:

Fixture Type:

Project:

Location:

Catalog Number:

