WAC LIGHTING

Ocularc 1.0

8W 0°-20° Adjustable Square

Tixture Type.	
Catalog Number:	
Project:	
Location:	

Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish
R1BSA-08	F 45°	927 2700K - 90	585	870	BK Black
		930 3000K - 90	630	941	BN Brushed Nickel
	N 25°	927 2700K - 90	630	2225	WT White
		930 3000K - 90	680	2405	

Example: R1BSA-08-F927-BK

DESCRIPTION

Engineered with state of the art LED and driver technology, Ocularc 3.0, 2.0, 1.0 family of recessed lighting offers various styles, IC and Airtight Rated New Construction and Remodel, and low glare optical distributions to beautifully illuminate a diverse range of applications.

FEATURES

- Cutout 2 1/2"
- Single spot light source
- Ceiling thickness: 1/2" 1"
- Sold as New Construction, may be reconfigured in the field for Remodel
- Driver concealed within the fixture
- 5 year warranty



Construction Die-cast aluminum trim with aluminum heat sink

Power: 7.5W

 Input:
 120 VAC,50/60Hz

 Dimming:
 ELV: 100-5%, YES

Light Source: Integrated LED, 3 Step Mac Adam Ellipse

Rated Life: 50,000 Hours

Cut Out: 2 1/2"

Finish: Electrostatically Powder Coated: White, Black, Electroplated

Brushed Nickel

Ceiling Thickness: 1/2" - 1"

Operating Temp: -4°F to 104°F (-20°C to 40°C)

Standards: ETL, cETL, Damp Location Listed, Energy Star 2.0, Airtight, IC



FINISHES:

Fixture Type



LINE DRAWING:

