

# 1" LEDme

# Catalog Number:

# Project:

#### Location:

Fixture Type:

# Round Adjustable Downlight (Remote Driver)

Model	Color Temp & CRI	Lumens	CBCP	Finish
HR-LED232R	<b>27</b> 2700K - 85	245	505	BN Brushed Nickel
	<b>30</b> 3000K - 85	250	515	GM Gun Metal
	<b>35</b> 3500K - 85	265	546	WT White
	<b>40</b> 4000K - 85	280	580	

Example: HR-LED232R-27-BN

### **DESCRIPTION**

Perfect for ceilings, under cabinet and wall niches. LED Miniature Recessed Downlights offer a super low profile and Die-cast aluminum trim with a 25° cutoff angle for comfortable general and task lighting.

#### **FEATURES**

- Round recessed trim with interior open reflector for use with a remote driver
- Driver Required: LD-700MA03-EDIM-IS or LD-700MA09-EDIM-IS
- 5 year warranty

#### **SPECIFICATIONS**

**Construction** Die-cast aluminum trim, aluminum heat sink and 20 gauge

steel housing painted black.

Power: 3W

**Dimming:** ELV: 100-10%

Light Source: Integrated LED, 3 Step Mac Adam Ellipse

Rated Life: 80,000 Hours

**Mounting:** Heavy gauge retention clips secures housing firmly to ceiling

Cut Out: 2 1/2"

Finish: Electrostatically Powder Coated: Electroplated Brushed Nickel,

Electroplated Gun Metal, White

Ceiling Thickness: 1/2" - 1"

Operating Temp: -4°F to 104°F (-20°C to 40°C)

Standards: UL, cUL, Damp Location Listed, Non IC



#### **FINISHES:**







Brushed Nickel

Gun Metal White

## LINE DRAWING:

