
EXTERMINATOR II

Monopoint Luminaire - 1035







Fixture Type:	
Catalog Number:	
Project:	
Location:	

PRODUCT DESCRIPTION

Exterminator II offers superior light output in a small, unobtrusive design. Developed for upscale residential and commercial environments.

FEATURES

- · Accommodates one lens accessory and one glare control accessory
- 365° horizontal rotation and 180° vertical aiming
- Ceiling and wall mountable
- 50,000 hour rated life
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Die-cast aluminum with removable front cap for easy change of

lenses or accessories

Power Consumption: 36W

Input: 120V-277V AC 50/60HZ

Dimming: 100%-1% Electronic Low Voltage (ELV, 120V only),

TRIAC (120V only) and 0-10V

Finish: Powder coated Black and White,

Electroplated Brushed Nickel

Standards: UL & cUL Damp Location listed, Title 24 JA8 Compliant.

System	Beam		Color	Гетр	CRI	Lumens	CBCP	Finish	
	S	15°	827 927 830 930 835 840	2700K 2700K 3000K 3000K 3500K 4000K	85 90 85 90 85 85	3120 2575 3315 2690 3395 3410	29050 23990 30870 25070 31615 31770		
MO-1035	N	30°	827 927 830 930 835 840	2700K 2700K 3000K 3000K 3500K 4000K	85 90 85 90 85 85	2860 2360 3035 2465 3110 3125	7295 6025 7755 6295 7940 7980	BK Black BN Brushed I WT White	Nickei
	F	51°	827 927 830 930 835 840	2700K 2700K 3000K 3000K 3500K 4000K	85 90 85 90 85 85	2885 2380 3065 2490 3140 3155	3240 2675 3445 2795 3525 3545		

LENS	ACCE	ESSO	RIES

LENS-20-AMB	Amber
LENS-20-BLU	Blue
LENS-20-GRN	Green
LENS-20-RED	Red
LENS-20-UVF	UV Filter
LENS-20-FR	Frosted
LENS-20-SPR	Spread
LENS-20-BEL	Beam Elongating

GLARE CONTROL - CROSS LOUVER

LENS-20P-CRL-BK	Black
LENS-20P-CRL-BN	Brushed Nickel
LENS-20P-CRL-WT	White

GLARE CONTROL - SNOOT

LENS-20-SNOOT-BK	Black
LENS-20-SNOOT-BN	Brushed Nickel
LENS-20-SNOOT-WT	White

Example: MO-1035F-830-BN

1