




**VINE™**

**VN-SERIES | FLEXIBLE LIGHTING SYSTEM**


Fixture Type: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_



### BEND RADIUS



MODEL:	VN24K	VN27K	VN30K	VN35K	VN40K
Kelvin	2400K	2700K	3000K	3500K	4000K
Lumens	230 lm/ft	268 lm/ft	275 lm/ft	281 lm/ft	290 lm/ft

### PRODUCT FEATURES

- 360° Continuous Light Source
- Universal Dimming
- 36,000 Hour Life
- IP65 Rated for Outdoor Use
- Factory-Installed Power Feed
- Injection-Molded Flush End Caps
- For Use with 24V Power Supplies

### ORDERING INFORMATION

Example: **VN-25-48-30K-E-72**

Series	Diameter	Length (Unlimited)	Color	Feed Point	Feed Length
<b>VN</b>	<b>25</b>				

**VN - Vine**      **25 - 1 Inch (25mm)**      **Inches**      **24K - 2400K**  
**27K - 2700K**  
**30K - 3000K**  
**35K - 3500K**  
**40K - 4000K**      **E - End Feed**  
**SF - Side Feed**      **72 - 72 Inch (Standard)**  
**192 - 192 Inch**

Conforms to ANSI/UL Standard 2108  
Certified to CAN/CSA Standard C22.2 No. 250.0






## VINE™ MOUNTING AND ACCESSORIES

### VISIBLE MOUNTING CLIP



#### SPECIFICATIONS

Model	VN-25-CP
Material	Clear Polycarbonate
Length	0.984" (25mm)
Width	2.032" (51.6mm)
Height	1.063" (27mm)
Internal Width	1" (25.4mm)



Surface Mounts Straight  
or Curved Runs



OR




### CONCEALED MOUNTING CLIP



#### SPECIFICATIONS

Model	VN-25-CCP
Material	Clear Polycarbonate
Length	1.43" (36mm)
Width	0.75" (19mm)
Height	0.27" (7mm)
Effective Height	0.11" (3mm)



Surface Mounts Straight  
or Curved Runs



OR






## VINE™ MOUNTING AND ACCESSORIES

### SPLICE




#### SPECIFICATIONS

Model	VN-25-CS
Material	Aluminum
Length	1.358" (34.5mm)
Diameter	1.22" (31mm)
Internal Diameter	1" (25.4mm)



Connects Power Feed  
End to Terminal End

For use with Side Feed option






### ARCH



#### SPECIFICATIONS

Model	VN-25-MA-FF
Material	Aluminum
Length	1.654" (42mm)
Diameter	1.28" (32.5mm)
Internal Diameter	1" (25.4mm)




Surface Mounts Power Feed  
End and Terminal End



## VINE™ MOUNTING AND ACCESSORIES

### FLUSH PENDANT




#### SPECIFICATIONS


Model	VN-25-FP-FF
Model w/ Sleeve*	VN-25-FP-2M
Material	Aluminum
EC Length	1.32" (33.5mm)
EC Diameter	1.24" (31.5mm)
CM Length	1.654" (42mm)
CM Diameter	1.28" (32.5mm)
Internal Diameter	1" (25.4mm)

\*Polycarbonate sleeve (not pictured) is required for Vine to hang perfectly vertical.

#### EC—End Cap




#### CM—Ceiling Mount



#### Surface Mounts Power Feed End and Caps Terminal End

### SUSPENDED PENDANT




#### SPECIFICATIONS


Model	VN-25-SP-V-FF
Model w/ Sleeve*	VN-25-SP-V-2M
Material	Aluminum
ECLength	1.654" (42mm)
EC Diameter	1.24" (31.5mm)
SP Length	2.68" (68mm)
SP Diameter	1.24" (31.5mm)
Internal Diameter	1" (25.4mm)
Cable Length	Variable, 6ft max

\*Polycarbonate sleeve (not pictured) is required for Vine to hang perfectly vertical.

#### EC—End Cap



#### SP—Suspended Pendant



#### Suspends Power Feed End and Caps Terminal End



## VINE™ MOUNTING AND ACCESSORIES

### RING CLIP MOUNT




#### SPECIFICATIONS


Model	VN-25-RCP-038
Model w/ Sleeve*	VN-25-RCP-038-2M
Suspension Kit	VN-25-RCP-SP
Material	Clear Polycarbonate
Width	1.15" (29.3mm)
Diameter	1.04" (26.3mm)
Length	1.50" (38.0mm)
Height	1.29" (32.7mm)

\*Polycarbonate sleeve (not pictured) is required for Vine to hang perfectly straight.

#### Front View



#### Side View



Can be used with Universal Standoff or Suspension Cable accessories



Illustration shows mounting with Side Feed option.