

Ocularc 2.0

9W 0° - 35° Adjustable Round

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish
R2BRA	F 45°	927 2700K - 90	640	1053	BK Black
		930 3000K - 90	685	1127	BN Brushed Nickel
	N 25°	927 2700K - 90	635	1984	WT White
		930 3000K - 90	680	2123	
	S 15°	927 2700K - 90	535	3131	
		930 3000K - 90	555	3245	

Example: R2BRA-F927-BK

DESCRIPTION

Engineered with state of the art LED and driver technology, Ocularc 3.0, 2.0, 1.0 family of recessed lighting offers various styles, IC and Airtight Rated New Construction and Remodel, and low glare optical distributions to beautifully illuminate a diverse range of applications.

FEATURES

- Cutout 3 1/16"
- Single spot light source
- Ceiling thickness: 1/2" 1"
- Sold as New Construction, may be reconfigured in the field for Remodel
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Construction Die-cast aluminum trim with aluminum heat sink

Power: 9W

Input: 120 VAC,50/60Hz

Dimming: ELV: 100-5%, 0-10V: 100-5%, TRIAC: 100-5%

Light Source: Integrated LED, 3 Step Mac Adam Ellipse

Rated Life: 50,000 Hours **Cut Out:** 3 1/16"

Finish: Electrostatically Powder Coated: White, Black, Brushed Nickel

Ceiling Thickness: 1/2" - 1"

Operating Temp: -4°F to 104°F (-20°C to 40°C)

Standards: ETL, cETL, Damp Location Listed, Energy Star 2.0, Airtight, IC



FINISHES:







Brushed Nickel

White

LINE DRAWING:

