

Project Name

Location

Prepared By



SATCO S11635

12WLED/DW/DNL3/930/SQ/RD/BN

Notes

(revised) 03-08-2023 00:00:00

General

Status	Transitioning
Substitute	S11635R1
Wattage	12W
Voltage	120V
Finish	Brushed Nickel
CCT (Kelvin)	3000K
Color Temperature	Warm White
Lumen Output	840L
Indoor or Outdoor Fixture	Indoor

Specifications

Technology	LED
CRI	90
Beam Angle	40
Rated Hours	50000
Operating Temperature	-20C (-4F) to +45C (+113F)
Dimmable	Yes-Dimmable
Sloped Ceiling	No

Dimensions

Length (in.)	4.38
Width (in.)	4.38
Height (in.)	3
Weight (lb.)	1.18

Compliance

Safety Listing	cETLus - Listed
Location Rating	Wet
UL Application	Ceiling
Energy Star	No
DLC Approved	No
Air Tight Rated	Yes
IC Rated	Yes
California Status	Lawful for sale in California
Title 20 / 24 Status	California T24 Listed
California Prop 65	Lead
RoHS Compliant	Yes
FCC Compliant	Yes
SDS Sheet	LED_Lamp

Additional Information

Additional Information	Integrated j-box for direct wire installation
Installation Notes	*If you purchase The 5W Emergency Driver (S8000) or the 10W Emergency Driver (S8002), you must also purchase the Emergency Driver Enclosure (80-973)
Warranty	5 Year Limited - Fixtures