# WAC LIGHTING

## 4" Low Voltage

### Die Cast Shower Trim Clear Flat Glass

Model & Light Source	Lumens	Finish
HR-D418-S LED MR16 ( Order separately ) HR-D418LED-S LED MR16 ( Included )		WT White

Example: HR-D418-S-WT

#### **DESCRIPTION**

Engineered for high-performance in a compact fixture, 4" Low Voltage Recessed Downlights are styled with form and function. Available for Non-IC installations, a variety of decorative adjustable and Wet Location trim options are available.

#### **FEATURES**

- Accommodates most LED MR16 lamps
- Center lamp holder allows lamp to be tilted up to 35° from vertical
- The supplied clear glass lens can be replaced with one lens accessory
- Steel spring clips secure trim to housing
- 5 year warranty



Construction Die-cast aluminum

Input: 12 VAC

Light Source: LED MR16 (Included), LED MR16 (Order separately)

Finish: Electrostatically Powder Coated: White

Standards: UL, cUL, Wet Location Listed



#### FINISHES:

Fixture Type:

Project:


Location:

Catalog Number:



White

### LINE DRAWING:



# WAC LIGHTING

## 4" Low Voltage

### Remodel Non-IC Housing

Model & Product

HR-8401E 4in Electronic Low Voltage Remodel Non-IC Housing

Example: HR-8401E

#### **DESCRIPTION**

Engineered for high-performance in a compact fixture, 4" Low Voltage Recessed Downlights are styled with form and function. Available with a variety of decorative adjustable and wet location trim options are available.

#### **FEATURES**

- Integral electronic transformer
- J-Box and transformer accessible through ceiling
- Advanced auto-reset, soft start and short circuit protection features
- · Supplied thermal protector protects against over-lamping
- Suitable for 2" × 6" joist installations, for use in shallow applications
- Accommodates most LED MR16 or Halogen MR16 lamps
- · Transformer included
- 5 year warranty

#### **SPECIFICATIONS**

Construction 20 gauge galvanized steel

120 VAC,50/60Hz Input: Dimming: ELV: 100-10%

**Light Source:** Halogen, LED (1W min)

Mounting: Two heavy gauge inner retention clips push out onto ceiling or

other mounting surface to firmly hold housing in place

**Cut Out:** 

**Ceiling Thickness:** 

3/4" **Operating Temp:** -4°F to 104°F (-20°C to 40°C)


Standards: UL, cUL, Damp Location Listed, Non IC





#### **LINE DRAWING:**

Fixture Type:



# WAC LIGHTING

## 4" Low Voltage

### **New Construction Non-IC Housing**

Model & Product

HR-8402E 4in Electronic Low Voltage New Construction Non-IC Housing

Example: HR-8402E

#### **DESCRIPTION**

Engineered for high-performance in a compact fixture, 4" Low Voltage Recessed Downlights are styled with form and function. Available with a variety of decorative adjustable and Wet Location trim options are available.

#### **FEATURES**

- Integral electronic transformer
- J-Box and transformer accessible through ceiling
- Advanced auto-reset, soft start and short circuit protection features
- Supplied thermal protector protects against over-lamping
- Transformer included
- 5 year warranty

#### **SPECIFICATIONS**

**Construction** 20 gauge galvanized steel

Power: 50W

Input: 120 VAC,50/60Hz
Dimming: ELV: 100-10%
Light Source: Halogen

Mounting: Supplied with hanger bars, adjustable from 15"-242" to

accommodate various joist construction and grid sizes.

Cut Out: 4 9/16"
Ceiling Thickness: 3/4"

Operating Temp: -4°F to 104°F (-20°C to 40°C)

Standards: UL, cUL, Damp Location Listed, Non IC



#### **LINE DRAWING:**

Fixture Type:

Project:

Location:

Catalog Number:





# 4" Low Voltage

New Construction Non-IC Housing

Fixture Type:	
Catalog Number:	
Project:	
Location:	

#### ACCESSORIES

 Model	Description	Finish
LENS-16-RED LENS-16-GRN LENS-16-BLU LENS-16-AMB	Colored Lens Colored Lens Colored Lens Colored Lens	Red Green Blue Amber
LENS-16-FR	Clear/Frosted Lens	Frosted
LENS-16-SPR	Spread Lens	Spread Lens
LENS-16-UVF	UV Filter lens	Clear
LENS-16-BEL	Beam Elongating Lens	Beam Elongating
LENS-16-HCL	Honeycomb Louver	Black