

1" LEDme

Round Adjustable Downlight w/ Integral Driver

	- 0 -	- 0 -	_	
Model	Color Temp & CRI	Lumens	CBCP	Finish
HR-LED212E	27 2700K - 85	245	505	BN Brushed Nickel
	30 3000K - 85	250	515	GM Gun Metal
	35 3500K - 85	265	546	WT White
	40 4000K - 85	280	580	

Example: HR-LED212E-27-BN

DESCRIPTION

Perfect for ceilings, under cabinet and wall niches. LED Miniature Recessed Downlights offer a super low profile and Die-cast aluminum trim with a 25° cutoff angle for comfortable general and task lighting.

FEATURES

- New Construction, may be re-configured in the field for Remodel
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Construction Die-cast aluminum trim, aluminum heat sink and 20 gauge

steel housing painted black.

Power: 4W

Input: 120 VAC,50/60Hz **Dimming:** ELV: 100-10%

Light Source: Integrated LED, 3 Step Mac Adam Ellipse

Rated Life: 80,000 Hours

Mounting: Heavy gauge retention clips secures housing firmly to ceiling

Cut Out: 2 1/2"

Finish: Electrostatically Powder Coated: White, Electroplated Brushed

Nickel, Electroplated Gun Metal

Ceiling Thickness: 1/2" - 1"

Operating Temp: -4°F to 104°F (-20°C to 40°C)

Standards: UL, cUL, Damp Location Listed, IC

REPLACEMENT PARTS

REF-R1GW04-BK - Multi Stealth Wall Wash Bevel REF-R1GW04-WT - Multi Stealth Wall Wash Bevel



FINISHES:

Fixture Type:

Project:

Location:

Catalog Number:



Brushed Nickel

Gun Metal

White

LINE DRAWING:

